

N-Channel 40V(D-S) MOSFET

GENERAL DESCRIPTION

The HM23185 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance.

FEATURES


- $R_{DS(ON)} \leq 28m\Omega @ V_{GS}=10V$
- $R_{DS(ON)} \leq 38m\Omega @ V_{GS}=4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- Capable doing Cu wire bonding

APPLICATIONS


- Power Management in Note book
- Portable Equipment
- Battery Powered System
- Load Switch
- DSC

Absolute Maximum Ratings (TA=25°C Unless Otherwise Noted)

Parameter	Symbol	Maximum Ratings	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	±20	V



SOT-23 @top view



Schematic diagram

N-Channel 40V(D-S) MOSFET

.....

..

Electrical Characteristics ($T_j=25^{\circ}\text{C}$ Unless Otherwise Specified)

Symbol	Parameter	Limit	Min	Typ	Max	Unit
STATIC						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250 μA	40			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250 μA	1.0		2.5	V
I _{GSS}	Gate Body Leakage	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =40V, V _{GS} =0V			1	μA
R _{DS(ON)}	Drain-Source On-Resistance	V _{GS} =10V, I _D =1.0A			28	mΩ
		V _{GS} =4.5V, I _D =3.5A			38	
V _{SD}	Diode Forward Voltage	I _S =1A		0.8	1.2	V
DYNAMIC						
Q _g	Total Gate Charge	V _{DS} =20V, V _{GS} =10V, I _D =1 A		16		nC
Q _g	Total Gate Charge	V _{DS} =20V, V _{GS} =4.5V, I _D =1 A		8.2		
Q _{gs}	Gate-Source Charge			3.6		
Q _{gd}	Gate-Drain Charge			3.9		
C _{iss}	Input capacitance	V _{DS} =20V, V _{GS} =0V, f=1MHz		560		pF
C _{oss}	Output Capacitance			70		
C _{rss}	Reverse Transfer Capacitance			22		
R _g	Gate Resistance	f =1MHz		0.7		Ω
t _{d(on)}	Turn-On Delay Time	V _{DD} =20V, R _L =20Ω I _D =1A, V _{GEN} =10V R _G =1Ω		12		ns
t _r	Turn-On Rise Time			12		
t _{d(off)}	Turn-Off Delay Time			37		
t _f	Turn-Off Fall Time			4		







Notes: a. Based on epoxy or solder paste and bond wire Cu 2mil×3(S), Au 1mil ×1(G) on each die of SOT-1 JES package.

b. Pulse test; pulse width ≤ 300us, duty cycle ≤ 2%.

c. H&M SEMI reserves the right to improve product design, functions and reliability without notice.



Typical Characteristics (T_J =25°C Noted)

N-Channel 40V(D-S) MOSFET




Typical Characteristics (T_J = 25°C Noted)

N-Channel 40V(D-S) MOSFET



.....
SOT!, - !' @PACKAGE INFORMATION

SOT-89-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047

Notes

1. All dimensions are in millimeters.
2. Tolerance $\pm 0.10\text{mm}$ (4 mil) unless otherwise specified
3. Package body sizes exclude mold flash and gate burrs. Mold flash at the non-lead sides should be less than 5 mils.
4. Dimension L is measured in gauge plane.
5. Controlling dimension is millimeter, converted inch dimensions are not necessarily exact.