



HMBTA13

NPN EPITAXIAL PLANAR TRANSISTOR

Description

Darlington Amplifier Transistor


Absolute Maximum Ratings

- Maximum Temperatures
Storage Temperature..... -55 ~ +150 °C
Junction Temperature..... +150 °C Maximum
- Maximum Power Dissipation
Total Power Dissipation ($T_A=25^{\circ}\text{C}$)..... 350 mW
- Thermal Resistance
Junction To Ambient $R_{\theta ja}$ 357 °C/mW
Junction To Ambient $R_{\theta jc}$ 170 °C/mW
- Maximum Voltages and Currents ($T_A=25^{\circ}\text{C}$)
 V_{CBO} Collector to Base Voltage 30 V
 V_{CES} Collector to Emitter Voltage 30 V
 V_{EBO} Emitter to Base Voltage 10 V
 I_C Collector Current 300 mA

Electrical Characteristics ($T_A=25^{\circ}\text{C}$)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV_{CBO}	30	-	-	V	$I_C=100\mu\text{A}$
BV_{CES}	30	-	-	V	$I_C=100\mu\text{A}$
BV_{EBO}	10	-	-	V	$I_E=10\mu\text{A}$
I_{CBO}	-	-	100	nA	$V_{CB}=30\text{V}$
I_{EBO}	-	-	100	nA	$V_{EB}=10\text{V}$
$*V_{CE(sat)}$	-	-	1.5	V	$I_C=100\text{mA}$, $I_B=0.1\text{mA}$
$V_{BE(on)}$	-	-	2.0	V	$V_{CE}=5\text{V}$, $I_C=100\text{mA}$
$*h_{FE1}$	5K	-	-		$V_{CE}=5\text{V}$, $I_C=10\text{mA}$
$*h_{FE2}$	10K	-	-		$V_{CE}=5\text{V}$, $I_C=100\text{mA}$
f_T	125	-	-	MHz	$V_{CE}=5\text{V}$, $I_C=10\text{mA}$, $f=100\text{MHz}$
Cob	-	-	6	pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$







*Pulse Test: Pulse Width $\leq 380\mu\text{s}$, Duty Cycle $\leq 2\%$



SOT-23




Characteristics Curve






SOT-23 Dimension



3-Lead SOT-23 Plastic
Surface Mounted Package
HSMC Package Code: N

Marking:



Pb Free Mark
Pb-Free: "●" (Note)
Normal: None

Note: Pb-free product can distinguish by the green label or the extra description on the right side of the label.

Pin Style: 1.Base 2.Emitter 3.Collector

Material:

- Lead solder plating: Sn60/Pb40 (Normal), Sn/3.0Ag/0.5Cu or Pure-Tin (Pb-free)
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

DIM	Min.	Max.
A	2.80	3.04
B	1.20	1.60
C	0.89	1.30
D	0.30	0.50
G	1.70	2.30
H	0.013	0.10
J	0.085	0.177
K	0.32	0.67
L	0.85	1.15
S	2.10	2.75
V	0.25	0.65

*: Typical, Unit: mm

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of HSMC.
- HSMC reserves the right to make changes to its products without notice.
- **HSMC semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- HSMC assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:


- **Head Office** (Hi-Sincerity Microelectronics Corp.): 10F., No. 61, Sec. 2, Chung-Shan N. Rd. Taipei Taiwan R.O.C.
Tel: 886-2-25212056 Fax: 886-2-25632712, 25368454
- **Factory 1:** No. 38, Kuang Fu S. Rd., Fu-Kou Hsin-Chu Industrial Park Hsin-Chu Taiwan. R.O.C
Tel: 886-3-5983621~5 Fax: 886-3-5982931



Soldering Methods for HSMC's Products

1. Storage environment: Temperature=10°C~35°C Humidity=65%±15%
2. Reflow soldering of surface-mount devices

Figure 1: Temperature profile



Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	<3°C/sec	<3°C/sec
Preheat		
- Temperature Min (T_{smin})	100°C	150°C
- Temperature Max (T_{smax})	150°C	200°C
- Time (min to max) (t_s)	60~120 sec	60~180 sec
T_{smax} to T_L		
- Ramp-up Rate	<3°C/sec	<3°C/sec
Time maintained above:		
- Temperature (T_L)	183°C	217°C
- Time (t_L)	60~150 sec	60~150 sec
Peak Temperature (T_P)	240°C +0/-5°C	260°C +0/-5°C
Time within 5°C of actual Peak Temperature (t_P)	10~30 sec	20~40 sec
Ramp-down Rate	<6°C/sec	<6°C/sec
Time 25°C to Peak Temperature	<6 minutes	<8 minutes

3. Flow (wave) soldering (solder dipping)

Products	Peak temperature	Dipping time
Pb devices.	245°C ±5°C	5sec ±1sec
Pb-Free devices.	260°C +0/-5°C	5sec ±1sec