


PNP Silicon Epitaxial Planar Transistor

for switching and amplifier applications. Especially suitable for AF-driver stages and low power output stages.

The transistor is subdivided into two groups, C and D, according to its DC current gain. As complementary type the NPN transistor HN 8050 is recommended.

On special request, these transistors can be manufactured in different pin configurations. Please refer to the "TO-92 TRANSISTOR PACKAGE OUTLINE" on page 80 for the available pin options.




TO-92 Plastic Package
Weight approx. 0.18 g
Dimensions in mm

Absolute Maximum Ratings


	Symbol	Value	Unit
Collector Emitter Voltage	-V _{CEO}	25	V
Collector Base Voltage	-V _{CBO}	40	V
Emitter Base Voltage	-V _{EBO}	6	V
Collector Current	-I _C	800	mA
Peak Collector Current	-I _{CM}	1	A
Base Current	-I _B	100	mA
Power Dissipation at T _{amb} = 25 °C	P _{tot}	625 ¹⁾	mW
Junction Temperature	T _j	150	°C
Storage Temperature Range	T _s	-55 to +150	°C

1) Valid provided that leads are kept at ambient temperature at a distance of 2 mm from case

G S P FORM A AVAILABLE**SEMTECH ELECTRONICS LTD.**(wholly owned subsidiary of **HONEY TECHNOLOGY LTD.**)


Characteristics at $T_{amb} = 25^{\circ}\text{C}$

		Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = -1\text{ V}$, $I_C = -100\text{ mA}$	HN 8550C	h_{FE}	120	-	200	-
	HN 8550D	h_{FE}	160	-	300	-
		h_{FE}	60	-	-	-
Collector Cutoff Current at $V_{CB} = -35\text{ V}$		$-I_{CBO}$	-	-	100	nA
Collector Saturation Voltage at $I_C = -500\text{ mA}$, $I_B = -50\text{ mA}$		$-V_{CESat}$	-	-	0.5	V
Base Saturation Voltage at $I_C = -500\text{ mA}$, $I_B = -50\text{ mA}$		$-V_{BESat}$	-	-	1.2	V
Collector Emitter Breakdown Voltage at $I_C = -2\text{ mA}$		$-V_{(BR)CEO}$	25	-	-	V
Collector Base Breakdown Voltage at $I_C = -10\text{ }\mu\text{A}$		$-V_{(BR)CBO}$	40	-	-	V
Emitter Base Breakdown Voltage at $I_E = -100\text{ }\mu\text{A}$		$-V_{(BR)EBO}$	6	-	-	V
Gain Bandwidth Product at $V_{CE} = -5\text{ V}$, $I_C = -10\text{ mA}$, $f = 50\text{ MHz}$		f_T	-	100	-	MHz
Collector Base Capacitance at $V_{CB} = -10\text{ V}$, $f = 1\text{ MHz}$		C_{CBO}	-	12	-	pF
Thermal Resistance Junction to Ambient		R_{thA}	-	-	200 ¹⁾	K/W


¹⁾ Valid provided that leads are kept at ambient temperature at a distance of 2 mm from case**G S P FORM A AVAILABLE****SEMTECH ELECTRONICS LTD.**(wholly owned subsidiary of **HONEY TECHNOLOGY LTD.**)

Admissible power dissipation versus ambient temperature

Valid provided that leads are kept at ambient temperature at a distance of 2 mm from case




Collector current versus base emitter voltage





Pulse thermal resistance versus pulse duration

Valid provided that leads are kept at ambient temperature at a distance of 2 mm from case



Collector cutoff current versus ambient temperature




SEMTECH ELECTRONICS LTD.


(wholly owned subsidiary of **HONEY TECHNOLOGY LTD.**)




DC current gain
versus collector current





Common emitter collector
characteristics



Common emitter collector
characteristics



Common emitter collector
characteristics



SEMTECH ELECTRONICS LTD.


(wholly owned subsidiary of

HONEY TECHNOLOGY LTD.)




ISO 9002 - 94
Certified No. 040-0554



Collector saturation voltage
versus collector current



Gain bandwidth product
versus collector current



Base saturation voltage
versus collector current



SEMTECH ELECTRONICS LTD.

(wholly owned subsidiary of **HONEY TECHNOLOGY LTD.**)

