


HAOPIN MICROELECTRONICS CO.,LTD.

Description

Passivated, sensitive gate triacs in a plastic envelope, intended for use in general purpose bidirectional switching and phase control applications, where high sensitivity is required in all four quadrants.

<p>Symbol</p> 		<p>Simplified outline</p> 	
Pin	Description		
1	Main terminal 1 (T1)		
2	Main terminal 2 (T2)		
3	gate (G)		
TAB	Main terminal 2 (T2)		

Applications:

- ◆ Motor control
- ◆ Industrial and domestic lighting
- ◆ Heating
- ◆ Static switching

Features

- ◆ Blocking voltage to 600 V
- ◆ On-state RMS current to 12 A

SYMBOL	PARAMETER	Value	Unit
V_{DRM}	Repetitive peak off-state voltages	600	V
$I_{T(RMS)}$	RMS on-state current	12	A
I_{TSM}	Non-repetitive peak on-state current	95	A

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
R_{thj-mb}	Thermal resistance Junction to mounting base	Full cycle	-	-	1.5	K/W
		Half cycle	-	-	2.0	K/W
R_{thj-a}	Thermal resistance Junction to ambient	In free air	-	60	-	K/W



HP12T60RT

Sensitive Gate Triacs

HAOPIN MICROELECTRONICS CO.,LTD.

Limiting values in accordance with the Maximum system(IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN	Value	UNIT	
V_{DRM}	Repetitive peak off-state Voltages		-	600	V	
$I_{T(RMS)}$	RMS on-state current	Full sine wave; $T_{mb} \leq 99^\circ C$	-	12	A	
I_{TSM}	Non-repetitive surge peak on-state current	full sine wave; $T_j = 25^\circ C$ prior to surge	t=20ms	-	95	A
			t=16.7ms	-	105	A
I^2t	I^2t for fusing	T=10ms	-	45	A ² S	
di_T/dt	Repetitive rate of rise of on-state current after triggering	$I_{TM}=20A; I_G=0.2A;$ $DI_G/dt=0.2A/\mu s$	T2+G+	-	50	A/ μs
			T2+G-	-	50	A/ μs
			T2-G-	-	50	A/ μs
			T2-G+	-	10	A/ μs
I_{GM}	Peak gate current		-	2	A	
V_{GM}	Peak gate voltage		-	5	V	
P_{GM}	Peak gate power		-	5	W	
$P_{G(AV)}$	Average gate power	Over any 20 ms period	-	0.5	W	
T_{stg}	Storage temperature		-40	150	$^\circ C$	
T_j	Operating junction Temperature		-	125	$^\circ C$	







$T_j=25^\circ C$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT	
Static characteristics							
I_{GT1}	Gate trigger current	$V_D=12V; I_T=0.1A$	T2+G+	-	1.3	5	mA
			T2+G-	-	2.8	5	mA
			T2-G-	-	3.2	5	mA
			T2-G+	-	5.5	10	mA
I_L	Latching current	$V_D=12V; I_{GT}=0.1A$	T2+G+	-	-	15	mA
			T2+G-	-	-	20	mA
			T2-G-	-	-	15	mA
			T2-G+	-	-	20	mA
I_H	Holding current	$V_D=12V; I_{GT}=0.1A$	-	-	10	mA	
V_T	On-state voltage	$I_T=15A$	-	1.4	1.65	V	
V_{GT}	Gate trigger voltage	$V_D=12V; I_T=0.1A$ $V_D=V_{DRM}; I_T=0.1A; T_j=125^\circ C$	-	0.7	1.5	V	
			0.25	0.4	-	V	
I_D	Off-state leakage current	$V_D=V_{DRM(max)}; T_j=125^\circ C$	-	0.1	0.5	mA	







Dynamic Characteristics

dV_D/dt	Critical rate of rise of Off-state voltage	$V_{DM}=67\% V_{DRM(max)}; T_j=110^\circ C;$ Exponential wave form; gate open circuit	-	50	-	V/ μs
t_{gt}	Gate controlled turn-on time	$I_{TM}=16A; V_D=V_{DRM(max)}; I_G=0.1A;$ $DI_G/dt=5A/\mu s$	-	2	-	μs

Description



Description





HP12T60RT

Sensitive Gate Triacs

HAOPIN MICROELECTRONICS CO.,LTD.

MECHANICAL DATA

Dimensions in mm
Net Mass: 2 g

