





PIN CONNECTIONS

1	2	3	4	5
DATA	W/R	CS	VCC	GND

NOTE:

DISPLAY TYPE : TN REFLECTIVE-POSITIVE
 VIEWING DIRECTION : 6: 00
 OPERATING VOLT. : VDD=3.3V;VOP=3.3V
 OPERATING TEMP. : -25℃ ~ +85℃
 STORAGE TEMP. : -30℃ ~ +90℃
 DRIVE METHOD : 1/4 DUTY 1/3BIAS
 DRIVE IC : HT1621

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
COM1	T	1D	C	2D	A	3D	--	4D	--	5D	DPO	6D	--	7D	COM1	--	--	--
COM2	1E	1C	2E	2C	3E	3C	4E	4C	5E	5C	6E	6C	7E	7C	--	COM2	--	--
COM3	1G	1B	2G	2B	3G	3B	4G	4B	5G	5B	6G	6B	7G	7B	--	COM3	--	--
COM4	1F	1A	2F	2A	3F	3A	4F	4A	5F	5A	6F	6A	7F	7A	--	--	COM4	--

原材料清单:

- 1.LCD 27*14*2.0MAX
- 2.FFC 25.0*6.0*0.3
- 3.PCB 28*16.8*0.6
- 4.IC HT1621
- 5.金属PIN 18根

TOLERANCE		HTDISPLAY CO., LTD.				DRAWING No. : HS0012C-NR63N-VA	
>0~6	±0.10					DRAWING TITLE: LCD MODULE	
>6~80	±0.20	DESIGN	ZOUYS	06.02.15	STANDARD	REV. : A	SCALE : -
>80~240	±0.30	CHECKED			TECHNOLOGY	PROJECTION:	UNIT : MM
>240~400	±0.50	APPROVED			Q.A		1/1
// ± ⊙ ±0.10							