



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	1/24
Document No.	DC110-000495	Revision	1.1

TO :

Date : April,8, 2008

HannStar Product Specification **(Preliminary)**

7" Color TFT-LCD Module

Model : HSD070IDW1-A**

- Note:1.Please contact HannStar Display Corp. before designing your product based on this module specification.
- 2.The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by HannStar for any intellectual property claims or other problems that may result from application based on the module described herein.
- 3.The mark “ ** ” of Model means sub-model code.



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	2/24
Document No.	DC110-000495	Revision	1.1

Record of Revisions

Rev.	Date	Sub-Model	Description of change
1.1	Apr, 08, 2008	- -	Preliminary Product Specification was first issued.



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	3/24
Document No.	DC110-000495	Revision	1.1

Contents

1.0	General description	p.4
2.0	Absolute maximum ratings	p.5
3.0	Optical characteristics	p.6
4.0	Block diagram	p.10
5.0	Interface pin connection	p.11
6.0	Electrical characteristics	p.13
7.0	Reliability test items.....	p.19
8.0	Outline dimension	p.20
9.0	Lot mark	p.21
10.0	Package specification	p.22
11.0	General precaution	p.23

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	4/24
Document No.	DC110-000495	Revision	1.1

1.0 GENERAL DESCRIPTION

1.1 Introduction

HannStar Display model HSD070IDW1-A is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT LCD panel, a driving circuit and a back light system. This TFT LCD has a 7.0 (16:9) inch diagonally measured active display area with 2400 x 480 dot (800 horizontal by 480 vertical pixel) resolution.

1.2 Features

- 7 (16:9 diagonal) inch configuration
- 6 bits + FRC driver with 1channel TTL interface
- RoHS Compliance

1.3 Applications

- Mobile NB
- Digital Photo frame
- Multimedia applications and Others AV system

1.4 General information

Item		Specification	Unit
Outline Dimension		165.0 x 104.0 x 5.1 (Typ.)	mm
Display area		153.6(H) x 86.64(V)	mm
Number of Pixel		800 RGB(H) x 480(V)	pixels
Pixel pitch		0.192(H) x 0.1805(V)	mm
Pixel arrangement		RGB Vertical stripe	
Display mode		Normally white	
Surface treatment		Antiglare, Hard-Coating(3H) with EWV film	
Weight		(130) (Typ.)	g
Back-light		Single LED (Side-Light type)	
Power Consumption	B/L System	(1.68)(Max.)	W

1.5 Mechanical Information

Item		Min.	Typ.	Max.	Unit
Module Size	Horizontal(H)	164.7	165.0	165.3	mm
	Vertical(V)	103.7	104.0	104.3	mm
	Depth(D)	—	5.1	5.4	mm
Weight (Without inverter)		—	(130)	—	g

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	5/24
Document No.	DC110-000495	Revision	1.1

2.0 ABSOLUTE MAXIMUM RATINGS

2.1 Electrical Absolute Rating

2.1.1 TFT LCD Module

Item	Symbol	Min.	Max.	Unit	Note
Power supply voltage	V _{CC}	-0.3	5.0	V	GND=0
	V _{GH}	TBD	TBD	V	GND=0
	V _{GL}	TBD	TBD	V	GND=0
	AV _{DD}	TBD	TBD	V	AGND=0
	V _{COM}	TBD	TBD	V	
Logic Signal Input Level	V _I	-0.3	V _{CC} +0.3	V	

2.1.2 Back-Light Unit

Item	Symbol	Typ.	Max.	Unit	Note
LED current	I _L	140	—	mA	(1) (2)
LED voltage	V _L	9.9	12	V	(1) (2)(3)

Note

- (1) Permanent damage may occur to the LCD module if beyond this specification. Functional operation should be restricted to the conditions described under normal operating conditions.
- (2) Ta =25±2℃
- (3) Test Condition: LED current 140 mA

2.2 Environment Absolute Rating

Item	Symbol	Min.	Max.	Unit	Note
Operating Temperature	T _{opa}	-20	70	℃	
Storage Temperature	T _{stg}	-30	80	℃	

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	6/24
Document No.	DC110-000495	Revision	1.1

3.0 OPTICAL CHARACTERISTICS

3.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast		CR	Normal viewing angle	400	500	—	msec	(1)(2)
Response time	Rising	T _R		—	5	7		(1)(3)
	Falling	T _F		—	20	28		
White luminance (Center)		Y _L		160	200	—	cd/m ²	(1)(4) (I _L =140mA)
Color chromaticity (CIE1931)	White	W _x		0.260	0.310	0.360		(1)(4)
		W _y	0.280	0.330	0.380			
Viewing angle	Hor.	Θ _L	CR>10	TBD	70	—		
		Θ _R		TBD	70	—		
	Ver.	Θ _U		TBD	50	—		
		Θ _D		TBD	60	—		
Brightness uniformity		B _{UNI}	Θ=0	70	—	—	%	(5)(7)
Optima View Direction		6 O' clock						(6)

3.2 Measuring Condition


- Measuring surrounding : dark room
- LED current I_L : 140mA
- Ambient temperature : $25\pm 2^\circ C$
- 15min. warm-up time.

3.3 Measuring Equipment

- FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.
- Measuring spot size : 20 ~ 21 mm

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	7/24
Document No.	DC110-000495	Revision	1.1

Note (1) Definition of Viewing Angle :




Note (2) Definition of Contrast Ratio(CR) :
measured at the center point of panel


$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	8/24
Document No.	DC110-000495	Revision	1.1

Note (3) Definition of Response Time : Sum of T_R and T_F




Note (4) Definition of optical measurement setup



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	9/24
Document No.	DC110-000495	Revision	1.1

Note (5) Definition of brightness uniformity



$$\text{Luminance uniformity} = \frac{(\text{Min Luminance of 9 points})}{(\text{Max Luminance of 9 points})} \times 100\%$$


Note (6) Rubbing Direction (The different Rubbing Direction will cause the different Optimal view direction.

Note (7) Measured at the brightness of the panel when all terminals of LCD panel are electrically open.


Document Title	HSD070IDW1-A Preliminary Specification	Page No.	10/24
Document No.	DC110-000495	Revision	1.1

4.0 BLOCK DIAGRAM

4.1 TFT LCD Module



4.2 Pixel Format



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	11/24
Document No.	DC110-000495	Revision	1.1

5.0 INTERFACE PIN CONNECTION

5.1 TFT LCD Module

CN2 (Input signal): FPC Down Connector, (FH28-60S-0.5SH (HIROSE),60pin,pitch = 0.5mm)

Terminal no.	Symbol	I/O	Function
1	AGND	P	Analog Ground
2	AVDD	P	Analog Power
3	VCC	P	Digital Power
4	R0	I	Data Input(LSB)
5	R1	I	Data Input
6	R2	I	Data Input
7	R3	I	Data Input
8	R4	I	Data Input
9	R5	I	Data Input
10	R6	I	Data Input
11	R7	I	Data Input(MSB)
12	G0	I	Data Input(LSB)
13	G1	I	Data Input
14	G2	I	Data Input
15	G3	I	Data Input
16	G4	I	Data Input
17	G5	I	Data Input
18	G6	I	Data Input
19	G7	I	Data Input(MSB)
20	B0	I	Data Input(LSB)
21	B1	I	Data Input
22	B2	I	Data Input
23	B3	I	Data Input
24	B4	I	Data Input
25	B5	I	Data Input
26	B6	I	Data Input
27	B7	I	Data Input(MSB)
28	DCLK	I	Clock input
29	DE	I	Data Enable signal
30	HSD	I	Horizontal sync input.Negative polarity
31	VSD	I	Vertical sync input.Negative polarity
32	MODE3	I	DE/SYNC mode select .normally pull high H:DE mode.L:HSD/VSD mode
33	RSTB	I	global reset pin.Active low to enter reset state.suggest to connecting with an RC reset circuit for stability .normally pull high.
34	STBYB	I	standby mode,normally pull high STBYB="1",normal operation STBYB="0",timming control ,source driver will turn off,all output are high-Z
35	SHLR	I	Source right or left sequence control.SHLR="L",shift left:last data=S1<-S2...S1200=first data SHLR="H",shift right:first data=S1->SS2...S1200=last data

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	12/24
Document No.	DC110-000495	Revision	1.1

Terminal no.	Symbol	I/O	Function
36	VCC	P	Digital Power
37	UPDN	I	Shift up or down control. UPDN= "H", up shift: STVD (Input) → G1 ~ G480 → STVU (Output) UPDN = "L", down shift: STVU (Input) → G480 ~ G1 → STVD (Output)
38	GND	P	Digital Ground
39	AGND	P	Analog Ground
40	AVDD	P	Analog Power
41	VCOMin	I	For external VCOM DC input(Optional)
42	DITH	I	Dithering setting DITH="H" 6bit resolution (last 2 bits of input data truncated) DITH="L" 8bit resolution (default setting)
43	BIST	I	Normal operation/BIST pattern select. Normally pull low. BIST=H:BIST(DCLK input is needed) BIST=L: Normal operation
44	VCOM	O	connect a capacitor
45	V10	P	Gamma correction voltage reference
46	V9	P	Gamma correction voltage reference
47	V8	P	Gamma correction voltage reference
48	V7	P	Gamma correction voltage reference
49	V6	P	Gamma correction voltage reference
50	V5	P	Gamma correction voltage reference
51	V4	P	Gamma correction voltage reference
52	V3	P	Gamma correction voltage reference
53	V2	P	Gamma correction voltage reference
54	V1	P	Gamma correction voltage reference
55	NC	-	Not connect
56	VGH	P	Positive Power for TFT
57	VCC	P	Digital Power
58	VGL	P	Negative Power for TFT
59	GND	P	Digital Ground
60	CAP	C	Connected to a capacitor

5.2 Back-Light Unit

CN1 LED Power Source Molex 51021-200

Mating Connector: Aces 85204-02001

Terminal no.	Symbol	Function
1	VL	LED power supply (high voltage)
2	GL	LED power supply (low voltage)

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	13/24
Document No.	DC110-000495	Revision	1.1

6.0 ELECTRICAL CHARACTERISTICS

6.1 TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Supply Voltage	V _{CC}	3.2	3.3	3.6	V	
	V _{GH}	TBD	15	TBD	V	
	V _{GL}	TBD	-7	TBD	V	
	AV _{DD}	TBD	11.6	TBD	V	
VCOM	V _{CDC}	1.472	2.972	4.472	V	
Input signal voltage	V _{iH}	0.7 V _{CC}	-	V _{CC}	V	Note (1)
	V _{iL}	0	-	0.3 V _{CC}	V	
Current of power supply	I _{DD}	-	TBD	-	uA	V _{CC} =3.3V
	I _{ADD}	-	TBD	-	mA	AV _{DD} =11.6V(Black)
	I _{GH}	-	TBD	-	uA	V _{GH} =15V
	I _{GL}	-	TBD	-	uA	V _{GL} = 7V
Input level of V1~V5	V _x	-	TBD	-	V	
Input level of V6~V10	V _x	-	TBD	-	V	

Note (1): HSYNC , VSYNC , DE , Digital Data

Note (2): Be sure to apply the power voltage as the power sequence spec.

Note (3): DGND=AGND=0V,)


Document Title	HSD070IDW1-A Preliminary Specification	Page No.	14/24
Document No.	DC110-000495	Revision	1.1

6.2 Back-Light Unit

The back-light system is an edge-lighting type with 21 LED.

The characteristics of the LED is shown in the following tables.

Item	Symbol	Min.	Typ.	Max.	Unit	Note
LED current	IL	—	140	—	mA	
LED voltage	VL	—	9.9	12	V	
Operating LED life time	Hr	20,000	—	—	Hour	(1)



Note (1) LED life time (Hr) can be defined as the time in which it continues to operate under the condition : $T_a=25\pm3^{\circ}\text{C}$, typical IL value indicated in the above table until the brightness becomes less than 50%.



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	15/24
Document No.	DC110-000495	Revision	1.1

6.3 AC Characteristics


Item	Symbol	Min.	Typ.	Max.	Unit	Note
DCLK cycle time	Tcph	37			ns	
DCLK frequency	fclk		25	27	MHz	
DCLK pulse duty	Tcwh	40	50	60	%	
VSD setup time	Tvst	8			ns	
VSD hold time	Tvhd	8			ns	
HSD setup time	Thst	8			ns	
HSD hold time	Thhd	8			ns	
Data setup time	Tdsu	24			ns	
Data hold time	Tdhd	8			ns	
DE setup time	Tesu	8			ns	
DE hold time	Tehd	8			ns	
Horizontal display area	thd		800		Tcph	
HSD period time	th		828		Tcph	
HSD pulse width	thpw	1	16		Tcph	
HSD back porch	thb		16		Tcph	
HSD front porch	thfp		12		Tcph	
Vertical display area	tvd		480		th	
VSD period time	tv		504		th	
VSD pulse width	tvpw		3		th	
VSD back porch	tvb		16		th	
VSD front porch	tvfp		8		th	

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	16/24
Document No.	DC110-000495	Revision	1.1

6.4 Timing Diagram of Interface Signal




Document Title	HSD070IDW1-A Preliminary Specification	Page No.	17/24
Document No.	DC110-000495	Revision	1.1




Vertical timing

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	18/24
Document No.	DC110-000495	Revision	1.1

6.5 Power Sequence



$T_0 < 20 \text{ ms}$ $T_3 > 20 \text{ ms}$
 $T_1 > 100 \mu\text{s}$ $T_4 > 10 \text{ ms}$
 $T_2 > 16 \text{ ms}$



Power On Sequence: $V_{DD} \rightarrow AVDD \rightarrow VGL \rightarrow VGH$

Power Off Sequence: $VGH \rightarrow VGL \rightarrow AVDD \rightarrow V_{DD}$

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	19/24
Document No.	DC110-000495	Revision	1.1

7.0 Reliability test items

No.	Item	Conditions	Remark
1	High Temperature Storage	Ta=+80°C, 240hrs	
2	Low Temperature Storage	Ta=-30°C, 240hrs	
3	High Temperature Operation	Ta=+70°C, 240hrs	
4	Low Temperature Operation	Ta=-20°C, 240hrs	
5	High Temperature and High Humidity (operation)	Ta=+60°C, 90%RH, 240hrs	
6	Thermal Cycling Test (non operation)	-30°C(30min) → +80°C(30min), 200cycles	
7	Electrostatic Discharge	±200V,200pF(0Ω) 1 time/each terminal	
8	Vibration	1.Random: 1.04Grms, 10~500Hz, X/Y/Z, 30min/each direction 2.Sweep sine: 1.5G, 5~500Hz, X/Y/Z, 30min/each direction	
9	Shock	100G,6ms, ±X, ±Y, ±Z 3 time for each direction	JIS C7021, A-10 (Condition A)
10	Vibration (with carton)	Random: 1.04Grms, 10~500Hz, X/Y/Z 45min/each direction Fixed: 5Hz, 1.5Grms, X/Y/Z 45min/each direction	
11	Drop (with carton)	Height: 60cm 1 corner, 3 edges, 6 surfaces	JIS Z0202




Note: There are no display function NG issue occurred, All the cosmetic specification is judged before the reliability stress.

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	20/24
Document No.	DC110-000495	Revision	1.1

8.0 OUTLINE DIMENSION

8.1 Outline Dimension

Unit : mm



<P> BM 寬縱向 | A-A' |

<Q> BM 寬橫向 | B-B' |

Note : 1.General tolerance : +/- 0.3 mm

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	21/24
Document No.	DC110-000495	Revision	1.1

9.0 LOT MARK

9.1 Lot Mark

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----

code 1,2,3,4,5,6: HannStar internal flow control code.

code 7: production location.

code 8: production year.

code 9: production month.

code 10,11,12,13,14,15: serial number.

Note (1) Production Year

Year	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008
Mark	9	0	1	2	3	4	5	6	7	8


Note (2) Production Month

Month	Jan.	Feb.	Mar.	Apr.	May.	Jun.	Jul.	Aug.	Sep.	Oct	Nov.	Dec.
Mark	1	2	3	4	5	6	7	8	9	A	B	C

9.2 Location of Lot Mark

(1) The label is attached to the backside of the LCD module.

(2) This is subject to change without prior notice.




Document Title	HSD070IDW1-A Preliminary Specification	Page No.	22/24
Document No.	DC110-000495	Revision	1.1

10.0 PACKAGE SPECIFICATION

10.1 packing form

- (1) Package quantity in one carton: 60 pieces.
- (2) Carton size: 464 ± 3 mm $\times$ 360 ± 3 mm $\times$ 370 ± 3 mm.
- (3) For domestic transportation only.

10.2 packing assembly drawings



Document Title	HSD070IDW1-A Preliminary Specification	Page No.	23/24
Document No.	DC110-000495	Revision	1.1

11.0 GENERAL PRECAUTION

11.1 Use Restriction

This product is not authorized for use in life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life-threatening or otherwise catastrophic.

11.2 Disassembling or Modification

Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. HannStar does not warrant the module, if customers disassemble or modify the module.

11.3 Breakage of LCD Panel

11.3.1. If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid crystal, and do not contact liquid crystal with skin.

11.3.2. If liquid crystal contacts mouth or eyes, rinse out with water immediately.

11.3.3. If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and rinse thoroughly with water.

11.3.4. Handle carefully with chips of glass that may cause injury, when the glass is broken.

11.4 Electric Shock

11.4.1. Disconnect power supply before handling LCD module.

11.4.2. Do not pull or fold the LED cable.

11.4.3. Do not touch the parts inside LCD modules and the fluorescent LED's connector or cables in order to prevent electric shock.

11.5 Absolute Maximum Ratings and Power Protection Circuit

11.5.1. Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature, etc., otherwise LCD module may be damaged.

11.5.2. Please do not leave LCD module in the environment of high humidity and high temperature for a long time.

11.5.3. It's recommended to employ protection circuit for power supply.

11.6 Operation

11.6.1 Do not touch, push or rub the polarizer with anything harder than HB pencil lead.

11.6.2 Use fingerstalls of soft gloves in order to keep clean display quality, when persons handle the LCD module for incoming inspection or assembly.

11.6.3 When the surface is dusty, please wipe gently with absorbent cotton or other soft material.

Document Title	HSD070IDW1-A Preliminary Specification	Page No.	24/24
Document No.	DC110-000495	Revision	1.1

11.6.4 Wipe off saliva or water drops as soon as possible. If saliva or water drops contact with polarizer for a long time, they may causes deformation or color fading.

11.6.5 When cleaning the adhesives, please use absorbent cotton wetted with a little petroleum benzine or other adequate solvent.

11.7 Mechanism

Please mount LCD module by using mouting holes arranged in four corners tightly.

11.8 Static Electricity

11.8.1 Protection film must remove very slowly from the surface of LCD module to prevent from electrostatic occurrence.

11.8.2. Because LCD module use CMOS-IC on circuit board and TFT-LCD panel, it is very weak to electrostatic discharge. Please be careful with electrostatic discharge. Persons who handle the module should be grounded through adequate methods.

11.9 Strong Light Exposure

The module shall not be exposed under strong light such as direct sunlight. Otherwise, display characteristics may be changed.

11.10 Disposal

When disposing LCD module, obey the local environmental regulations.