



## NON INSULATED TYPE TRIAC (TO-220F PACKAGE)

### Features

- \* Repetitive Peak Off-State Voltage: 800V
- \* R.M.S On-state Current( $I_{T(RMS)}=8A$ )
- \* High Commutation  $dv/dt$

### General Description



The Triac HTP8A80 is suitable for AC switching application, phase control application such as heater control, motor control, lighting control, and static switching relay.









### Absolute Maximum Ratings ( $T_a=25$ )

$T_{stg}$ —Storage Temperature.....	-40~125
$T_j$ —Operating Junction Temperature .....	-40~125
$P_{GM}$ —Peak Gate Power Dissipation.....	5W
$V_{DRM}$ —Repetitive Peak Off-State Voltage.....	800V
$I_T$ ( RMS )—R.M.S On-State Current ( $T_a=105$ ) .....	8A
$V_{GM}$ —Peak Gate Voltage.....	10V
$I_{GM}$ —Peak Gate Current.....	2.0A
$I_{TSM}$ —Surge On-State Current (One Cycle, 50/60Hz,Peak,Non-Repetitive).....	80/88A

### Electrical Characteristics ( $T_a=25$ )

Symbol	Items	Min.	Typ.	Max.	Unit	Conditions
$I_{DRM}$	Repetitive Peak Off-State Current			2.0	mA	$V_D=V_{DRM}$ , Single Phase,Half Wave, $T_j=125$
$V_{TM}$	Peak On-State Voltage			1.4	V	$I_T=12A$ , Inst. Measurement
$I_{+GT1}$	Gate Trigger Current ( )			30	mA	$V_D=6V$ , $R_L=10$ ohm
$I_{-GT1}$	Gate Trigger Current ( )			30	mA	$V_D=6V$ , $R_L=10$ ohm
$I_{-GT3}$	Gate Trigger Current ( )			30	mA	$V_D=6V$ , $R_L=10$ ohm
$V_{+GT1}$	Gate Trigger Voltage ( )			1.5	V	$V_D=6V$ , $R_L=10$ ohm
$V_{-GT1}$	Gate Trigger Voltage ( )			1.5	V	$V_D=6V$ , $R_L=10$ ohm
$V_{-GT3}$	Gate Trigger Voltage ( )			1.5	V	$V_D=6V$ , $R_L=10$ ohm
$V_{GD}$	Non-Trigger Gate Voltage	0.2			V	$T_j=125$ , $V_D=1/2V_{DRM}$
$(dv/dt)_c$	Critical Rate of Rise of Off-State Voltage at Commutation	10			V/ $\mu$ S	$T_j=125$ , $V_D=400V$ $(di/dt)_c=-4A/ms$
$I_H$	Holding Current		15		mA	
$R_{th(j-c)}$	Thermal Resistance			3.7	/W	Junction to case







**Trigger mode of the triac**

