


Silicon Epitaxial Trench Pin Diode

HVC136

■ Features

- Adopting the trench structure improves low capacitance.(C = 0.45 pF max)
- Low forward resistance. ($r_f=2.5\ \Omega$ max)
- Low operation current.

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Value	Unit
Peak reverse voltage	V_{RM}	65	V
Reverse voltage	V_R	60	V
Forward current	I_F	100	mA
Power dissipation	P_d	150	mW
Junction temperature	T_j	125	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +125	$^\circ\text{C}$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse current	I_R	$V_R = 60\text{ V}$			0.1	μA
Reverse voltage	V_F	$I_F = 2\text{ mA}$			0.9	V
Capacitance	C	$V_R = 1\text{ V}, f = 1\text{ MHz}$			0.45	pF
Forward resistance	r_f	$I_F = 2\text{ mA}, f = 100\text{ MHz}$			2.5	Ω
ESD-Capability *1		C =200pF, Both forward and reverse direction 1 pulse	100			V

Note

1. Failure criterion ; $I_R > 100\text{ nA}$ at $V_R = 60\text{ V}$.

■ Marking

Marking	P6
---------	----