


• H HiTRON

UNIVERSAL INPUT AC-DC OPEN FRAME SINGLE & MULTI-OUTPUT 72 WATTS INTERNAL SWITCHING POWER SUPPLIES HVI72 SERIES



FEATURES:

- ACCOMMODATE UNIVERSAL AC SOURCES
- OPEN FRAME OR BOX FORMATS
- LOW COST COMMERCIAL GRADE
- MEET UNIVERSAL SAFETY STANDARDS
- EMI MEET CISPR PUB. 22 & FCC CLASS B
- CE MARKING COMPLIANCE

SPECIFICATION

INPUT SPECIFICATION

Input Voltage: Range 90-264Vac.
Rating 100 to 240Vac.
Input Connector: B-S or V-M connectors.
Input Frequency: 47-63Hz.
Inrush Current: Typ. 25A peak @230Vac.
Input Current: Typ. 2.0A @115Vac, 0.6 A @230Vac.
Dielectric Withstand: Meet IEC 60950-1.
EMI: Meet CISPR PUB. 22 & FCC Class B.
No Load Operation: No damage.
Overshoot: No voltage spike while power ON/OFF.
Hold-up Time: Typ. 20mS @115Vac, 80mS @230Vac.
Earth Leakage: Less than 0.5mA @230Vac.

OUTPUT SPECIFICATION

Output Voltage: See Ratings Chart.
Output Current: See Rating Chart.
Output Connector: B-S or V-M connector.
Output Wattage: Typ. 72 Watts.
Line Regulation: Typ. 0.1%.
Load Regulation: Main VO1 typ. $\pm 1.0\%$.
Aux. VO2 typ. $\pm 3.0\%$. (stacked on)
Aux. VO3/VO4 typ. $\pm 2.0\%$. (P.R.)
Noise & Ripple: Typ. 1.0% peak to peak.
OVP: Built-in at main VO1 (Latch).
Adjustability: Available at main VO1.
LED Indicator: Output indicating.
Overload Protection (OLP):
Fully protected against output overload and short circuit.
OLP set at about 125-150% rating output wattage.
Consult the factory for OLP setting.

GENERAL SPECIFICATION

Efficiency: Typ. 72%.
Switching Frequency: Fixed frequency 45K Hz.
Circuit Topology: Fixed Frequency Flyback Circuit.
Transient Response: Output voltage returns in less than 3mS following a 25% load change.
Safety Standard: UL 60950-1/EN 60950-1 Class I.
Operating Temperature: 0 to +50°C.
Storage Temperature: -20 to +85°C.
Temperature Coefficient: Typ. 0.03% /°C.
Cooling: Free air convection cooling.
Construction format: L-Bracket or enclosure box format.
Power Density: 2.0 Watts / Cubic Inch.

Note: Due to requests in market and advances in technology, specifications subject to change without notification.



In application

OUTPUT VOLTAGE / CURRENT RATINGS CHART

SINGLE OUTPUT

MODEL NO.	MAIN VO1 @★
	Typ. Volt.
HVI72-10	14.0A 5.0V
HVI72-11	6.0A 12.0V
HVI72-12	4.8A 15.0V
HVI72-13	3.0A 24.0V
HVI72-14	2.3A 32.0V
HVI72-15	1.6A 48.0V
HVI72-19	14.0A 3.3V

TRIPLE OUTPUT

MODEL NO.	MAIN VO1 @★	AUX. +VO2 †	AUX. ±VO3 ●
	Typ. Volt.	Typ. Volt.	Typ. Volt.
HVI72-30	7.0A +5V	2.0A +12V	1.0A 12V
HVI72-31	7.0A +5V	2.0A +12V	1.0A 5V
HVI72-32	7.0A +5V	1.0A +24V	1.0A 12V
HVI72-33	7.0A +5V	1.5A +15V	1.0A 15V
HVI72-050060-BG	6.0A +5V	2.0A +12V	1.0A -12V

QUAD OUTPUT

MODEL NO.	MAIN VO1 @★	AUX. +VO2 †	AUX. ±VO3 ●	AUX. -VO4 ●
	Typ. Volt.	Typ. Volt.	Typ. Volt.	Typ. Volt.
HVI72-40	6.5A +5V	2.0A +12V	0.5A 12V	0.5A -12V
HVI72-41	6.5A +5V	2.0A +12V	1.0A 5V	1.0A -5V
HVI72-42	6.5A +5V	1.0A +24V	0.5A 12V	0.5A -12V
HVI72-43	6.5A +5V	1.6A +15V	0.5A 15V	0.5A -15V
HVI72-43A	5.0A +5V	1.5A +15V	1.0A -15V	1.0A -5V

Symbol: "★" OVP built-in. "@" Adjustable. "†" Stacked on main O/P. "●" Installed with Post Regulator (P.R.).


Remark: At least 20% of typical main output current is required to maintain stated regulation.

MECHANICAL DIMENSIONS: MM [INCHES]

WEIGHT: L-B 396.0g (13.97 Oz.)

Box 489.0g (1.25 Oz.)

www.DataSheet4U.com



INPUT & OUTPUT CONNECTORS PIN ASSIGNMENT

	AC INPUT			SINGLE OUTPUT		TRIPLE / QUAD OUTPUT				
ASSIGNMENT	AC-LINE	AC-NEUTRAL	AC-GROUND	VO1	DC-COM	VO1	VO2	VO3	VO4	DC-COM
B-S CNTR & PIN#	P1-1	P1-2	P1-3	P1-5	P1-4	P1-8	P1-6	P1-5	P1-4	P1-7
V-M CNTR & PIN#	P2-L	P2-N	P2-G	P3-4,5,6	P3-1,2,3	P3-7,8	P3-3	P3-2	P3-1	P3-4,5

Mating connector: P2 Molex 5195 or 5239 series.