


HX1009

314.85 MHz

Hybrid Transmitter

- Ideal for 314.85 MHz Unlicensed Transmitters
- Transmission Rates of up to 10kbps
- Compact, Surface-Mount Case with <110 mm² Footprint

The HX1009 is a miniature hybrid transmitter designed for data transmission using on-off keyed (OOK) modulation. The transmitter is stabilized by a quartz SAW device for long-term frequency stability. The HX1009 is designed specifically for unlicensed transmitters operating at 314.85 MHz.



Electrical Characteristics

Characteristic		Sym	Notes	Minimum	Typical	Maximum	Units
Operating Frequency	Absolute Frequency	f_O	1, 2, 3, 4, 10	314.65		315.05	MHz
	Tolerance from 314.85 MHz	Δf_O				± 200	kHz
RF Output Power into 50 Ω at 25°C		P_O	2, 4, 5, 10	-3	0		dBm
	Within Specified Temperature Range		2, 3, 4, 5	-5	0		
Harmonic Spurious Emissions			2, 3, 4, 5		-40		dBc
Modulation Input	Input HIGH Voltage	V_{IH}	3, 4, 5	2.5		V_{CC}	V
	Input LOW Voltage	V_{IL}		0.0		0.3	
	Input HIGH Current	I_{IH}			100		μA
	Input LOW Current	I_{IL}		0.0			
Data Timing Parameters	Modulation Rise Time	t_R	3, 4, 5, 6		20		μs
	Modulation Fall Time	t_F			20		
Power Supply	Voltage	V_{CC}	5, 7	2.7	3	3.3	VDC
	Peak Current	I_{CC}	3, 4, 5, 8		7	10	mA
	Standby Current		5, 9		1.0		μA
Operating Case Temperature Range		T_C	5	-40		+85	°C
Lid Symbolization (in addition to Lot and/or Date Codes)		RFM HX1009					



CAUTION: Electrostatic Sensitive Device.
Observe precautions for handling.

NOTES:

1. One or more of the following United States patents apply: 4,454,488; 4,616,197; 4,670,681; and 4,760,352.
2. Typically, equipment utilizing this device requires emissions testing and government approval, which is the responsibility of the equipment manufacturer.
3. Applies over the specified range of operating temperature.
4. Applies over the specified range of operating power supply voltage.
5. The design, manufacturing process, and specifications of this device are subject to change without notice.
6. The maximum modulation bandwidth (and data rate) is dependent on the characteristics of the external encoding circuitry (not included).
7. Unless noted otherwise, case temperature $T_C = +25^\circ C \pm 2^\circ C$, test load impedance = 50 Ω , and modulation input is at logic HIGH.

8. The maximum operating current occurs at the maximum specified power supply voltage and maximum specified operating temperature.
9. Standby current is defined as the supply current consumed with the modulation input at logic LOW.
10. Improper antenna loading affects performance of HX device.


Absolute Maximum Ratings

Rating	Value	Units
Power Supply and/or Modulation Input Voltage	10	V
Nonoperating Case Temperature	-40 to +85	°C
Ten-Second Soldering Temperature	230	°C

The HX Series SMT Hybrid Transmitters


Electrical Connections

Terminal Number	Connections
1	Data Input
2	+DC Supply
3	Ground
4	RF Output to 50 Ω




TOP VIEW

Footprint




Block Diagram




BOTTOM VIEW

Typical Test Circuit




Case Design



Dimensions	Millimeters		Inches	
	Min	Max	Min	Max
A		11.13		0.438
B	1.27 Nominal		0.050 Nominal	
C	2.67 Nominal		0.105 Nominal	
D	5.08 Nominal		0.200 Nominal	
E	1.70 Nominal		0.067 Nominal	
F	5.36 Nominal		0.211 Nominal	
G		2.03		0.110
H		9.86		0.388

*Note: Bypass required only for "HX2..." series transmitters in the 902 to 928 MHz band.

Typical Transmitter Application



Notes:

1. This matching component is required only for antennas that are not 50 ohms. It is typically a chip inductor to match to stub antennas shorter than $\frac{1}{4}$ wavelength. For very low radiated field-strength applications, a resistor can also be used.
2. For ESD protection.