


HYS72T512020HR-[3.7/5]-A

240-Pin Registered-DDR2-SDRAM Modules
DDR2 SDRAM
RoHS Compliant



Internet Data Sheet

Rev. 1.11



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

HYS72T512020HR-[3.7/5]-A	
Revision History: 2006-09, Rev. 1.11	
Page	Subjects (major changes since last revision)
All	Qimonda Update
All	Adapted internet edition
Previous Revision: 2005-05, Rev. 1.0	
27,31	SPD Update
36	Package outline figure updated
Previous Revision: 2005-02, Rev. 0.5	
26, 27	Corrected IDD Currents
26, 27	Removed IDD6(I) from IDD specification tables
Previous Revision: 2005-02, Rev. 0.5	

We Listen to Your Comments

Any information within this document that you feel is wrong, unclear or missing at all?

Your feedback will help us to continuously improve the quality of this document.

Please send your proposal (including a reference to this document) to:

techdoc@qimonda.com



1 Overview

1.1 Features

This chapter contains features and the description

- 240-pin PC2-4200 and PC2-3200 DDR2 SDRAM memory modules for PC, Workstation and Server main memory applications
- Two ranks 512M x 72 module organization with 256M x4 chip organization
- Standard Double-Data-Rate-Two Synchronous DRAMs (DDR2 SDRAM) with a single + 1.8 V (± 0.1 V) power supply
- Built with 1-Gbit DDR2 SDRAMs in P-TFBGA-68 chipsize packages.
- Programmable CAS Latencies (3, 4 & 5), Burst Length (4 & 8) and Burst Type
- Auto Refresh (CBR) and Self Refresh
- All inputs and outputs SSTL_1.8 compatible
- Off-Chip Driver Impedance Adjustment (OCD) and On-Die Termination (ODT)
- Serial Presence Detect with E²PROM
- RDIMM Dimensions (nominal): 50.00 mm high, 133.35 mm wide
- Qimonda Proprietary Raw Card Layout
- RoHS compliant products¹⁾

TABLE 1
Performance for DDR2-533 and DDR2-400

Product Type Speed Code			-3.7	-5	Units
Speed Grade			PC2-4200 4-4-4	PC2-3200 3-3-3	—
Max. Clock Frequency	@CL5	f_{CK5}	266	200	MHz
	@CL4	f_{CK4}	266	200	MHz
	@CL3	f_{CK3}	200	200	MHz
Min. RAS-CAS-Delay		t_{RCD}	15	15	ns
Min. Row Precharge Time		t_{RP}	15	15	ns
Min. Row Active Time		t_{RAS}	45	40	ns
Min. Row Cycle Time		t_{RC}	60	55	ns

1) RoHS Compliant Product: Restriction of the use of certain hazardous substances (RoHS) in electrical and electronic equipment as defined in the directive 2002/95/EC issued by the European Parliament and of the Council of 27 January 2003. These substances include mercury, lead, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated biphenyl ethers.



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

1.2 Description

The Qimonda HYS72T512020HR-[3.7/5]-A module family are Registered DIMM modules "RDIMMs" with 50,0 mm height based on DDR2 technology.

DIMMs are available as ECC modules in 512M x 72 (4 GByte) organization and density, intended for mounting into 240-Pin connector sockets. The memory array is designed with 1-Gbit Double-Data-Rate-Two (DDR2) Synchronous DRAMs. All control and address signals are re-

driven on the DIMM using register devices and a PLL for the clock distribution. This reduces capacitive loading to the system bus, but adds one cycle to the SDRAM timing. Decoupling capacitors are mounted on the PCB board. The DIMMs feature serial presence detect based on a serial E²PROM device using the 2-pin I²C protocol. The first 128 bytes are programmed with configuration data and the second 128 bytes are available to the customer.



TABLE 2
Ordering Information for RoHS Compliant Products

Product Type ¹⁾	Compliance Code ²⁾	Description	SDRAM Technology
PC2-4200			
HYS72T512020HR-3.7-A	4 GB 2R×4 PC2-4200R-444-11-ZZ	2 Ranks, ECC	1 Gbit (×4)
PC2-3200			
HYS72T512020HR-5-A	4 GB 2R×4 PC2-3200R-333-11-ZZ	2 Ranks, ECC	1 Gbit (×4)

- 1) All part numbers end with a place code, designating the silicon die revision. Example: HYS72T512020HR-5-A, indicating Rev. "A" dies are used for DDR2 SDRAM components. For all Qimonda DDR2 module and component nomenclature see **Chapter 6** of this data sheet.
- 2) The Compliance Code is printed on the module label and describes the speed grade, for example "PC2-4200R-444-11-ZZ", where 4200R means Registered DIMM modules with 4.26 GB/sec Module Bandwidth and "444-11" means Column Address Strobe (CAS) latency = 4, Row Column Delay (RCD) latency = 4 and Row Precharge (RP) latency = 4 using the latest JEDEC SPD Revision 1.1 and produced on the Raw Card "ZZ"

TABLE 3
Address Format

DIMM Density	Module Organization	Memory Ranks	ECC/ Non-ECC	# of SDRAMs	# of row/bank/columns bits	Raw Card
4 GB	512M × 72	2	ECC	36	14/3/11	ZZ

TABLE 4
Components on Modules

Product Type ¹⁾	DRAM Components ¹⁾	DRAM Density	DRAM Organization	Note ²⁾
HYS72T512020HR	HYB18T1G400AF	1 Gbit	256M × 4	

- 1) Green Product
- 2) For a detailed description of all available functions of the DRAM components on these modules see the component data sheet.



2 Pin Configuration

2.1 Pin Configuration

The pin configuration of the Registered DDR2 SDRAM DIMM is listed by function in **Table 5** (240 pins). The abbreviations used in columns Pin and Buffer Type are explained in **Table 6**

and **Table 7** respectively. The pin numbering is depicted in **Figure 1**.

TABLE 5
Pin Configuration of RDIMM

Ball No.	Name	Pin Type	Buffer Type	Function
Clock Signals				
185	CK0	I	SSTL	Clock Signal CK0, Complementary Clock Signal CK0
186	$\overline{\text{CK0}}$	I	SSTL	
52	CKE0	I	SSTL	Clock Enables 1:0
171	CKE1	I	SSTL	<i>Note: 2-Ranks module</i>
	NC	NC	—	Not Connected <i>Note: 1-Rank module</i>
Control Signals				
193	$\overline{\text{S0}}$	I	SSTL	Chip Select Rank 1:0 <i>Note: 2-Ranks module</i>
76	$\overline{\text{S1}}$	I	SSTL	
	NC	NC	—	Not Connected <i>Note: 1-Rank module</i>
192	$\overline{\text{RAS}}$	I	SSTL	Row Address Strobe (RAS), Column Address Strobe (CAS), Write Enable (WE)
74	$\overline{\text{CAS}}$	I	SSTL	
73	$\overline{\text{WE}}$	I	SSTL	
18	$\overline{\text{RESET}}$	I	CMOS	Register Reset
Address Signals				
71	BA0	I	SSTL	Bank Address Bus 1:0
190	BA1	I	SSTL	
54	BA2	I	SSTL	Bank Address Bus 2
	NC	I	SSTL	Not Connected



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Ball No.	Name	Pin Type	Buffer Type	Function
188	A0	I	SSTL	Address Bus 12:0, Address Signal 10/AutoPrecharge
183	A1	I	SSTL	
63	A2	I	SSTL	
182	A3	I	SSTL	
61	A4	I	SSTL	
60	A5	I	SSTL	
180	A6	I	SSTL	
58	A7	I	SSTL	
179	A8	I	SSTL	
177	A9	I	SSTL	
70	A10	I	SSTL	
	AP	I	SSTL	
57	A11	I	SSTL	
176	A12	I	SSTL	
196	A13	I	SSTL	Address Signal 13
	NC	NC	—	Not Connected
174	A14	I	SSTL	Address Signal 14
	NC	NC	—	Not Connected
173	A15	I	SSTL	Address Signal 14
	NC	NC	—	Not Connected



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Ball No.	Name	Pin Type	Buffer Type	Function
Data Signals				
3	DQ0	I/O	SSTL	Data Bus 63:0
4	DQ1	I/O	SSTL	
9	DQ2	I/O	SSTL	
10	DQ3	I/O	SSTL	
122	DQ4	I/O	SSTL	
123	DQ5	I/O	SSTL	
128	DQ6	I/O	SSTL	
129	DQ7	I/O	SSTL	
12	DQ8	I/O	SSTL	
13	DQ9	I/O	SSTL	
21	DQ10	I/O	SSTL	
22	DQ11	I/O	SSTL	
131	DQ12	I/O	SSTL	
132	DQ13	I/O	SSTL	
140	DQ14	I/O	SSTL	
141	DQ15	I/O	SSTL	
24	DQ16	I/O	SSTL	
25	DQ17	I/O	SSTL	
30	DQ18	I/O	SSTL	
31	DQ19	I/O	SSTL	
143	DQ20	I/O	SSTL	
144	DQ21	I/O	SSTL	
149	DQ22	I/O	SSTL	
150	DQ23	I/O	SSTL	
33	DQ24	I/O	SSTL	
34	DQ25	I/O	SSTL	
39	DQ26	I/O	SSTL	
40	DQ27	I/O	SSTL	
152	DQ28	I/O	SSTL	
153	DQ29	I/O	SSTL	
158	DQ30	I/O	SSTL	
159	DQ31	I/O	SSTL	
80	DQ32	I/O	SSTL	
81	DQ33	I/O	SSTL	
86	DQ34	I/O	SSTL	
87	DQ35	I/O	SSTL	
199	DQ36	I/O	SSTL	
200	DQ37	I/O	SSTL	
205	DQ38	I/O	SSTL	



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Ball No.	Name	Pin Type	Buffer Type	Function
206	DQ39	I/O	SSTL	Data Bus 63:0
89	DQ40	I/O	SSTL	
90	DQ41	I/O	SSTL	
95	DQ42	I/O	SSTL	
96	DQ43	I/O	SSTL	
208	DQ44	I/O	SSTL	
209	DQ45	I/O	SSTL	
214	DQ46	I/O	SSTL	
215	DQ47	I/O	SSTL	
98	DQ48	I/O	SSTL	
99	DQ49	I/O	SSTL	
107	DQ50	I/O	SSTL	
108	DQ51	I/O	SSTL	
217	DQ52	I/O	SSTL	
218	DQ53	I/O	SSTL	
226	DQ54	I/O	SSTL	
227	DQ55	I/O	SSTL	
110	DQ56	I/O	SSTL	
111	DQ57	I/O	SSTL	
116	DQ58	I/O	SSTL	
117	DQ59	I/O	SSTL	
229	DQ60	I/O	SSTL	
230	DQ61	I/O	SSTL	
235	DQ62	I/O	SSTL	
236	DQ63	I/O	SSTL	
Check Bits				
42	CB0	I/O	SSTL	Check Bits 7:0
43	CB1	I/O	SSTL	
48	CB2	I/O	SSTL	
49	CB3	I/O	SSTL	
161	CB4	I/O	SSTL	
162	CB5	I/O	SSTL	
167	CB6	I/O	SSTL	
168	CB7	I/O	SSTL	



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Ball No.	Name	Pin Type	Buffer Type	Function
Data Strobe Bus				
7	DQS0	I/O	SSTL	Data Strobes 17:0
6	$\overline{\text{DQS0}}$	I/O	SSTL	
16	DQS1	I/O	SSTL	
15	$\overline{\text{DQS1}}$	I/O	SSTL	
28	DQS2	I/O	SSTL	
27	$\overline{\text{DQS2}}$	I/O	SSTL	
37	DQS3	I/O	SSTL	
36	$\overline{\text{DQS3}}$	I/O	SSTL	
84	DQS4	I/O	SSTL	
83	$\overline{\text{DQS4}}$	I/O	SSTL	
93	DQS5	I/O	SSTL	
92	$\overline{\text{DQS5}}$	I/O	SSTL	
105	DQS6	I/O	SSTL	
104	$\overline{\text{DQS6}}$	I/O	SSTL	
114	DQS7	I/O	SSTL	
113	$\overline{\text{DQS7}}$	I/O	SSTL	
46	DQS8	I/O	SSTL	
45	$\overline{\text{DQS8}}$	I/O	SSTL	
125	DQS9	I/O	SSTL	
126	$\overline{\text{DQS9}}$	I/O	SSTL	
134	DQS10	I/O	SSTL	
135	$\overline{\text{DQS10}}$	I/O	SSTL	
146	DQS11	I/O	SSTL	
147	$\overline{\text{DQS11}}$	I/O	SSTL	
155	DQS12	I/O	SSTL	
156	$\overline{\text{DQS12}}$	I/O	SSTL	
202	DQS13	I/O	SSTL	
203	$\overline{\text{DQS13}}$	I/O	SSTL	
211	DQS14	I/O	SSTL	
212	$\overline{\text{DQS14}}$	I/O	SSTL	
223	DQS15	I/O	SSTL	
224	$\overline{\text{DQS15}}$	I/O	SSTL	
232	DQS16	I/O	SSTL	
233	$\overline{\text{DQS16}}$	I/O	SSTL	
164	DQS17	I/O	SSTL	
165	$\overline{\text{DQS17}}$	I/O	SSTL	



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Ball No.	Name	Pin Type	Buffer Type	Function
Data Mask				
125	DM0	I	SSTL	Data Masks 8:0 <i>Note: ×8 based module</i>
134	DM1	I	SSTL	
146	DM2	I	SSTL	
155	DM3	I	SSTL	
202	DM4	I	SSTL	
211	DM5	I	SSTL	
223	DM6	I	SSTL	
232	DM7	I	SSTL	
164	DM8	I	SSTL	
EEPROM				
120	SCL	I	CMOS	Serial Bus Clock
119	SDA	I/O	OD	Serial Bus Data
239	SA0	I	CMOS	Serial Address Select Bus 2:0
240	SA1	I	CMOS	
101	SA2	I	CMOS	
Parity				
55	ERR_OUT	O	CMOS	Parity bits
	PAR_IN	I	CMOS	
Power Supplies				
1	V _{REF}	AI	—	I/O Reference Voltage
238	V _{DDSPD}	PWR	—	EEPROM Power Supply
51, 56, 62, 72, 75, 78, 170, 175,, 181, 191, 194	V _{DDQ}	PWR	—	I/O Driver Power Supply
53, 59, 64, 67, 69, 172, 178, 184,, 187, 189, 197	V _{DD}	PWR	—	Power Supply
2, 5, 8, 11, 14, 17, 20, 23, 26, 29, 32, 35, 38, 41, 44, 47, 50, 65, 66, 79, 82, 85, 88, 91, 94, 97, 100, 103, 106, 109, 112, 115, 118, 121, 124, 127, 130, 133, 136, 139, 142, 145, 148, 151, 154, 157, 160, 163, 166, 169, 198, 201, 204, 207, 210, 213, 216, 219, 222, 225, 228, 231, 234, 237	V _{SS}	GND	—	Ground Plane



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Ball No.	Name	Pin Type	Buffer Type	Function
Other Pins				
19, 55, 68, 102, 137, 138, 173, 220, 221	NC	NC	—	Not connected
195	ODT0	I	SSTL	On-Die Termination Control 1:0
77	ODT1	I	SSTL	<i>Note: 2-Ranks module</i>
	NC	NC	—	<i>Note: 1-Rank modules</i>

TABLE 6
Abbreviations for Buffer Type

Abbreviation	Description
SSTL	Serial Stub Terminated Logic (SSTL_18)
CMOS	CMOS Levels
OD	Open Drain. The corresponding pin has 2 operational states, active low and tristate, and allows multiple devices to share as a wire-OR.

TABLE 7
Abbreviations for Pin Type

Abbreviation	Description
I	Standard input-only pin. Digital levels.
O	Output. Digital levels.
I/O	I/O is a bidirectional input/output signal.
AI	Input. Analog levels.
PWR	Power
GND	Ground
NU	Not Usable
NC	Not Connected



3 Electrical Characteristics

This chapter lists the electrical characteristics.

3.1 Absolute Maximum Ratings

This chapter contains the absolute maximum ratings table.

TABLE 8
Absolute Maximum Ratings

Parameter	Symbol	Values		Unit	Note
		Min.	Max.		
Voltage on any pins relative to V_{SS}	V_{IN}, V_{OUT}	-0.5	2.3	V	1)
Voltage on V_{DD} relative to V_{SS}	V_{DD}	-1.0	2.3	V	1)
Voltage on V_{DDQ} relative to V_{SS}	V_{DDQ}	-0.5	2.3	V	1)
Storage Humidity (without condensation)	H_{STG}	5	95	%	1)

- 1) Stresses greater than those listed may cause permanent damage to the device. This is a stress rating only, and device functional operation at or above the conditions indicated is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability

3.2 DC Operating Conditions

This chapter describes the operating conditions.

TABLE 9
Operating Conditions

Parameter	Symbol	Values		Unit	Note
		Min.	Max.		
DIMM Module Operating Temperature Range (ambient)	T_{OPR}	0	+55	°C	
DRAM Component Case Temperature Range	T_{CASE}	0	+95	°C	1)2)3)4)
Storage Temperature	T_{STG}	-50	+100	°C	
Barometric Pressure (operating & storage)	PBar	+69	+105	kPa	5)
Operating Humidity (relative)	H_{OPR}	10	90	%	

- 1) DRAM Component Case Temperature is the surface temperature in the center on the top side of any of the DRAMs.
2) Within the DRAM Component Case Temperature range all DRAM specification will be supported.
3) Above 85 °C DRAM case temperature the Auto-Refresh command interval has to be reduced to $t_{REFI} = 3.9 \mu s$.
4) Self-Refresh period is hard-coded in the DRAMs and therefore it is imperative that the system ensures the DRAM is below 85 °C case temperature before initiating self-refresh operation.
5) Up to 3000 m



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

TABLE 10
Supply Voltage Levels and DC Operating Conditions

Parameter	Symbol	Values			Unit	Note
		Min.	Nom.	Max.		
Device Supply Voltage	V_{DD}	1.7	1.8	1.9	V	
Output Supply Voltage	V_{DDQ}	1.7	1.8	1.9	V	1)
Input Reference Voltage	V_{REF}	$0.49 \times V_{DDQ}$	$0.5 \times V_{DDQ}$	$0.51 \times V_{DDQ}$	V	2)
SPD Supply Voltage	V_{DDSPD}	1.7	—	3.6	V	
DC Input Logic High	$V_{IH(DC)}$	$V_{REF} + 0.125$	—	$V_{DDQ} + 0.3$	V	
DC Input Logic Low	$V_{IL(DC)}$	-0.30	—	$V_{REF} - 0.125$	V	
In / Output Leakage Current	I_L	-5	—	5	μA	3)

1) Under all conditions, V_{DDQ} must be less than or equal to V_{DD}

2) Peak to peak AC noise on V_{REF} may not exceed $\pm 2\% V_{REF(DC)}$. V_{REF} is also expected to track noise variations in V_{DDQ} .

3) Input voltage for any connector pin under test of $0 V \leq V_{IN} \leq V_{DDQ} + 0.3 V$; all other pins at 0 V. Current is per pin



3.3 AC Characteristics

This chapter describes the AC characteristics.

3.3.1 Speed Grades Definitions

This chapter contains the Speed Grade Definition tables.

TABLE 11
Speed Grade Definition Speed Bins for DDR2-533 and DDR2-400

Speed Grade			DDR2–533C		DDR2–400B		Unit	Note
IFX Sort Name			–3.7		–5			
CAS-RCD-RP latencies			4–4–4		3–3–3		t_{CK}	
Parameter		Symbol	Min.	Max.	Min.	Max.	—	
Clock Frequency	@ CL = 3	t_{CK}	5	8	5	8	ns	1)2)3)4)
	@ CL = 4	t_{CK}	3.75	8	5	8	ns	1)2)3)4)
	@ CL = 5	t_{CK}	3.75	8	5	8	ns	1)2)3)4)
Row Active Time		t_{RAS}	45	70000	40	70000	ns	1)2)3)4)5)
Row Cycle Time		t_{RC}	60	—	55	—	ns	1)2)3)4)
RAS-CAS-Delay		t_{RCD}	15	—	15	—	ns	1)2)3)4)
Row Precharge Time		t_{RP}	15	—	15	—	ns	1)2)3)4)

- 1) Timings are guaranteed with CK/CK differential Slew Rate of 2.0 V/ns. For DQS signals timings are guaranteed with a differential Slew Rate of 2.0 V/ns in differential strobe mode and a Slew Rate of 1 V/ns in single ended mode. Timings are further guaranteed for normal OCD drive strength (EMRS(1) A1 = 0) only.
- 2) The CK/CK input reference level (for timing reference to CK/CK) is the point at which CK and CK cross. The DQS / DQS, RDQS / RDQS, input reference level is the crosspoint when in differential strobe mode
- 3) Inputs are not recognized as valid until V_{REF} stabilizes. During the period before V_{REF} stabilizes, CKE = 0.2 x V_{DDQ} is recognized as low.
- 4) The output timing reference voltage level is V_{TT} .
- 5) $t_{RAS,MAX}$ is calculated from the maximum amount of time a DDR2 device can operate without a refresh command which is equal to 9 x t_{REFI} .



3.3.2 AC Timing Parameters

This chapter contains the AC Timing Parameters.

TABLE 12

Timing Parameter by Speed Grade - DDR2-400 & DDR2-533

Parameter	Symbol	DDR2-533		DDR2-400		Unit	Note ¹⁾²⁾ 3)4)5)6)7)
		Min.	Max.	Min.	Max.		
DQ output access time from CK/ $\overline{\text{CK}}$	t_{AC}	-500	+500	-600	+600	ps	
CAS A to CAS B command period	t_{CCD}	2	—	2	—	t_{CK}	
CK, $\overline{\text{CK}}$ high-level width	t_{CH}	0.45	0.55	0.45	0.55	t_{CK}	
CKE minimum high and low pulse width	t_{CKE}	3	—	3	—	t_{CK}	
CK, $\overline{\text{CK}}$ low-level width	t_{CL}	0.45	0.55	0.45	0.55	t_{CK}	
Auto-Precharge write recovery + precharge time	t_{DAL}	WR + t_{RP}	—	WR + t_{RP}	—	t_{CK}	
Minimum time clocks remain ON after CKE asynchronously drops LOW	t_{DELAY}	$t_{\text{IS}} + t_{\text{CK}} + t_{\text{IH}}$	—	$t_{\text{IS}} + t_{\text{CK}} + t_{\text{IH}}$	—	ns	
DQ and DM input hold time (differential data strobe)	$t_{\text{DH}}(\text{base})$	225	—	275	—	ps	
DQ and DM input hold time (single ended data strobe)	$t_{\text{DH1}}(\text{base})$	-25	—	25	—	ps	
DQ and DM input pulse width (each input)	t_{DIPW}	0.35	—	0.35	—	t_{CK}	
DQS output access time from CK/ $\overline{\text{CK}}$	t_{DQSK}	-450	+450	-500	+500	ps	
DQS input low (high) pulse width (write cycle)	$t_{\text{DQSL,H}}$	0.35	—	0.35	—	t_{CK}	
DQS-DQ skew (for DQS & associated DQ signals)	t_{DQSQ}	—	300	—	350	ps	
Write command to 1st DQS latching transition	t_{DQSS}	- 0.25	+ 0.25	- 0.25	+ 0.25	t_{CK}	
DQ and DM input setup time (differential data strobe)	$t_{\text{DS}}(\text{base})$	100	—	150	—	ps	
DQ and DM input setup time (single ended data strobe)	$t_{\text{DS1}}(\text{base})$	-25	—	25	—	ps	
DQS falling edge hold time from CK (write cycle)	t_{DSH}	0.2	—	0.2	—	t_{CK}	
DQS falling edge to CK setup time (write cycle)	t_{DSS}	0.2	—	0.2	—	t_{CK}	
Four Activate Window period	t_{FAW}	37.5	—	37.5	—	ns	
		50	—	50	—	ns	8)
Clock half period	t_{HP}	MIN. (t_{CL} , t_{CH})		MIN. (t_{CL} , t_{CH})			
Data-out high-impedance time from CK/ $\overline{\text{CK}}$	t_{HZ}	—	$t_{\text{AC,MAX}}$	—	$t_{\text{AC,MAX}}$	ps	
Address and control input hold time	$t_{\text{IH}}(\text{base})$	375	—	475	—	ps	



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Parameter	Symbol	DDR2-533		DDR2-400		Unit	Note ¹⁾²⁾ 3)4)5)6)7)
		Min.	Max.	Min.	Max.		
Address and control input pulse width (each input)	t_{IPW}	0.6	—	0.6	—	t_{CK}	
Address and control input setup time	$t_{IS}(\text{base})$	250	—	350	—	ps	
DQ low-impedance time from CK / $\overline{CK}$	$t_{LZ}(DQ)$	$2 \times t_{AC,MIN}$	$t_{AC,MAX}$	$2 \xi t_{AC,MIN}$	$t_{AC,MAX}$	ps	
DQS low-impedance from CK / $\overline{CK}$	$t_{LZ}(DQS)$	$t_{AC,MIN}$	$t_{AC,MAX}$	$t_{AC,MIN}$	$t_{AC,MAX}$	ps	
Mode register set command to ODT update delay	t_{MOD}	0	12	0	12	ns	
Mode register set command cycle time	t_{MRD}	2	—	2	—	t_{CK}	
OCD drive mode output delay	t_{OIT}	0	12	0	12	ns	
Data output hold time from DQS	t_{QH}	$t_{HP} - t_{QHS}$	—	$t_{HPQ} - t_{QHS}$	—		
Data hold skew factor	t_{QHS}	—	400	—	450	ps	
Average periodic refresh Interval	t_{REFI}	—	7.8	—	7.8	μs	9)
		—	3.9	—	3.9	μs	10)
Auto-Refresh to Active/Auto-Refresh command period	t_{RFC}	127.5	—	127.5	—	ns	
Precharge-All (8 banks) command period	t_{RP}	$15 + 1t_{CK}$	—	$15 + 1t_{CK}$	—	ns	
Read preamble	t_{RPRE}	0.9	1.1	0.9	1.1	t_{CK}	
Read postamble	t_{RPST}	0.40	0.60	0.40	0.60	t_{CK}	
Active bank A to Active bank B command period	t_{RRD}	7.5	—	7.5	—	ns	11)
Internal Read to Precharge command delay	t_{RTP}	7.5	—	7.5	—	ns	
Write preamble	t_{WPRE}	$0.35 \times t_{CK}$	—	$0.35 \times t_{CK}$	—	t_{CK}	
Write postamble	t_{WPST}	0.40	0.60	0.40	0.60	t_{CK}	
Write recovery time for write without Auto-Precharge	t_{WR}	15	—	15	—	ns	
Write recovery time for write with Auto-Precharge	WR	t_{WR}/t_{CK}	—	t_{WR}/t_{CK}	—	t_{CK}	
Internal Write to Read command delay	t_{WTR}	7.5	—	10	—	ns	
Exit power down to any valid command (other than NOP or Deselect)	t_{XARD}	2	—	2	—	t_{CK}	
Exit active power-down mode to Read command (slow exit, lower power)	t_{XARDS}	6 – AL	—	6 – AL	—	t_{CK}	
Exit precharge power-down to any valid command (other than NOP or Deselect)	t_{XP}	2	—	2	—	t_{CK}	
Exit Self-Refresh to non-Read command	t_{XSNR}	$t_{RFC} + 10$	—	$t_{RFC} + 10$	—	ns	
Exit Self-Refresh to Read command	$t_{XS RD}$	200	—	200	—	t_{CK}	

1) For details and notes see the relevant QIMONDA component data sheet

2) $V_{DDQ} = 1.8 V \pm 0.1 V$; $V_{DD} = 1.8 V \pm 0.1 V$. See notes 4)5)6)7)



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

- 3) Timing that is not specified is illegal and after such an event, in order to guarantee proper operation, the DRAM must be powered down and then restarted through the specified initialization sequence before normal operation can continue.
- 4) Timings are guaranteed with $\overline{CK}/\overline{CK}$ differential Slew Rate of 2.0 V/ns. For DQS signals timings are guaranteed with a differential Slew Rate of 2.0 V/ns in differential strobe mode and a Slew Rate of 1 V/ns in single ended mode.
- 5) The $\overline{CK}/\overline{CK}$ input reference level (for timing reference to $\overline{CK}/\overline{CK}$) is the point at which $\overline{CK}$ and $\overline{CK}$ cross. The $\overline{DQS}/\overline{DQS}$, $\overline{RDQS}/\overline{RDQS}$, input reference level is the crosspoint when in differential strobe mode
- 6) Inputs are not recognized as valid until V_{REF} stabilizes. During the period before V_{REF} stabilizes, $\overline{CKE} = 0.2 \times V_{DDQ}$ is recognized as low.
- 7) The output timing reference voltage level is V_{TT} .
- 8) x16 (2k page size), not on 256 Mbit component
- 9) $0 \leq T_{CASE} \leq 85^\circ\text{C}$
- 10) $85^\circ\text{C} < T_{CASE} \leq 95^\circ\text{C}$
- 11) x4 & x8



3.3.3 ODT AC Electrical Characteristics

This chapter contains the ODT AC electrical characteristics tables.

TABLE 13

ODT AC Characteristics and Operating Conditions for DDR2-533/DDR2-400

Symbol	Parameter / Condition	Values		Unit	Note
		Min.	Max.		
t_{AOND}	ODT turn-on delay	2	2	t_{CK}	
t_{AON}	ODT turn-on	$t_{AC.MIN}$	$t_{AC.MAX} + 1 \text{ ns}$	ns	1)
t_{AONPD}	ODT turn-on (Power-Down Modes)	$t_{AC.MIN} + 2 \text{ ns}$	$2 t_{CK} + t_{AC.MAX} + 1 \text{ ns}$	ns	
t_{AOFD}	ODT turn-off delay	2.5	2.5	t_{CK}	
t_{AOF}	ODT turn-off	$t_{AC.MIN}$	$t_{AC.MAX} + 0.6 \text{ ns}$	ns	2)
t_{AOFPD}	ODT turn-off (Power-Down Modes)	$t_{AC.MIN} + 2 \text{ ns}$	$2.5 t_{CK} + t_{AC.MAX} + 1 \text{ ns}$	ns	
t_{ANPD}	ODT to Power Down Mode Entry Latency	3	—	t_{CK}	
t_{AXPD}	ODT Power Down Exit Latency	8	—	t_{CK}	

- 1) ODT turn on time min. is when the device leaves high impedance and ODT resistance begins to turn on. ODT turn on time max is when the ODT resistance is fully on. Both are measure from t_{AOND} .
- 2) ODT turn off time min. is when the device starts to turn off ODT resistance. ODT turn off time max is when the bus is in high impedance. Both are measured from t_{AOFD} .



3.4 Currents Specifications and Conditions

TABLE 14

I_{DD} Measurement Conditions

Parameter	Symbol	Note ¹⁾²⁾³⁾⁴⁾⁵⁾⁶⁾⁷⁾⁸⁾
Operating Current 0 One bank Active - Precharge; $t_{CK} = t_{CK.MIN}$, $t_{RC} = t_{RC.MIN}$, $t_{RAS} = t_{RAS.MIN}$, CKE is HIGH, $\overline{CS}$ is HIGH between valid commands. Address and control inputs are SWITCHING, Databus inputs are SWITCHING.	I_{DD0}	
Operating Current 1 One bank Active - Read - Precharge; $I_{OUT} = 0$ mA, BL = 4, $t_{CK} = t_{CK.MIN}$, $t_{RC} = t_{RC.MIN}$, $t_{RAS} = t_{RAS.MIN}$, $t_{RCD} = t_{RCD.MIN}$, AL = 0, CL = CL _{MIN} ; CKE is HIGH, $\overline{CS}$ is HIGH between valid commands. Address and control inputs are SWITCHING, Databus inputs are SWITCHING.	I_{DD1}	
Precharge Standby Current All banks idle; $\overline{CS}$ is HIGH; CKE is HIGH; $t_{CK} = t_{CK.MIN}$; Other control and address inputs are SWITCHING, Data bus inputs are SWITCHING	I_{DD2N}	
Precharge Power-Down Current Other control and address inputs are STABLE, Data bus inputs are FLOATING	I_{DD2P}	
Precharge Quiet Standby Current All banks idle; $\overline{CS}$ is HIGH; CKE is HIGH; $t_{CK} = t_{CK.MIN}$; Other control and address inputs are STABLE, Data bus inputs are FLOATING.	I_{DD2Q}	
Active Power-Down Current All banks open; $t_{CK} = t_{CK.MIN}$, CKE is LOW; Other control and address inputs are STABLE, Data bus inputs are FLOATING. MRS A12 bit is set to LOW (Fast Power-down Exit);	$I_{DD3P(0)}$	
Active Power-Down Current All banks open; $t_{CK} = t_{CK.MIN}$, CKE is LOW; Other control and address inputs are STABLE, Data bus inputs are FLOATING. MRS A12 bit is set to HIGH (Slow Power-down Exit);	$I_{DD3P(1)}$	
Active Standby Current Burst Read: All banks open; Continuous burst reads; BL = 4; AL = 0, CL = CL _{MIN} ; $t_{CK} = t_{CK.MIN}$; $t_{RAS} = t_{RAS.MAX}$, $t_{RP} = t_{RP.MIN}$; CKE is HIGH, $\overline{CS}$ is HIGH between valid commands. Address inputs are SWITCHING; Data Bus inputs are SWITCHING; $I_{OUT} = 0$ mA.	I_{DD3N}	
Operating Current Burst Read: All banks open; Continuous burst reads; BL = 4; AL = 0, CL = CL _{MIN} ; $t_{CK} = t_{CK.MIN}$; $t_{RAS} = t_{RAS.MAX}$, $t_{RP} = t_{RP.MIN}$; CKE is HIGH, $\overline{CS}$ is HIGH between valid commands. Address inputs are SWITCHING; Data Bus inputs are SWITCHING; $I_{OUT} = 0$ mA.	I_{DD4R}	
Operating Current Burst Write: All banks open; Continuous burst writes; BL = 4; AL = 0, CL = CL _{MIN} ; $t_{CK} = t_{CK.MIN}$; $t_{RAS} = t_{RAS.MAX}$, $t_{RP} = t_{RP.MAX}$; CKE is HIGH, $\overline{CS}$ is HIGH between valid commands. Address inputs are SWITCHING; Data Bus inputs are SWITCHING;	I_{DD4W}	
Burst Refresh Current $t_{CK} = t_{CK.MIN}$, Refresh command every $t_{RFC} = t_{RFC.MIN}$ interval, CKE is HIGH, $\overline{CS}$ is HIGH between valid commands, Other control and address inputs are SWITCHING, Data bus inputs are SWITCHING.	I_{DD5B}	
Distributed Refresh Current $t_{CK} = t_{CK.MIN}$, Refresh command every $t_{RFC} = t_{REFI}$ interval, CKE is LOW and $\overline{CS}$ is HIGH between valid commands, Other control and address inputs are SWITCHING, Data bus inputs are SWITCHING.	I_{DD5D}	



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Parameter	Symbol	Note ¹⁾²⁾³⁾⁴⁾⁵⁾⁶⁾⁷⁾⁸⁾
Self-Refresh Current CKE ≤ 0.2 V; external clock off, CK and $\overline{\text{CK}}$ at 0 V; Other control and address inputs are FLOATING, Data bus inputs are FLOATING. RESET is LOW. I_{DD6} current values are guaranteed up to T_{CASE} of 85 °C max.	I_{DD6}	
All Bank Interleave Read Current All banks are being interleaved at minimum t_{RC} without violating t_{RRD} using a burst length of 4. Control and address bus inputs are STABLE during DESELECTS. $I_{\text{OUT}} = 0$ mA.	I_{DD7}	

- 1) $V_{\text{DDQ}} = 1.8 \text{ V} \pm 0.1 \text{ V}$; $V_{\text{DD}} = 1.8 \text{ V} \pm 0.1 \text{ V}$
- 2) IDD specifications are tested after the device is properly initialized and IDD parameter are specified with ODT disabled.
- 3) Definitions for I_{DD} see **Table 15**
- 4) I_{DD1} , I_{DD4R} and I_{DD7} current measurements are defined with the outputs disabled ($I_{\text{OUT}} = 0$ mA). To achieve this on module level the output buffers can be disabled using an EMRS(1) (Extended Mode Register Command) by setting A12 bit to HIGH.
- 5) For two rank modules: for all active current measurements the other rank is in Precharge Power-Down Mode I_{DD2P}
- 6) RESET signal is HIGH for all currents, except for I_{DD6} (Self Refresh)
- 7) All current measurements includes Register and PLL current consumption
- 8) For details and notes see the relevant QIMONDA component data sheet

TABLE 15
Definitions for I_{DD}

Parameter	Description
LOW	$V_{\text{IN}} \leq V_{\text{IL(ac).MAX}}$; HIGH is defined as $V_{\text{IN}} \geq V_{\text{IH(ac).MIN}}$
STABLE	inputs are stable at a HIGH or LOW level
FLOATING	inputs are $V_{\text{REF}} = V_{\text{DDQ}}/2$
SWITCHING	inputs are changing between HIGH and LOW every other clock (once per 2 cycles) for address and control signals, and inputs changing between HIGH and LOW every other data transfer (once per cycle) for DQ signals not including mask or strobes.



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

TABLE 16
 I_{DD} Specification for HYS72T512020HR-3.7-A

Product Type	HYS72T512020HR-3.7-A	Unit	Note ¹⁾
Organization	4 G		
	2 Ranks		
	×72		
	-3.7		
Symbol	Max.	mA	
I_{DD0}	1950		
I_{DD1}	2130		
I_{DD2N}	2160		
I_{DD2P}	710		
I_{DD2Q}	1650		
I_{DD3N}	2300		
I_{DD3P} (MRS = 0)	1110		
I_{DD3P} (MRS = 1)	720		
I_{DD4R}	3210		
I_{DD4W}	3120		
I_{DD5B}	3930		
I_{DD5D}	750		
I_{DD6}	205		
I_{DD7}	4740		

- 1) Module I_{DD} is calculated on the basis of component I_{DD} and includes currents of Registers and PLL. ODT disabled. I_{DD1} , I_{DD4R} , and I_{DD7} , are defined with the outputs disabled.
- 2) The other rank is in I_{DD2P} Precharge Power-Down Standby Current mode
- 3) Both ranks are in the same I_{DD} current mode



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

TABLE 17
 I_{DD} Specification for HYS72T512020HR-5-A

Product Type	HYS72T512020HR-5-A	Unit	Note ¹⁾
Organization	4 G		
	2 Ranks		
	×72		
	-5		
Symbol	Max.		
I_{DD0}	1770	mA	2)
I_{DD1}	1950	mA	2)
I_{DD2N}	1670	mA	3)
I_{DD2P}	610	mA	3)
I_{DD2Q}	1410	mA	3)
I_{DD3N}	1850	mA	3)
I_{DD3P} (MRS = 0)	870	mA	3)
I_{DD3P} (MRS = 1)	620	mA	3)
I_{DD4R}	2580	mA	2)
I_{DD4W}	2490	mA	2)
I_{DD5B}	3750	mA	2)
I_{DD5D}	660	mA	3)
I_{DD6}	205	mA	3)
I_{DD7}	4200	mA	2)

- 1) Module I_{DD} is calculated on the basis of component I_{DD} and includes currents of Registers and PLL. ODT disabled. I_{DD1} , I_{DD4R} , and I_{DD7} , are defined with the outputs disabled.
- 2) The other rank is in I_{DD2P} Precharge Power-Down Standby Current mode
- 3) Both ranks are in the same I_{DD} current mode



3.4.1 Currents Test Conditions

For testing the I_{DD} parameters, the following timing parameters are used:

TABLE 18

I_{DD} Measurement Test Conditions for DDR2-400 and DDR2-533

Parameter	Symbol	-3.7	-5	Unit
		DDR2-533C	DDR2-400B	
CAS Latency	$CL_{(IDD)}$	4	3	t_{CK}
Clock Cycle Time	$t_{CK(IDD)}$	3.75	5	ns
Active to Read or Write delay	$t_{RCD(IDD)}$	15	15	ns
Active to Active / Auto-Refresh command period	$t_{RC(IDD)}$	60	55	ns
Active bank A to Active bank B command delay				
Active to Precharge Command	$t_{RAS.MIN(IDD)}$	45	40	ns
	$t_{RAS.MAX(IDD)}$	70000	70000	ns
Precharge Command Period	$t_{RP(IDD)}$	15	15	ns
Auto-Refresh to Active / Auto-Refresh command period	$t_{RFC(IDD)}$	127.5	127.5	ns
Average periodic Refresh interval	t_{REFI}	7.8	7.8	μs

3.4.2 On Die Termination (ODT) Current

The ODT function adds additional current consumption to the DDR2 SDRAM when enabled by the EMRS(1). Depending on address bits A[6,2] in the EMRS(1) a “weak” or “strong” termination can be selected. The current consumption for any

terminated input pin, depends on the input pin is in tri-state or driving 0 or 1, as long a ODT is enabled during a given period of time.

TABLE 19

ODT current per terminated pin

Parameter	Symbol	Min.	Typ.	Max.	Unit	EMRS(1) State
Enabled ODT current per DQ ODT is HIGH; Data Bus inputs are FLOATING	I_{ODTO}	5	6	7.5	mA/DQ	A6 = 0, A2 = 1
		2.5	3	3.75	mA/DQ	A6 = 1, A2 = 0
Active ODT current per DQ ODT is HIGH; worst case of Data Bus inputs are STABLE or SWITCHING.	I_{ODTT}	10	12	15	mA/DQ	A6 = 0, A2 = 1
		5	6	7.5	mA/DQ	A6 = 1, A2 = 0



4 SPD Codes

This chapter lists all hexadecimal byte values stored in the EEPROM of the products described in this data sheet. SPD stands for serial presence detect. All values with XX in the table are module specific bytes which are defined during production.

List of SPD Code Tables

- Table 20 “SPD codes for PC2-4200R-444” on Page 27
- Table 21 “SPD codes for PC2-3200R-333” on Page 31

TABLE 20
SPD codes for PC2-4200R-444

Product Type		HYS72T512020HR-3.7-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-4200R-444
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
0	Programmed SPD Bytes in EEPROM	80
1	Total number of Bytes in EEPROM	08
2	Memory Type (DDR2)	08
3	Number of Row Addresses	0E
4	Number of Column Addresses	0B
5	DIMM Rank and Stacking Information	61
6	Data Width	48
7	Not used	00
8	Interface Voltage Level	05
9	t_{CK} @ CL_{MAX} (Byte 18) [ns]	3D
10	t_{AC} SDRAM @ CL_{MAX} (Byte 18) [ns]	50
11	Error Correction Support (non-ECC, ECC)	02
12	Refresh Rate and Type	82
13	Primary SDRAM Width	04
14	Error Checking SDRAM Width	04
15	Not used	00
16	Burst Length Supported	0C
17	Number of Banks on SDRAM Device	08
18	Supported CAS Latencies	38
19	DIMM Mechanical Characteristics	00
20	DIMM Type Information	01



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Product Type		HYS72T512020HR-3.7-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-4200R-444
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
21	DIMM Attributes	07
22	Component Attributes	01
23	$t_{CK} @ CL_{MAX} -1$ (Byte 18) [ns]	3D
24	t_{AC} SDRAM @ $CL_{MAX} -1$ [ns]	50
25	$t_{CK} @ CL_{MAX} -2$ (Byte 18) [ns]	50
26	t_{AC} SDRAM @ $CL_{MAX} -2$ [ns]	60
27	$t_{RP.MIN}$ [ns]	3C
28	$t_{RRD.MIN}$ [ns]	1E
29	$t_{RCD.MIN}$ [ns]	3C
30	$t_{RAS.MIN}$ [ns]	2D
31	Module Density per Rank	02
32	$t_{AS.MIN}$ and $t_{CS.MIN}$ [ns]	25
33	$t_{AH.MIN}$ and $t_{CH.MIN}$ [ns]	37
34	$t_{DS.MIN}$ [ns]	10
35	$t_{DH.MIN}$ [ns]	22
36	$t_{WR.MIN}$ [ns]	3C
37	$t_{WTR.MIN}$ [ns]	1E
38	$t_{RTP.MIN}$ [ns]	1E
39	Analysis Characteristics	00
40	t_{RC} and t_{RFC} Extension	06
41	$t_{RC.MIN}$ [ns]	3C
42	$t_{RFC.MIN}$ [ns]	7F
43	$t_{CK.MAX}$ [ns]	80
44	$t_{DQSQ.MAX}$ [ns]	1E
45	$t_{QHS.MAX}$ [ns]	28
46	PLL Relock Time	0F
47	$T_{CASE.MAX}$ Delta / ΔT_{4R4W} Delta	51
48	Psi(T-A) DRAM	60
49	ΔT_0 (DT0)	37
50	ΔT_{2N} (DT2N, UDIMM) or ΔT_{2Q} (DT2Q, RDIMM)	1D
51	ΔT_{2P} (DT2P)	23
52	ΔT_{3N} (DT3N)	1E
53	$\Delta T_{3P.fast}$ (DT3P fast)	1F



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Product Type		HYS72T512020HR-3.7-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-4200R-444
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
54	$\Delta T_{3P,slow}$ (DT3P slow)	16
55	ΔT_{4R} (DT4R) / ΔT_{4R4W} Sign (DT4R4W)	43
56	ΔT_{5B} (DT5B)	22
57	ΔT_7 (DT7)	2A
58	Psi(ca) PLL	C4
59	Psi(ca) REG	8C
60	ΔT_{PLL} (DTPLL)	61
61	ΔT_{REG} (DTREG) / Toggle Rate	78
62	SPD Revision	11
63	Checksum of Bytes 0-62	A7
64	Manufacturer's JEDEC ID Code (1)	7F
65	Manufacturer's JEDEC ID Code (2)	7F
66	Manufacturer's JEDEC ID Code (3)	7F
67	Manufacturer's JEDEC ID Code (4)	7F
68	Manufacturer's JEDEC ID Code (5)	7F
69	Manufacturer's JEDEC ID Code (6)	51
70	Manufacturer's JEDEC ID Code (7)	00
71	Manufacturer's JEDEC ID Code (8)	00
72	Module Manufacturer Location	xx
73	Product Type, Char 1	37
74	Product Type, Char 2	32
75	Product Type, Char 3	54
76	Product Type, Char 4	35
77	Product Type, Char 5	31
78	Product Type, Char 6	32
79	Product Type, Char 7	30
80	Product Type, Char 8	32
81	Product Type, Char 9	30
82	Product Type, Char 10	48
83	Product Type, Char 11	52
84	Product Type, Char 12	33
85	Product Type, Char 13	2E
86	Product Type, Char 14	37



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Product Type		HYS72T512020HR-3.7-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-4200R-444
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
87	Product Type, Char 15	41
88	Product Type, Char 16	20
89	Product Type, Char 17	20
90	Product Type, Char 18	20
91	Module Revision Code	5x
92	Test Program Revision Code	xx
93	Module Manufacturing Date Year	xx
94	Module Manufacturing Date Week	xx
95 - 98	Module Serial Number	xx
99 - 127	Not used	00
128 - 255	Blank for customer use	FF



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

TABLE 21
SPD codes for PC2-3200R-333

Product Type		HYS72T512020HR-5-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-3200R-333
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
0	Programmed SPD Bytes in EEPROM	80
1	Total number of Bytes in EEPROM	08
2	Memory Type (DDR2)	08
3	Number of Row Addresses	0E
4	Number of Column Addresses	0B
5	DIMM Rank and Stacking Information	61
6	Data Width	48
7	Not used	00
8	Interface Voltage Level	05
9	$t_{CK} @ CL_{MAX}$ (Byte 18) [ns]	50
10	t_{AC} SDRAM @ CL_{MAX} (Byte 18) [ns]	60
11	Error Correction Support (non-ECC, ECC)	02
12	Refresh Rate and Type	82
13	Primary SDRAM Width	04
14	Error Checking SDRAM Width	04
15	Not used	00
16	Burst Length Supported	0C
17	Number of Banks on SDRAM Device	08
18	Supported CAS Latencies	38
19	DIMM Mechanical Characteristics	00
20	DIMM Type Information	01
21	DIMM Attributes	07
22	Component Attributes	01
23	$t_{CK} @ CL_{MAX} -1$ (Byte 18) [ns]	50
24	t_{AC} SDRAM @ $CL_{MAX} -1$ [ns]	60
25	$t_{CK} @ CL_{MAX} -2$ (Byte 18) [ns]	50
26	t_{AC} SDRAM @ $CL_{MAX} -2$ [ns]	60
27	$t_{RP.MIN}$ [ns]	3C
28	$t_{RRD.MIN}$ [ns]	1E
29	$t_{RCD.MIN}$ [ns]	3C



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Product Type		HYS72T512020HR-5-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-3200R-333
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
30	$t_{RAS.MIN}$ [ns]	28
31	Module Density per Rank	02
32	$t_{AS.MIN}$ and $t_{CS.MIN}$ [ns]	35
33	$t_{AH.MIN}$ and $t_{CH.MIN}$ [ns]	47
34	$t_{DS.MIN}$ [ns]	15
35	$t_{DH.MIN}$ [ns]	27
36	$t_{WR.MIN}$ [ns]	3C
37	$t_{WTR.MIN}$ [ns]	28
38	$t_{RTP.MIN}$ [ns]	1E
39	Analysis Characteristics	00
40	t_{RC} and t_{RFC} Extension	06
41	$t_{RC.MIN}$ [ns]	37
42	$t_{RFC.MIN}$ [ns]	7F
43	$t_{CK.MAX}$ [ns]	80
44	$t_{DQSQ.MAX}$ [ns]	23
45	$t_{QHS.MAX}$ [ns]	2D
46	PLL Relock Time	0F
47	$T_{CASE.MAX}$ Delta / ΔT_{4R4W} Delta	51
48	Psi(T-A) DRAM	60
49	ΔT_0 (DT0)	33
50	ΔT_{2N} (DT2N, UDIMM) or ΔT_{2Q} (DT2Q, RDIMM)	1A
51	ΔT_{2P} (DT2P)	23
52	ΔT_{3N} (DT3N)	18
53	$\Delta T_{3P.fast}$ (DT3P fast)	18
54	$\Delta T_{3P.slow}$ (DT3P slow)	16
55	ΔT_{4R} (DT4R) / ΔT_{4R4W} Sign (DT4R4W)	35
56	ΔT_{5B} (DT5B)	21
57	ΔT_7 (DT7)	25
58	Psi(ca) PLL	C4
59	Psi(ca) REG	8C
60	ΔT_{PLL} (DTPLL)	59
61	ΔT_{REG} (DTREG) / Toggle Rate	5C
62	SPD Revision	11



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Product Type		HYS72T512020HR-5-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-3200R-333
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
63	Checksum of Bytes 0-62	D5
64	Manufacturer's JEDEC ID Code (1)	7F
65	Manufacturer's JEDEC ID Code (2)	7F
66	Manufacturer's JEDEC ID Code (3)	7F
67	Manufacturer's JEDEC ID Code (4)	7F
68	Manufacturer's JEDEC ID Code (5)	7F
69	Manufacturer's JEDEC ID Code (6)	51
70	Manufacturer's JEDEC ID Code (7)	00
71	Manufacturer's JEDEC ID Code (8)	00
72	Module Manufacturer Location	xx
73	Product Type, Char 1	37
74	Product Type, Char 2	32
75	Product Type, Char 3	54
76	Product Type, Char 4	35
77	Product Type, Char 5	31
78	Product Type, Char 6	32
79	Product Type, Char 7	30
80	Product Type, Char 8	32
81	Product Type, Char 9	30
82	Product Type, Char 10	48
83	Product Type, Char 11	52
84	Product Type, Char 12	35
85	Product Type, Char 13	41
86	Product Type, Char 14	20
87	Product Type, Char 15	20
88	Product Type, Char 16	20
89	Product Type, Char 17	20
90	Product Type, Char 18	20
91	Module Revision Code	5x
92	Test Program Revision Code	xx
93	Module Manufacturing Date Year	xx
94	Module Manufacturing Date Week	xx
95 - 98	Module Serial Number	xx




HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Product Type		HYS72T512020HR-5-A
Organization		4 GByte
		×72
		2 Ranks (×4)
Label Code		PC2-3200R-333
JEDEC SPD Revision		Rev. 1.1
Byte#	Description	HEX
99 - 127	Not used	00
128 - 255	Blank for customer use	FF



5 Package Outlines

FIGURE 2
Package Outline Raw Card ZZ L-DIM-240-42



GLD01044



6 Product Type Nomenclature

Qimonda's nomenclature uses simple coding combined with some proprietary coding. **Table 22** provides examples for module and component product type number as well as the

field number. The detailed field description together with possible values and coding explanation is listed for modules in **Table 23** and for components in **Table 24**.

TABLE 22
Nomenclature Fields and Examples

Example for	Field Number										
	1	2	3	4	5	6	7	8	9	10	11
Micro-DIMM	HYS	64	T		0	2	0	K	M	-5	-A
DDR2 DRAM	HYB	18	T	1G	16		0	A	C	-5	

TABLE 23
DDR2 DIMM Nomenclature

Field	Description	Values	Coding
1	Qimonda Module Prefix	HYS	Constant
2	Module Data Width [bit]	64	Non-ECC
		72	ECC
3	DRAM Technology	T	DDR2
4	Memory Density per I/O [Mbit]; Module Density ¹⁾	32	256 MByte
		64	512 MByte
		128	1 GByte
		256	2 GByte
		512	4 GByte
5	Raw Card Generation	0 .. 9	Look up table
6	Number of Module Ranks	0, 2, 4	1, 2, 4
7	Product Variations	0 .. 9	Look up table
8	Package, Lead-Free Status	A .. Z	Look up table
9	Module Type	D	SO-DIMM
		M	Micro-DIMM
		R	Registered
		U	Unbuffered
		F	Fully Buffered



HYS72T512020HR-[3.7/5]-A
Registered DDR2 SDRAM Modules

Field	Description	Values	Coding
10	Speed Grade	-2.5F	PC2-6400 5-5-5
		-2.5	PC2-6400 6-6-6
		-3	PC2-5300 4-4-4
		-3S	PC2-5300 5-5-5
		-3.7	PC2-4200 4-4-4
		-5	PC2-3200 3-3-3
11	Die Revision	-A	First
		-B	Second

1) Multiplying "Memory Density per I/O" with "Module Data Width" and dividing by 8 for Non-ECC and 9 for ECC modules gives the overall module memory density in MBytes as listed in column "Coding".

TABLE 24
DDR2 DRAM Nomenclature

Field	Description	Values	Coding
1	Qimonda Component Prefix	HYB	Constant
2	Interface Voltage [V]	18	SSTL_18
3	DRAM Technology	T	DDR2
4	Component Density [Mbit]	256	256 Mbit
		512	512 Mbit
		1G	1 Gbit
		2G	2 Gbit
5+6	Number of I/Os	40	×4
		80	×8
		16	×16
7	Product Variations	0 .. 9	Look up table
8	Die Revision	A	First
		B	Second
9	Package, Lead-Free Status	C	FBGA, lead-containing
		F	FBGA, lead-free
10	Speed Grade	-25F	DDR2-800 5-5-5
		-2.5	DDR2-800 6-6-6
		-3	DDR2-667 4-4-4
		-3S	DDR2-667 5-5-5
		-3.7	DDR2-533 4-4-4
		-5	DDR2-400 3-3-3



Table of Contents

1	Overview	3
1.1	Features	3
1.2	Description	4
2	Pin Configuration	6
2.1	Pin Configuration	6
3	Electrical Characteristics	15
3.1	Absolute Maximum Ratings	15
3.2	DC Operating Conditions	15
3.3	AC Characteristics	17
3.3.1	Speed Grades Definitions	17
3.3.2	AC Timing Parameters	17
3.3.3	ODT AC Electrical Characteristics	21
3.4	Currents Specifications and Conditions	22
3.4.1	Currents Test Conditions	26
3.4.2	On Die Termination (ODT) Current	26
4	SPD Codes	27
5	Package Outlines	35
6	Product Type Nomenclature	36
	Table of Contents	38

Edition 2006-09
Published by Qimonda AG
Gustav-Heinemann-Ring 212
D-81739 München, Germany
© Qimonda AG 2006.
All Rights Reserved.

Legal Disclaimer

The information given in this Internet Data Sheet shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Qimonda hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Qimonda Office.

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Qimonda Office.

Qimonda Components may only be used in life-support devices or systems with the express written approval of Qimonda, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.