



Integrated Device Technology, Inc.

HIGH-SPEED CMOS SYNCHRONOUS PRESETTABLE BINARY COUNTERS

IDT54/74AHCT161/163


FEATURES:

- Equivalent to ALS speeds and output drive over full temperature and voltage supply extremes
- $I_{OL} = 14\text{mA}$ over full military temperature range
- CMOS power levels ($5\mu\text{W}$ typ. static)
- Both CMOS and TTL output compatible
- Substantially lower input current levels than ALS ($5\mu\text{A}$ max)
- 100% product assurance screening to MIL-STD-883, Class B is available
- JEDEC standard pinout for DIP and LCC

DESCRIPTION:

The IDT54/74AHCT161/163 are high-speed synchronous modulo-16 binary counters built using advanced CEMOS™, a dual metal CMOS technology. They are synchronously presettable for application in programmable dividers and have two types of Count Enable inputs plus a Terminal Count output for versatility in forming synchronous multistage counters. The IDT54/74AHCT161/163 have asynchronous Master Reset inputs that override all other inputs and force the outputs LOW. The IDT54/74AHCT161/163 have Synchronous Reset inputs that override counting and parallel loading and allow the outputs to be simultaneously reset on the rising edge of the clock.

FUNCTIONAL BLOCK DIAGRAM





5

CEMOS is a trademark of Integrated Device Technology, Inc.

MILITARY AND COMMERCIAL TEMPERATURE RANGES

JULY 1986

PIN CONFIGURATIONS



*MR FOR '161
*SR FOR '163

ABSOLUTE MAXIMUM RATING⁽¹⁾

SYMBOL	RATING	COMMERCIAL	MILITARY	UNIT
V _{TERM}	Terminal Voltage with Respect to GND	-0.5 to +7.0	-0.5 to +7.0	V
T _A	Operation Temperature	0 to +70	-55 to +125	°C
T _{BIAS}	Temperature Under Bias	-55 to +125	-65 to +135	°C
T _{STG}	Storage Temperature	-55 to +125	-65 to +155	°C
I _{OUT}	DC Output Current	120	120	mA

NOTE:

1. Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:

T_A = 0°C to +70°C V_{CC} = 5.0V ± 5% Min. = 4.75V Max. = 5.25V (Commercial)
 T_A = -55°C to +125°C V_{CC} = 5.0V ± 10% Min. = 4.50V Max. = 5.50V (Military)
 V_{LC} = 0.2V
 V_{HC} = V_{CC} - 0.2V

SYMBOL	PARAMETER	TEST CONDITIONS ⁽¹⁾	MIN.	TYP ⁽²⁾	MAX.	UNIT	
V _{IH}	Input HIGH Level	Guaranteed Logic High Level	2.0	—	—	V	
V _{IL}	Input LOW Level	Guaranteed Logic Low Level	—	—	0.8	V	
I _{IH}	Input HIGH Current	V _{CC} = Max., V _{IN} = V _{CC}	—	—	5	μA	
I _{IL}	Input LOW Current	V _{CC} = Max., V _{IN} = GND	—	—	-5	μA	
I _{SC}	Short Circuit Current	V _{CC} = Max. ⁽³⁾	-60	-100	—	mA	
V _{OH}	Output HIGH Voltage	V _{CC} = 3V, V _{IN} = V _{LC} or V _{HC} , I _{OH} = -32μA	V _{HC}	V _{CC}	—	V	
		V _{CC} = Min. V _{IN} = V _{IH} or V _{IL}	I _{OH} = -150μA	V _{HC}	V _{CC}		
			I _{OH} = -1.0mA MIL.	2.4	4.3		
			I _{OH} = -2.6mA COM'L.	2.4	4.3		
V _{OL}	Output LOW Voltage	V _{CC} = 3V, V _{IN} = V _{LC} or V _{HC} , I _{OL} = 300μA	—	GND	V _{LC}	V	
		V _{CC} = Min. V _{IN} = V _{IH} or V _{IL}	I _{OL} = 300μA	—	GND		V _{LC}
			I _{OL} = 14mA MIL.	—	—		0.4
			I _{OL} = 24mA COM'L.	—	—		0.5

NOTES:

- For conditions shown as max. or min., use appropriate value specified under Electrical Characteristics for the applicable device type.
- Typical values are at V_{CC} = 5.0V, +25°C ambient and maximum loading.
- Not more than one output should be shorted at one time. Duration of the short circuit test should not exceed one second.

POWER SUPPLY CHARACTERISTICS (IDT54/74AHCT161)

$V_{LC} = 0.2V; V_{HC} = V_{CC} - 0.2V$

SYMBOL	PARAMETER	TEST CONDITIONS ⁽¹⁾		MIN.	TYP. ⁽²⁾	MAX.	UNIT
I_{CCQ}	Quiescent Power Supply Current	$V_{CC} = \text{Max.}$ $V_{IN} \geq V_{HC}; V_{IN} \leq V_{LC}$ $f_{CP} = f_i = 0$		—	0.001	1.5	mA
I_{CCT}	Power Supply Current per TTL Input HIGH	$V_{CC} = \text{Max.}$ $V_{IN} = 3.4V^{(4)}$		—	0.5	1.6	mA
I_{CCD}	Dynamic Power Supply Current	$V_{CC} = \text{Max.}$ Outputs Open Count Mode $CEP = CET = \overline{MR} =$ $\overline{PE} = V_{HC}$ $P_{0-3} = V_{LC}$	CP $V_{IN} \geq V_{HC}$ $V_{IN} \leq V_{LC}$ (AHCT)	—	0.3	—	mA/ MHz
I_{CC}	Total Power Supply Current ⁽⁴⁾	$V_{CC} = \text{Max.}$ Outputs Open $f_{CP} = 10\text{MHz}$, 50% Duty Cycle Count Mode $CEP = CET = \overline{MR} =$ $\overline{PE} = V_{HC}$ $P_{0-3} = V_{LC}$	CP $V_{IN} \geq V_{HC}$ $V_{IN} \leq V_{LC}$ (AHCT)	—	0.3	—	mA
			CP $V_{IN} = 3.4V$ or $V_{IN} = \text{GND}$	—	1.1	—	

POWER SUPPLY CHARACTERISTICS (IDT54/74AHCT163)

$V_{LC} = 0.2V; V_{HC} = V_{CC} - 0.2V$

SYMBOL	PARAMETER	TEST CONDITIONS ⁽¹⁾		MIN.	TYP. ⁽²⁾	MAX.	UNIT
I_{CCQ}	Quiescent Power Supply Current	$V_{CC} = \text{Max.}$ $V_{IN} \geq V_{HC}; V_{IN} \leq V_{LC}$ $f_{CP} = f_i = 0$		—	0.001	1.5	mA
I_{CCT}	Power Supply Current per TTL Input HIGH	$V_{CC} = \text{Max.}$ $V_{IN} = 3.4V^{(4)}$		—	0.5	1.6	mA
I_{CCD}	Dynamic Power Supply Current	$V_{CC} = \text{Max.}$ Outputs Open Count Mode $CEP = CET = \overline{SR} =$ $\overline{PE} = V_{HC}$ $P_{0-3} = V_{LC}$	CP $V_{IN} \geq V_{HC}$ $V_{IN} \leq V_{LC}$ (AHCT)	—	0.3	—	mA/ MHz
I_{CC}	Total Power Supply Current ⁽⁴⁾	$V_{CC} = \text{Max.}$ Outputs Open $f_{CP} = 1.0\text{MHz}$, 50% Duty Cycle Count Mode $CEP = CET = \overline{SR} =$ $\overline{PE} = V_{HC}$ $P_{0-3} = V_{LC}$	$V_{IN} \geq V_{HC}$ $V_{IN} \leq V_{LC}$ (AHCT)	—	0.3	—	mA
			$V_{IN} = 3.4V$ or $V_{IN} = \text{GND}$	—	1.1	—	

NOTES:

- For conditions shown as max. or min., use appropriate value specified under Electrical Characteristics for the applicable device type.
- Typical values are at $V_{CC} = 5.0V$, +25°C ambient and maximum loading.
- Per TTL driven input ($V_{IN} = 3.4V$); all other inputs at V_{CC} or GND.
- $I_{CC} = I_{\text{QUIESCENT}} + I_{\text{INPUTS}} + I_{\text{DYNAMIC}}$
 $I_{CC} = I_{CCQ} + I_{CCT}D_HN_T + I_{CCD}(f_{CP} + f_iN_i)$
 I_{CCQ} = Quiescent Current
 I_{CCT} = Power Supply Current for a TTL High Input ($V_{IN} = 3.4V$)
 D_H = Duty Cycle for TTL Inputs High
 N_T = Number of TTL Inputs at D_H
 I_{CCD} = Dynamic Current caused by an Input Transition pair (HLH or LHL)
 f_{CP} = Count Clock or Load Clock Frequency
 f_i = P_{0-3} Input Frequency (Load)
 N_i = Number of P_{0-3} Inputs at f_i (Load)

All currents are in milliamps and all frequencies are in megahertz.

5

DEFINITION OF FUNCTIONAL TERMS

PIN NAMES	DESCRIPTION
CEP	Count Enable Parallel Input
CET	Count Enable Trickle Input
CP	Clock Pulse Input (Active Rising Edge)
MR (161)	Asynchronous Master Reset Input (Active LOW)
SR (163)	Synchronous Reset Input (Active LOW)
P ₀₋₃	Parallel Data Inputs
PE	Parallel Enable Input (Active LOW)
Q ₀₋₃	Flip-Flop Outputs
TC	Terminal Count Output

TRUTH TABLE

SR ⁽¹⁾	PE	CET	CEP	ACTION ON THE RISING CLOCK EDGE (J)
L	X	X	X	Reset (Clear)
H	L	X	X	Load (P _n → Q _n)
H	H	H	H	Count (Increment)
H	H	L	X	No Change (Hold)
H	H	X	L	No Change (Hold)

NOTES:

- For AHCT163 only
- H = HIGH Voltage Level
 L = LOW Voltage Level
 X = Immaterial

SWITCHING CHARACTERISTICS OVER OPERATING RANGE

SYMBOL	PARAMETER	CONDITION	TYPICAL	MILITARY		COMMERCIAL		UNITS
				MIN	MAX	MIN	MAX	
t _{PLH} t _{PHL}	Propagation Delay CP to Q _n (PE Input HIGH)	C _L = 50pF R _L = 500Ω	12.0	4.0	20.0	3.0	17.0	ns
t _{PLH} t _{PHL}	Propagation Delay CP to Q _n (PE Input LOW)		12.0	4.0	20.0	3.0	17.0	ns
t _{PLH} t _{PHL}	Propagation Delay CP to TC		18.0	5.0	30.0	5.0	26.0	ns
t _{PHL} t _{PHL}	Propagation Delay CET to TC		10.0	3.0	16.0	3.0	13.0	ns
t _{PHL}	Propagation Delay MR to Q _n (161)		10.0	6.0	27.0	6.0	24.0	ns
t _{PHL}	Propagation Delay MR to TC		10.0	6.0	31.0	6.0	28.0	ns
t _S (H) t _S (L)	Setup Time, HIGH or LOW P _n to CP		—	20.0	—	15.0	—	ns
t _H (H) t _H (L)	Hold Time, HIGH or LOW P _n to CP		—	0	—	0	—	ns
t _S (H) t _S (L)	Setup Time, HIGH or LOW PE or SR to CP		—	20.0	—	15.0	—	ns
t _H (H) t _H (L)	Setup Time, HIGH or LOW PE or SR to CP		—	0	—	0	—	ns
t _S (H) t _S (L)	Setup Time, HIGH or LOW CEP or CET to CP		—	25.0	—	20.0	—	ns
t _H (H) t _H (L)	Setup Time, HIGH or LOW CEP to CET to CP		—	0	—	0	—	ns
t _W (H) t _W (L)	Clock Pulse Width (Load) HIGH or LOW		—	20.0	—	15.0	—	ns
t _W (H) t _W (L)	Clock Pulse Width (Count) HIGH or LOW		—	20.0	—	15.0	—	ns
t _W (L)	MR Pulse Width, LOW (161)		—	20.0	—	15.0	—	ns
t _{REC}	Recovery Time MR to CP (161)		—	20.0	—	15.0	—	ns