

Connectivity

- Four 10-pin RJ connectors for microphone units DML5500/CML5500
- Four 8-pin shielded RJ connectors for delegate channel selectors, loudspeakers LS5500 or for voting panels
- Two 8-pin RJ connectors for the TMS digital data bus

Accessories

- Digital bus cable YPC to interconnect Delegate Controller Interfaces and to connect to the central unit

| | | |
|-------|-----|--------------|
| YPC1 | 1m | (71.67.4001) |
| YPC2 | 2m | (71.67.4002) |
| YPC5 | 3m | (71.67.4005) |
| YPC10 | 10m | (71.67.4010) |
| YPC20 | 20m | (71.67.4020) |



Description

The Delegate Controller Interface INT5500 allows connection of 4 delegate microphone units and 4 delegate channel selectors, voting panels or loudspeaker panels.

The controller interfaces are connected to the central unit in daisy chain. Replacement of a defective interface can be effected without shutting down the system ("hot swapping")

Specifications

| Technical Data | |
|-----------------|--------------------------|
| Dimensions (mm) | 85 (h) x 182 (w) x 42(d) |
| Mounting | See drawings on reverse |
| Weight (g) | +/- 700 |
| Colour | Stainless steel |
| Housing | Metal |
| Part Number | 71.67.5046 |

