

F SERIES

TFX12 V2.1



POWERMAN 300W 12V PSU

IP-P300F1-0



FEATURES

- | Support Intel TFX12 V2.1
- | EMI Meet FCC Part 15 Class B, CISPR 22 Class B
- | UL/cUL 60950, TUV and CB EN 60950 certified
- | MTBF 100KHRs @ 25°C per MIL-STD-217D/E
- | Operating ambient +10°C minimum to +50°C maximum

Specifications

- | Input Voltage 115/230Vac
- | Input Frequency 60/50 Hz
- | Efficiency >75% at full load
- | Leakage Current 3.5mA maximum at 230Vac test
- | Hold-up Time 17mS minimum with full load
- | Output Rise Time 0.1 ~ 20mS

Dimensions

- | 180(W) x 80(L) x 45(H) mm

SAFETY



Tested to Comply
With FCC Standards
FOR HOME OR OFFICE USE



CB



Model	MAX OUTPUT	AC Input	Max Output Current									
			+12V1/Peak	+12V2/Peak	+5V	+3.3V	-5V	-12V	5VSB	MAX1	MAX2	MAX3
IP-P300F1-0	300W	115/230V, 7/4A, 60/50Hz	16/18A	16/18A	22A	18A	NA	0.5A	2/2.5A	130W	290W	240W

MAX1 : 5V & 3.3V Total Output
MAX2 : 5V, 3.3V, 12V1, 12V2, 12V3 & 12V4 Total Output
MAX3 : 12V1, 12V2, 12V3 & 12V4 Total Output



Contemporary & Innovative
www.in-win.com