


OptiMOS[®]-T Power-Transistor
Features

- N-channel - Logic Level - Enhancement mode
- Automotive AEC Q101 qualified
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- **Green package (lead free)**
- Ultra low Rds(on)
- 100% Avalanche tested
- ESD Class 1C (HBM)
EIA/JESD22-A114-B

Product Summary

| | | |
|--------------------------------|------|----|
| V_{DS} | 55 | V |
| $R_{DS(on),max}$ (SMD version) | 21.3 | mΩ |
| I_D | 25 | A |


PG-TO263-3-2




PG-TO262-3-1



PG-TO220-3-1



| Type | Package | Ordering Code | Marking |
|----------------|--------------|---------------|---------|
| IPB25N06S3L-22 | PG-TO263-3-2 | SP0000-87994 | 3N06L22 |
| IPI25N06S3L-22 | PG-TO262-3-1 | SP0000-87996 | 3N06L22 |
| IPP25N06S3L-22 | PG-TO220-3-1 | SP0000-87993 | 3N06L22 |


Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|--|----------------|--|--------------|------|
| Continuous drain current ¹⁾ | I_D | $T_C=25\text{ °C}$, $V_{GS}=10\text{ V}$ | 25 | A |
| | | $T_C=100\text{ °C}$, $V_{GS}=10\text{ V}^{2)}$ | 25 | |
| Pulsed drain current ²⁾ | $I_{D,pulse}$ | $T_C=25\text{ °C}$ | 100 | |
| Avalanche energy, single pulse ³⁾ | E_{AS} | $I_D=12\text{ A}$ | 60 | mJ |
| Drain gate voltage ²⁾ | V_{DG} | | 55 | V |
| Gate source voltage ⁴⁾ | V_{GS} | | ±16 | V |
| Power dissipation | P_{tot} | $T_C=25\text{ °C}$ | 50 | W |
| Operating and storage temperature | T_j, T_{stg} | | -55 ... +175 | °C |
| IEC climatic category; DIN IEC 68-1 | | | 55/175/56 | |



| Parameter | Symbol | Conditions | Values | | | Unit |
|--|------------|--|--------|------|------|------|
| | | | min. | typ. | max. | |
| Thermal characteristics²⁾ | | | | | | |
| Thermal resistance, junction - case | R_{thJC} | | - | - | 3.3 | K/W |
| Thermal resistance, junction - ambient, leaded | R_{thJA} | | - | - | 62 | |
| SMD version, device on PCB | R_{thJA} | minimal footprint | - | - | 62 | |
| | | 6 cm ² cooling area ⁵⁾ | - | - | 40 | |

Electrical characteristics, at $T_j=25\text{ °C}$, unless otherwise specified

Static characteristics

| | | | | | | |
|----------------------------------|---------------|---|-----|------|------|---------------|
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | $V_{GS}=0\text{ V}, I_D=1\text{ mA}$ | 55 | - | - | V |
| Gate threshold voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_D=20\text{ }\mu\text{A}$ | 1.2 | 1.7 | 2.2 | |
| Zero gate voltage drain current | I_{DSS} | $V_{DS}=55\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$ | - | 0.01 | 1 | μA |
| | | $V_{DS}=55\text{ V}, V_{GS}=0\text{ V}, T_j=125\text{ °C}^{2)}$ | - | 1 | 100 | |
| Gate-source leakage current | I_{GSS} | $V_{GS}=16\text{ V}, V_{DS}=0\text{ V}$ | - | 1 | 100 | nA |
| Drain-source on-state resistance | $R_{DS(on)}$ | $V_{GS}=5\text{ V}, I_D=11\text{ A}$ | - | 32.9 | 39.9 | m Ω |
| | | $V_{GS}=5\text{ V}, I_D=11\text{ A},$ SMD version | - | 32.6 | 39.6 | |
| | | $V_{GS}=10\text{ V}, I_D=17\text{ A}$ | - | 18.4 | 21.6 | |
| | | $V_{GS}=10\text{ V}, I_D=17\text{ A},$ SMD version | - | 18.1 | 21.3 | |



| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Dynamic characteristics²⁾

| | | | | | | |
|------------------------------|--------------|---|---|------|---|----|
| Input capacitance | C_{iss} | $V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$ | - | 2260 | - | pF |
| Output capacitance | C_{oss} | | - | 283 | - | |
| Reverse transfer capacitance | C_{rss} | | - | 270 | - | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DD}=27.5\text{ V},$ $V_{GS}=10\text{ V}, I_D=25\text{ A},$ $R_G=14.8\ \Omega$ | - | 9 | - | ns |
| Rise time | t_r | | - | 26 | - | |
| Turn-off delay time | $t_{d(off)}$ | | - | 30 | - | |
| Fall time | t_f | | - | 43 | - | |

Gate Charge Characteristics²⁾

| | | | | | | |
|-----------------------|---------------|--|---|-----|----|----|
| Gate to source charge | Q_{gs} | $V_{DD}=11\text{ V}, I_D=25\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$ | - | 11 | - | nC |
| Gate to drain charge | Q_{gd} | | - | 6 | - | |
| Gate charge total | Q_g | | - | 31 | 47 | |
| Gate plateau voltage | $V_{plateau}$ | | - | 4.7 | - | V |

Reverse Diode

| | | | | | | |
|--|---------------|---|-----|-----|-----|----|
| Diode continuous forward current ²⁾ | I_S | $T_C=25\text{ }^\circ\text{C}$ | - | - | 25 | A |
| Diode pulse current ²⁾ | $I_{S,pulse}$ | | - | - | 100 | |
| Diode forward voltage | V_{SD} | $V_{GS}=0\text{ V}, I_F=25\text{ A},$ $T_C=25\text{ }^\circ\text{C}$ | 0.6 | 0.9 | 1.3 | V |
| Reverse recovery time ²⁾ | t_{rr} | $V_R=27.5\text{ V}, I_F=I_S,$ $di_F/dt=100\text{ A}/\mu\text{s}$ | - | 32 | - | ns |
| Reverse recovery charge ²⁾ | Q_{rr} | | - | 28 | - | |

¹⁾ Current is limited by bondwire; with an $R_{thJC} = 3.3\text{ K/W}$ the chip is able to carry 31 A at 25°C. For detailed information see Application Note ANPS071E at www.infineon.com/optimos

²⁾ Defined by design. Not subject to production test.

³⁾ See diagrams 12 and 13.


⁴⁾ Qualified at -5V and +16V.

⁵⁾ Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical in still air.




1 Power dissipation

$P_{tot} = f(T_C); V_{GS} \geq 4 \text{ V}$



2 Drain current


$I_D = f(T_C); V_{GS} \geq 4 \text{ V}$



3 Safe operating area

$I_D = f(V_{DS}); T_C = 25 \text{ °C}; D = 0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$

parameter: $D = t_p/T$






5 Typ. output characteristics

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



7 Typ. transfer characteristics


$I_D = f(V_{GS}); V_{DS} = 4\text{ V}$

parameter: T_j



8 Typ. drain-source on-state resistance

$R_{DS(on)} = f(T_j); I_D = 25\text{ A}; V_{GS} = 10\text{ V}$






9 Typ. gate threshold voltage


$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}$

parameter: I_D



10 Typ. capacitances


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$



11 Typical forward diode characteristics

$I_F = f(V_{SD})$


parameter: T_j



12 Typ. avalanche characteristics

$I_{AV} = f(t_{AV})$

parameter: $T_{j(start)}$






13 Typical avalanche energy


$E_{AS} = f(T_j)$;

parameter: I_D



14 Drain-source breakdown voltage


$V_{BR(DSS)} = f(T_j); I_D = 1 \text{ mA}$




15 Typ. gate charge

$V_{GS} = f(Q_{gate}); I_D = 25 \text{ A pulsed}$

parameter: V_{DD}



16 Gate charge waveforms





Published by
Infineon Technologies AG
St.-Martin-Straße 53
D-81541 München
© Infineon Technologies AG 2004
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as a guarantee of characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Information

For further information on technology, delivery terms and conditions and prices, please contact your nearest Infineon Technologies Office (www.infineon.com)

Warnings

Due to technical requirements, components may contain dangerous substances.
For information on the types in question, please contact your nearest Infineon Technologies Office.

Infineon Technologies' components may only be used in life-support devices or systems with the expressed written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.