

isc N-Channel MOSFET Transistor


IRF430

DESCRIPTION

- silicon Gate for fast switching at elevate
- rugged
- low drive requirements
- ease of paralleling
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


APPLICATIONS

- high speed applications such as
Switching power supplies, AC and DC motor controls
relay and solenoid driver.



ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage ($V_{GS}=0$)	500	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current-continuous@ $TC=25^\circ\text{C}$	4.5	A
P_{tot}	Total Dissipation@ $TC=25^\circ\text{C}$	75	W
T_j	Max. Operating Junction Temperature	-55~150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$



THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	0.83	$^\circ\text{C}/\text{W}$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	30	$^\circ\text{C}/\text{W}$

isc N-Channel Mosfet Transistor

IRF430

• ELECTRICAL CHARACTERISTICS (T_c=25°C)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYPE	MAX	UNIT
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0; I _D =0.25mA	500			V
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} = V _{GS} ; I _D =250μA	2		4	V
R _{DS(ON)}	Drain-Source On-stage Resistance	V _{GS} =10V; I _D =2.5A			1.5	Ω
I _{GSS}	Gate Source Leakage Current	V _{GS} =±20V; V _{DS} =0			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =500V; V _{GS} =0			250	uA
V _{SD}	Diode Forward Voltage	I _F =4.5A; V _{GS} =0			1.4	V
C _{iss}	Input Capacitance	V _{DS} =25V; V _{GS} =0V; f _T =1MHz		600		pF
C _{rss}	Reverse Transfer Capacitance			100		
C _{oss}	Output Capacitance			30		
t _r	Rise Time	I _D =4.5A; V _{DD} =250V; R _G =12Ω		11	17	ns
t _{d(on)}	Turn-on Telay Time			15	23	
t _f	Fall Time			35	53	
t _{d(off)}	Turn-off Delay Time			15	23	

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.