


IRGTIN075K06

"HALF-BRIDGE" IGBT INT-A-PAK
Low conduction loss IGBT

- Rugged Design
- Simple gate-drive
- Switching-Loss Rating includes all "tail" losses
- Short circuit rated



$$V_{CE} = 600V$$


$$I_C = 75A$$

$$V_{CE(ON)} < 2.7V$$

$$t_{sc} > 10\mu s$$

Description

IR's advanced IGBT technology is the key to this line of INT-A-PAK Power Modules. The efficient geometry and unique processing of the IGBT allow higher current densities than comparable bipolar power module transistors, while at the same time requiring the simpler gate-drive of the familiar power MOSFET. These modules are short circuit rated for applications such as motor control requiring this important feature.



Absolute Maximum Ratings

Parameter	Description	Value	Units
V_{CES}	Continuous collector to emitter voltage	600	V
$I_C @ T_C = 25^\circ C$	Continuous collector current	95	A
$I_C @ T_C = 85^\circ C$	Continuous collector current	55	
$I_C @ T_C = 100^\circ C$	Continuous collector current	40	
I_{LM}	Peak switching current	150	
I_{FM}	Peak diode forward current (1)	150	V
V_{GE}	Gate to emitter voltage	± 20	
V_{ISOL}	RMS isolation voltage, any terminal to case, $t = 1$ min	2500	W
$P_D @ T_C = 25^\circ C$	Power dissipation	391	
T_J	Operating junction temperature range	-40 to 150	www.DataSheet4U.com
T_{STG}	Storage temperature range	-40 to 125	

(1) Duration limited by max junction temperature.

IRGTIN075K06

Target Data

Electrical Characteristics - $T_J = 25^\circ\text{C}$, unless otherwise stated

Parameter	Description	Min	Typ	Max	Units	Test Conditions
BV_{CES}	Collector-to-emitter breakdown voltage	600	—	—	V	$V_{GE} = 0V, I_C = 1mA$
$V_{CE(ON)}$	Collector-to-emitter voltage	—	—	2.7		$V_{GE} = 15V, I_C = 75A$
		—	2.7	—		$V_{GE} = 15V, I_C = 75A, T_J = 125^\circ\text{C}$
V_{FM}	Diode forward voltage - maximum	—	1.8	2.0		$I_F = 75A, V_{GE} = 0V$
		—	1.75	—		$I_F = 75A, V_{GE} = 0V, T_J = 125^\circ\text{C}$
V_{GEth}	Gate threshold voltage	3.0	—	5.5	mV/°C	$I_C = 500\mu A$
DV_{GEth}	Threshold voltage temperature coefficient	—	-11	—		$V_{CE} = V_{GE}, I_C = 500\mu A$
g_{fs}	Forward transconductance	34	—	58		$V_{CE} = 25V, I_C = 75A$
I_{CES}	Collector-to-emitter leakage current	—	—	1		$V_{GE} = 0V, V_{CE} = 600V$
		—	—	10		$V_{GE} = 0V, V_{CE} = 600V, T_J = 125^\circ\text{C}$
I_{GES}	Gate-to-emitter leakage current	—	—	± 1	μA	$V_{GE} = \pm 20V$

Dynamic Characteristics - $T_J = 125^\circ\text{C}$, unless otherwise stated

Parameter	Description	Min	Typ	Max	Units	Test Conditions
E_{on}	Turn-on switching energy	—	0.04	—	mJ/A	$R_G = 15\Omega, V_{CC} = 300V$
E_{off} (1)	Turn-off switching energy	—	0.06	—		$I_C = 75A, L_S = 100nH$
E_{ts} (1)	Total switching energy	—	—	0.12		$V_{GE} = \pm 15V$
$t_{d(on)}$	Turn-on delay time	—	200	—	ns	$R_G = 15\Omega, V_{CC} = 300V$
t_r	Rise time	—	500	—		$I_C = 75A$
$t_{d(off)}$	Turn-off delay time	—	250	—		$V_{GE} = \pm 15V$
t_f	Fall time	—	120	—		Resistive load, $T_J = 25^\circ\text{C}$
I_{rr}	Diode peak recovery current	—	27	—	A	$R_G = 15\Omega, V_{CC} = 300V$
t_{rr}	Diode recovery time	—	110	—	ns	$I_C = 75A$
Q_{rr}	Diode recovery charge	—	1.7	—	μC	$V_{GE} = \pm 15V$
Q_{ge}	Gate-to-emitter charge (turn-on)	26	—	42	nC	$V_{CC} = 480V$
Q_{gc}	Gate-to-collector charge (turn-on)	70	—	140		$I_C = 54A$
Q_g	Total gate charge (turn-on)	150	—	280		$V_{GE} = \pm 15V$
C_{ies}	Input capacitance	—	5800	—	pF	$V_{GE} = 0V$
C_{oes}	Output capacitance	—	660	—		$V_{CC} = 30V$
C_{res}	Reverse transfer capacitance	—	80	—		$f = 1MHz$
t_{sc}	Short circuit withstand time	10	—	—	μs	$V_{CC} = 360V, V_{GE} = \pm 15V$ Min $R_G = 15\Omega, V_{CEP} = 500V$

(1) Includes tail losses

Thermal and Mechanical Characteristics

Parameter	Description	Typ	Max	Units
R_{thJC} (IGBT)	Thermal resistance, junction to case, each IGBT	—	0.32	$^\circ\text{C/W}$
R_{thJC} (Diode)	Thermal resistance, junction to case, each diode	—	0.48	
R_{thCS} (Module)	Thermal resistance, case to sink	0.041	0.100	
Wt	Weight of module	150	—	g

Refer to Section D - page D-17 for Package Outline11 -INT-A-PAK, New -Half Bridge

DataSheet4U.com