


**RADIATION HARDENED
POWER MOSFET
SURFACE MOUNT (SMD-2)**
**100V, P-CHANNEL
REF: MIL-PRF-19500/713**

Product Summary

Part Number	Radiation Level	RDS(on)	I _D	QPL Part Number
IRHNA597160	100 kRads(Si)	0.049Ω	-47A	JANSR2N7550U2
IRHNA593160	300 kRads(Si)	0.049Ω	-47A	JANSF2N7550U2


Description

IR HiRel R5 technology provides high performance power MOSFETs for space applications. These devices have been characterized for Single Event Effects (SEE) with useful performance up to an LET of 80 (MeV/(mg/cm²)). The combination of low RDS(on) and low gate charge reduces the power losses in switching applications such as DC to DC converters and motor control. These devices retain all of the well established advantages of MOSFETs such as voltage control, fast switching and temperature stability of electrical parameters.

Features

- Single Event Effect (SEE) Hardened
- Ultra Low RDS(on)
- Low Total Gate Charge
- Simple Drive Requirements
- Hermetically Sealed
- Surface Mount
- Ceramic Package
- Light Weight

Absolute Maximum Ratings

Pre-Irradiation			
Symbol	Parameter	Value	Units
I _{D1} @ V _{GS} = -12V, T _C = 25°C	Continuous Drain Current	-47	A
I _{D2} @ V _{GS} = -12V, T _C = 100°C	Continuous Drain Current	-30	
I _{DM} @ T _C = 25°C	Pulsed Drain Current ①	-188	
P _D @ T _C = 25°C	Maximum Power Dissipation	250	W
	Linear Derating Factor	2.0	W/°C
V _{GS}	Gate-to-Source Voltage	± 20	V
E _{AS}	Single Pulse Avalanche Energy ②	400	mJ
I _{AR}	Avalanche Current ①	-47	A
E _{AR}	Repetitive Avalanche Energy ①	25	mJ
dv/dt	Peak Diode Recovery dv/dt ③	-10	V/ns
T _J	Operating Junction and Storage Temperature Range	-55 to + 150	°C
T _{STG}	Lead Temperature	300 (for 5sec)	
	Weight	3.3 (Typical)	g

For Footnotes, refer to the page 2.

Pre-Irradiation
Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (Unless Otherwise Specified)

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	-100	—	—	V	$\text{V}_{\text{GS}} = 0\text{V}$, $\text{I}_D = -1.0\text{mA}$
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	-0.1	—	$\text{V}/^\circ\text{C}$	Reference to 25°C , $\text{I}_D = -1.0\text{mA}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-State R _s tance	—	—	0.049	Ω	$\text{V}_{\text{GS}} = -12\text{V}$, $\text{I}_{\text{D2}} = -30\text{A}$ ④
$\text{V}_{\text{GS}(\text{th})}$	Gate Threshold Voltage	-2.0	—	-4.0	V	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}$, $\text{I}_D = -1.0\text{mA}$
G_{fs}	Forward Transconductance	24	—	—	S	$\text{V}_{\text{DS}} = -15\text{V}$, $\text{I}_{\text{D2}} = -30\text{A}$ ④
I_{DSS}	Zero Gate Voltage Drain Current	—	—	-10	μA	$\text{V}_{\text{DS}} = -80\text{V}$, $\text{V}_{\text{GS}} = 0\text{V}$
		—	—	-25		$\text{V}_{\text{DS}} = -80\text{V}$, $\text{V}_{\text{GS}} = 0\text{V}$, $T_J = 125^\circ\text{C}$
I_{GSS}	Gate-to-Source Leakage Forward	—	—	-100	nA	$\text{V}_{\text{GS}} = -20\text{V}$
	Gate-to-Source Leakage Reverse	—	—	100		$\text{V}_{\text{GS}} = 20\text{V}$
Q_G	Total Gate Charge	—	—	170	nC	$\text{I}_{\text{D1}} = -47\text{A}$
Q_{GS}	Gate-to-Source Charge	—	—	65		$\text{V}_{\text{DS}} = -50\text{V}$
Q_{GD}	Gate-to-Drain ('Miller') Charge	—	—	30		$\text{V}_{\text{GS}} = -12\text{V}$
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	—	30	ns	$\text{V}_{\text{DD}} = -50\text{V}$
t_{r}	Rise Time	—	—	100		$\text{I}_{\text{D1}} = -47\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	—	100		$R_G = 2.35\Omega$
t_f	Fall Time	—	—	120		$\text{V}_{\text{GS}} = -12\text{V}$
$L_s + L_D$	Total Inductance	—	4.0	—	nH	Measured from center of Drain pad to center of Source pad
C_{iss}	Input Capacitance	—	6240	—	pF	$\text{V}_{\text{GS}} = 0\text{V}$
C_{oss}	Output Capacitance	—	1570	—		$\text{V}_{\text{DS}} = -25\text{V}$
C_{rss}	Reverse Transfer Capacitance	—	115	—		$f = 1.0\text{MHz}$

Source-Drain Diode Ratings and Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	-47	A	
I_{SM}	Pulsed Source Current (Body Diode) ①	—	—	-188		
V_{SD}	Diode Forward Voltage	—	—	-5.0	V	$T_J = 25^\circ\text{C}$, $I_S = -47\text{A}$, $\text{V}_{\text{GS}} = 0\text{V}$ ④
t_{rr}	Reverse Recovery Time	—	—	230	ns	$T_J = 25^\circ\text{C}$, $I_F = -47\text{A}$, $\text{V}_{\text{DD}} \leq -50\text{V}$
Q_{rr}	Reverse Recovery Charge	—	—	1.6		$dI/dt = 100\text{A}/\mu\text{s}$ ④
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible (turn-on is dominated by $L_s + L_D$)				

Thermal Resistance

Symbol	Parameter	Min.	Typ.	Max.	Units
$R_{\theta\text{JC}}$	Junction-to-Case	—	—	0.50	$^\circ\text{C/W}$
$R_{\theta\text{-PCB}}$	Junction-to-PC Board (soldered to 1 inch square cu clad board)	—	1.6	—	

Footnotes:

- ① Repetitive Rating; Pulse width limited by maximum junction temperature.
- ② $\text{V}_{\text{DD}} = -50\text{V}$, starting $T_J = 25^\circ\text{C}$, $L = 0.36\text{mH}$, Peak $I_L = -47\text{A}$, $\text{V}_{\text{GS}} = -12\text{V}$
- ③ $I_{\text{SD}} \leq -47\text{A}$, $dI/dt \leq -450\text{A}/\mu\text{s}$, $\text{V}_{\text{DD}} \leq -100\text{V}$, $T_J \leq 150^\circ\text{C}$
- ④ Pulse width $\leq 300\ \mu\text{s}$; Duty Cycle $\leq 2\%$
- ⑤ Total Dose Irradiation with V_{GS} Bias. -12 volt V_{GS} applied and $\text{V}_{\text{DS}} = 0$ during irradiation per MIL-STD-750, Method 1019, condition A.
- ⑥ Total Dose Irradiation with V_{DS} Bias. -80 volt V_{DS} applied and $\text{V}_{\text{GS}} = 0$ during irradiation per MIL-STD-750, Method 1019, condition A.

Radiation Characteristics

IR HiRel radiation hardened MOSFETs are tested to verify their radiation hardness capability. The hardness assurance program at IR HiRel is comprised of two radiation environments. Every manufacturing lot is tested for total ionizing dose (per notes 5 and 6) using the TO-3 package. Both pre- and post-irradiation performance are tested and specified using the same drive circuitry and test conditions in order to provide a direct comparison.

Table 1. Electrical Characteristics @ $T_j = 25^\circ\text{C}$, Post Total Dose Irradiation ⑤⑥

Symbol	Parameter	100 kRads (Si)¹		300 kRads (Si)²		Units	Test Conditions
		Min.	Max.	Min.	Max.		
BV_{DSS}	Drain-to-Source Breakdown Voltage	-100	—	-100	—	V	$\text{V}_{\text{GS}} = 0\text{V}$, $\text{I}_D = -1.0\text{mA}$
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	-2.0	-4.0	-2.0	-5.0	V	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}$, $\text{I}_D = -1.0\text{mA}$
I_{GSS}	Gate-to-Source Leakage Forward	—	-100	—	-100	nA	$\text{V}_{\text{GS}} = -20\text{V}$
I_{GSS}	Gate-to-Source Leakage Reverse	—	100	—	100	nA	$\text{V}_{\text{GS}} = 20\text{V}$
I_{DSS}	Zero Gate Voltage Drain Current	—	-10	—	-10	μA	$\text{V}_{\text{DS}} = -80\text{V}$, $\text{V}_{\text{GS}} = 0\text{V}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source ④ On-State Resistance (TO-3)	—	0.05	—	0.05	Ω	$\text{V}_{\text{GS}} = -12\text{V}$, $\text{I}_{\text{D2}} = -30\text{A}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source ④ On-State Resistance (SMD-2)	—	0.049	—	0.049	Ω	$\text{V}_{\text{GS}} = -12\text{V}$, $\text{I}_{\text{D2}} = -30\text{A}$
V_{SD}	Diode Forward Voltage	—	-5.0	—	-5.0	V	$\text{V}_{\text{GS}} = 0\text{V}$, $\text{I}_S = -47\text{A}$

1. Part number IRHNA597160 (JANSR2N7550U2)

2. Part numbers IRHNA593160 (JANSF2N7550U2)

IR HiRel radiation hardened MOSFETs have been characterized in heavy ion environment for Single Event Effects (SEE). Single Event Effects characterization is illustrated in Fig. a and Table 2.

Table 2. Typical Single Event Effect Safe Operating Area

Ion	LET (MeV/(mg/cm²))	Energy (MeV)	Range (μm)	V_{DS} (V)					
				@V_{GS}= 0V	@V_{GS}= 5V	@V_{GS}= 10V	@V_{GS}= 15V	@V_{GS}= 17.5V	@V_{GS}= 20V
Br	37.9	252.6	33.1	-100	-100	-100	-100	-100	-100
I	59.7	314	30.5	-100	-100	-100	-100	-100	-75
Au	82.3	350	28.4	-100	-100	-100	-30	—	—




Fig a. Typical Single Event Effect, Safe Operating Area

For Footnotes, refer to the page 2.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature




Fig 5. Typical Capacitance Vs.
Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs.
Gate-to-Source Voltage

Pre-Irradiation




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10. Maximum Avalanche Energy Vs. Drain Current




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

Pre-Irradiation




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 13a. Gate Charge Waveform




Fig 13b. Gate Charge Test Circuit




Fig 14a. Switching Time Test Circuit





Fig 14b. Switching Time Waveforms

Case Outline and Dimensions — SMD-2



NOTES:

1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
 2. CONTROLLING DIMENSION: INCH.
 3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
- (4) DIMENSION INCLUDES METALLIZATION FLASH.
 (5) DIMENSION DOES NOT INCLUDE METALLIZATION FLASH.

PAD ASSIGNMENTS

MOSFET	
1	= DRAIN
2	= GATE
3	= SOURCE

Infineon Technologies Service Center: USA Tel: +1 (866) 951-9519 and International Tel: +49 89 234 65555
 Leominster, Massachusetts 01453, USA Tel: +1 (978) 534-5776
 San Jose, California 95134, USA Tel: +1 (408) 434-5000
 Data and specifications subject to change without notice.

IMPORTANT NOTICE

The information given in this document shall be in no event regarded as guarantee of conditions or characteristic. The data contained herein is a characterization of the component based on internal standards and is intended to demonstrate and provide guidance for typical part performance. It will require further evaluation, qualification and analysis to determine suitability in the application environment to confirm compliance to your system requirements.

With respect to any example hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind including without limitation warranties on non-infringement of intellectual property rights and any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's product and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of any customer's technical departments to evaluate the suitability of the product for the intended applications and the completeness of the product information given in this document with respect to applications.

For further information on the product, technology, delivery terms and conditions and prices, please contact your local sales representative or go to (www.infineon.com/hirel).

WARNING

Due to technical requirements products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.