

International **IR** Rectifier

RADIATION HARDENED POWER MOSFET THRU-HOLE (Low-Ohmic TO-257AA)

PD - 95819

IRHYB597Z30CM
30V, P-CHANNEL
R5™ TECHNOLOGY



Product Summary

Part Number	Radiation Level	R _{Ds(on)}	I _D
IRHYB597Z30CM	100K Rads (Si)	0.048Ω	-20A*
IRHYB593Z30CM	300K Rads (Si)	0.048Ω	-20A*

International Rectifier's R5™ technology provides high performance power MOSFETs for space applications. These devices have been characterized for Single Event Effects (SEE) with useful performance up to an LET of 80 (MeV/(mg/cm²)). The combination of low R_{Ds(on)} and low gate charge reduces the power losses in switching applications such as DC to DC converters and motor control. These devices retain all of the well established advantages of MOSFETs such as voltage control, fast switching, ease of paralleling and temperature stability of electrical parameters.

Features:

- Low R_{Ds(on)}
- Fast Switching
- Single Event Effect (SEE) Hardened
- Low Total Gate Charge
- Simple Drive Requirements
- Ease of Paralleling
- Hermetically Sealed
- Ceramic Eyelets
- Electrically Isolated
- Light Weight

Absolute Maximum Ratings

Pre-Irradiation

	Parameter		Units
I _D @ V _{GS} = -12V, T _C = 25°C	Continuous Drain Current	-20*	A
I _D @ V _{GS} = -12V, T _C = 100°C	Continuous Drain Current	-18	
I _{DM}	Pulsed Drain Current ①	-80	
P _D @ T _C = 25°C	Max. Power Dissipation	75	W
	Linear Derating Factor	0.6	W/C
V _{GS}	Gate-to-Source Voltage	±20	V
E _{AS}	Single Pulse Avalanche Energy ②	166	mJ
I _{AR}	Avalanche Current ①	-20	A
E _{AR}	Repetitive Avalanche Energy ①	7.5	mJ
dV/dt	Peak Diode Recovery dV/dt ③	-1.1	V/ns
T _J	Operating Junction	-55 to 150	°C
T _{STG}	Storage Temperature Range		
	Lead Temperature	300 (0.063in./1.6mm from case for 10s)	
	Weight	4.3 (Typical)	g

* Current is limited by package

For footnotes refer to the last page

www.irf.com

1

05/10/04

Electrical Characteristics @ $T_j = 25^\circ\text{C}$ (Unless Otherwise Specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
BVDSS	Drain-to-Source Breakdown Voltage	-30	—	—	V	$V_{GS} = 0\text{V}, I_D = -1.0\text{mA}$
$\Delta BVDSS/\Delta T_J$	Temperature Coefficient of Breakdown Voltage	—	-0.03	—	$^\circ\text{C}$	Reference to 25°C , $I_D = -1.0\text{mA}$
RDS(on)	Static Drain-to-Source On-State Resistance	—	—	0.048	Ω	$V_{GS} = -12\text{V}, I_D = -18\text{A}$ ④
$V_{GS(\text{th})}$	Gate Threshold Voltage	-2.0	—	-4.0	V	$V_{DS} = V_{GS}, I_D = -1.0\text{mA}$
g_{fs}	Forward Transconductance	12	—	—	S (mS)	$V_{DS} = -15\text{V}, I_{DS} = -18\text{A}$ ④
IDSS	Zero Gate Voltage Drain Current	—	—	-10	μA	$V_{DS} = -24\text{V}, V_{GS} = 0\text{V}$
		—	—	-25	μA	$V_{DS} = -24\text{V}, V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$
IGSS	Gate-to-Source Leakage Forward	—	—	-100	nA	$V_{GS} = -20\text{V}$
IGSS	Gate-to-Source Leakage Reverse	—	—	100	nA	$V_{GS} = 20\text{V}$
Qg	Total Gate Charge	—	—	45	nC	$V_{GS} = -12\text{V}, I_D = -20\text{A}$
Qgs	Gate-to-Source Charge	—	—	20	nC	$V_{DS} = -15\text{V}$
Qgd	Gate-to-Drain ('Miller') Charge	—	—	13	nC	
td(on)	Turn-On Delay Time	—	—	25	ns	$V_{DD} = -15\text{V}, I_D = -20\text{A}$
tr	Rise Time	—	—	100	ns	$V_{GS} = -12\text{V}, R_G = 7.5\Omega$
td(off)	Turn-Off Delay Time	—	—	50	ns	
tf	Fall Time	—	—	70	ns	
LS + LD	Total Inductance	—	6.8	—	nH	Measured from Drain lead (6mm / 0.25in. from package) to Source lead (6mm / 0.25in. from package)
Ciss	Input Capacitance	—	1690	—	pF	$V_{GS} = 0\text{V}, V_{DS} = -25\text{V}$
Coss	Output Capacitance	—	980	—	pF	$f = 1.0\text{MHz}$
Crss	Reverse Transfer Capacitance	—	130	—	pF	
Rg	Internal Gate Resistance	—	6.6	—	Ω	$f = 1.0\text{MHz}$, open drain

Source-Drain Diode Ratings and Characteristics

	Parameter	Min	Typ	Max	Units	Test Conditions
IS	Continuous Source Current (Body Diode)	—	—	-20*	A	
ISM	Pulse Source Current (Body Diode) ①	—	—	-80	A	
VSD	Diode Forward Voltage	—	—	-5.0	V	$T_j = 25^\circ\text{C}, I_S = -20\text{A}, V_{GS} = 0\text{V}$ ④
trr	Reverse Recovery Time	—	—	75	ns	$T_j = 25^\circ\text{C}, I_F = -20\text{A}, dI/dt \leq -100\text{A}/\mu\text{s}$
QRR	Reverse Recovery Charge	—	—	125	nC	$V_{DD} \leq -25\text{V}$ ④
ton	Forward Turn-On Time	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by LS + LD.				

* Current is limited by package

Thermal Resistance

	Parameter	Min	Typ	Max	Units	Test Conditions
RthJC	Junction-to-Case	—	—	1.67	$^\circ\text{C/W}$	
RthJA	Junction-to-Ambient	—	—	80	$^\circ\text{C/W}$	Typical Socket Mount

Note: Corresponding Spice and Saber models are available on International Rectifier Web site.

For footnotes refer to the last page

Radiation Characteristics

IRHYB597Z30CM

International Rectifier Radiation Hardened MOSFETs are tested to verify their radiation hardness capability. The hardness assurance program at International Rectifier is comprised of two radiation environments. Every manufacturing lot is tested for total ionizing dose (per notes 5 and 6) using the TO-3 package. Both pre- and post-irradiation performance are tested and specified using the same drive circuitry and test conditions in order to provide a direct comparison.

Table 1. Electrical Characteristics @ $T_j = 25^\circ\text{C}$, Post Total Dose Irradiation ⁽⁵⁾⁽⁶⁾

	Parameter	100KRads(Si) ¹		300KRads(Si) ²		Units	Test Conditions
		Min	Max	Min	Max		
BV_{DSS}	Drain-to-Source Breakdown Voltage	-30	—	-30	—	V	$\text{V}_{\text{GS}} = 0\text{V}, \text{I}_D = -1.0\text{mA}$
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	-2.0	-4.0	-2.0	-5.0		$\text{V}_{\text{GS}} = \text{V}_{\text{DS}}, \text{I}_D = -1.0\text{mA}$
I_{GSS}	Gate-to-Source Leakage Forward	—	-100	—	-100	nA	$\text{V}_{\text{GS}} = -20\text{V}$
I_{GSS}	Gate-to-Source Leakage Reverse	—	100	—	100		$\text{V}_{\text{GS}} = 20\text{ V}$
I_{DSS}	Zero Gate Voltage Drain Current	—	-10	—	-10	μA	$\text{V}_{\text{DS}} = -24\text{V}, \text{V}_{\text{GS}} = 0\text{V}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source ⁽⁴⁾ On-State Resistance (TO-3)	—	0.048	—	0.048	Ω	$\text{V}_{\text{GS}} = -12\text{V}, \text{I}_D = -18\text{A}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source On-State ⁽⁴⁾ Resistance(Low-OhmicTO-257AA)	—	0.048	—	0.048	Ω	$\text{V}_{\text{GS}} = -12\text{V}, \text{I}_D = -18\text{A}$
V_{SD}	Diode Forward Voltage ⁽⁴⁾	—	-5.0	—	-5.0	V	$\text{V}_{\text{GS}} = 0\text{V}, \text{I}_S = -18\text{A}$

1. Part number IRHYB597Z30CM

2. Part number IRHYB593Z30CM

International Rectifier radiation hardened MOSFETs have been characterized in heavy ion environment for Single Event Effects (SEE). Single Event Effects characterization is illustrated in Fig. a and Table 2.

Table 2. Single Event Effect Safe Operating Area

Ion	LET (MeV/(mg/cm ²))	Energy (MeV)	Range (μm)	V _{DS} (V)				
				@V _{GS} =0V	@V _{GS} =5V	@V _{GS} =10V	@V _{GS} =15V	@V _{GS} =20V
Br	37.5	278.5	36	-30	-30	-30	-30	-30
I	59.7	320	31	-30	-30	-30	-30	-25
Au	81.4	332	27	-30	-30	-30	-25	—




Fig a. Single Event Effect, Safe Operating Area

For footnotes refer to the last page

IRHYB597Z30CM




Fig 1. Typical Output Characteristics

Pre-Irradiation




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance
Vs. Temperature

Pre-Irradiation

IRHYB597Z30CM




Fig 5. Typical Capacitance Vs.
Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs.
Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode
Forward Voltage




Fig 8. Maximum Safe Operating Area

IRHYB597Z30CM

Pre-Irradiation




Fig 9. Maximum Drain Current Vs.
Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

Pre-Irradiation




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 13a. Basic Gate Charge Waveform

IRHYB597Z30CM




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 13b. Gate Charge Test Circuit


IRHYB597Z30CM

Pre-Irradiation

Footnotes:

- ① Repetitive Rating; Pulse width limited by maximum junction temperature.
- ② V_{DD} = -25V, starting T_J = 25°C, L=0.83mH
Peak I_L = - 20A, V_{GS} = -12V
- ③ I_{SD} ≤ - 20A, di/dt ≤ - 115A/μs,
V_{DD} ≤ - 30V, T_J ≤ 150°C
- ④ Pulse width ≤ 300 μs; Duty Cycle ≤ 2%
- ⑤ **Total Dose Irradiation with V_{GS} Bias.**
-12 volt V_{GS} applied and V_{DS} = 0 during irradiation per MIL-STD-750, method 1019, condition A.
- ⑥ **Total Dose Irradiation with V_{DS} Bias.**
- 24 volt V_{DS} applied and V_{GS} = 0 during irradiation per MIL-STD-750, method 1019, condition A.

Case Outline and Dimensions — Low-Ohmic TO-257AA (Tabless)



NOTES:

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M-1994.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
4. TO-257AA TABLESS IS A MODIFIED JEDEC OUTLINE TO-257AA.

LEAD ASSIGNMENTS

- 1 = DRAIN
- 2 = SOURCE
- 3 = GATE

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

IR LEOMINSTER : 205 Crawford St., Leominster, Massachusetts 01453, USA Tel: (978) 534-5776

TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information.
Data and specifications subject to change without notice. 05/2004