



1300MHz-1700MHz, 180W, 28V High Power RF LDMOS FETs


Description

The ITCH16180B2 is a 180-watt, internally matched LDMOS FET, designed for multicarrier WCDMA/PCS/DCS/LTE base station and ISM applications with frequencies from 1300 to 1700 MHz. It Can be used in Class AB/B and Class C for all typical cellular base station modulation formats.

•Typical Performance (On Innogrations fixture with device soldered):

VDD = 28 Volts, I_{DQ} = 800 mA, Pulse CW, Pulse Width=12 us, Duty cycle=10% .

Frequency	G _p (dB)	P _{-1dB} (dBm)	η _D @P ₋₁ (%)	P _{-3dB} (dBm)	η _D @P ₋₃ (%)
1390 MHz	18.8	52.8	55	53.7	57
1450 MHz	19.2	52	54	53.2	57.3
1529 MHz	18.4	51	54	52.2	57.6



•Typical Performance (On Innogrations fixture with device soldered):

VDD = 28 Volts, I_{DQ} = 800 mA, Pulse CW, Pulse Width=12 us, Duty cycle=10% .

Frequency	G _p (dB)	P _{-1dB} (dBm)	η _D @P ₋₁ (%)	P _{-3dB} (dBm)	η _D @P ₋₃ (%)
1350 MHz	19.6	52.4	53.5	53.5	57.8
1375 MHz	19.7	52.1	54	53.3	58.2
1400 MHz	19.4	51.7	53.5	53	58

•Typical Performance (On Innogrations fixture with device soldered):

VDD = 28 Volts, I_{DQ} = 800 mA, Pulse CW, Pulse Width=12 us, Duty cycle=10% .

Frequency	G _p (dB)	P _{-1dB} (dBm)	η _D @P ₋₁ (%)	P _{-3dB} (dBm)	η _D @P ₋₃ (%)
1440 MHz	19.8	52.2	55.8	53.2	59
1450 MHz	19.9	51.9	55	53	59
1470 MHz	19.8	51.5	54.9	52.7	59

Features

- High Efficiency and Linear Gain Operations
- Integrated ESD Protection
- Internally Matched for Ease of Use
- Excellent thermal stability, low HCI drift
- Large Positive and Negative Gate/Source Voltage Range for Improved Class C Operation
- Pb-free, RoHS-compliant

Table 1. Maximum Ratings

Rating	Symbol	Value	Unit
Drain--Source Voltage	V _{DSS}	70	Vdc
Gate--Source Voltage	V _{GS}	-10 to +10	Vdc
Operating Voltage	V _{DD}	+32	Vdc
Storage Temperature Range	T _{stg}	-65 to +150	°C
Case Operating Temperature	T _C	+150	°C



Operating Junction Temperature	T_J	+225	°C
--------------------------------	-------	------	----

Table 2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction to Case $T_C=85^\circ\text{C}, T_J=200^\circ\text{C}, \text{DC test}$	$R_{\theta JC}$	0.38	°C/W

Table 3. ESD Protection Characteristics

Test Methodology	Class
Human Body Model (per JESD22--A114)	Class 2

Table 4. Electrical Characteristics (TA = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

DC Characteristics

Drain-Source Breakdown Voltage ($V_{GS}=0\text{V}; I_D=100\mu\text{A}$)	V_{DSS}	65			V
Zero Gate Voltage Drain Leakage Current ($V_{DS} = 28\text{ V}, V_{GS} = 0\text{ V}$)	I_{DSS}			10	μA
Gate--Source Leakage Current ($V_{GS} = 6\text{ V}, V_{DS} = 0\text{ V}$)	I_{GSS}			1	μA
Gate Threshold Voltage ($V_{DS} = 28\text{V}, I_D = 600\ \mu\text{A}$)	$V_{GS(th)}$		1.6		V
Gate Quiescent Voltage ($V_{DD} = 28\text{ V}, I_{DQ} = 800\text{ mA}, \text{Measured in Functional Test}$)	$V_{GS(Q)}$	2.2	2.7	3.2	V

Functional Tests (In Innogrator 1.44-147GHz-demo, 50 ohm system) : $V_{DD} = 28\text{ Vdc}, I_{DQ} = 800\text{ mA}, f = 1470\text{ MHz}, \text{Pulse CW}, \text{Pulse Width}=12\ \mu\text{s}, \text{Duty cycle}=10\%$.

Power Gain	G_p		19.8		dB
Drain Efficiency@P3dB	η_D		59		%
1 dB Compression Point	P_{-1dB}		51.5		dBm
3dB Compression Point	P_{-3dB}		52.7		dBm
Input Return Loss	IRL		-10		dB

Load Mismatch (In Innogrator Test Fixture, 50 ohm system): $V_{DD} = 28\text{ Vdc}, I_{DQ} = 800\text{ mA}, f = 1500\text{ MHz}$

VSWR 10:1 at 180W pulse CW Output Power	No Device Degradation
---	-----------------------

Reference Circuit of Test Fixture Assembly Diagram




Figure 1. Test Circuit Component Layout (1440MHz~1470MHz)

Table 5. Test Circuit Component Designations and Values

Component	Description	Suggested Manufacturer	P/N
C1	Ceramic Capacitor,30pF	ATC	600F 300
C2	Ceramic Capacitor,2.2pF	ATC	600F 2R2
C3,C10	Ceramic Capacitor,27pF	ATC	600F 270
C5	Ceramic Capacitor,4.7pF	ATC	600F 4R7
C6	Ceramic Capacitor,3.9pF	ATC	600F 3R9
C7	Ceramic Capacitor,5.6pF	ATC	600F 5R6
C8	Ceramic Capacitor,3.0pF	ATC	600F 3R0
C9	Ceramic Capacitor,33pF	ATC	600F 330
C4,C11,C12	Capacitor,10uF	Murata	GRM32DF51H106
R1	Chip Resistor,10Ω	Digi-Key	P10ECT-ND
PCB	0.76mm [0.030"] thick, $\epsilon_r=3.48$, Rogers RO4350, 1 oz. copper		



TYPICAL CHARACTERISTICS





Figure 1. Power gain and drain efficiency as function of Pulse output power (1440-1470MHz)



Package Outline

Flanged ceramic package; 2 mounting holes; 2 leads (1—DRAIN、2—GATE、3—SOURCE)




UNIT	A	b	c	D	D ₁	E	E ₁	F	H	L	p	Q	q	U ₁	U ₂	W ₁	W ₂
mm	4.72	12.83	0.15	20.02	19.96	9.50	9.53	1.14	19.94	5.33	3.38	1.70	27.94	34.16	9.91	0.25	0.51
	3.43	12.57	0.08	19.61	19.66	9.30	9.25	0.89	18.92	4.32	3.12	1.45		33.91	9.65		
inches	0.186	0.505	0.006	0.788	0.786	0.374	0.375	0.045	0.785	0.210	0.133	0.067	1.100	1.345	0.390	0.01	0.02
	0.135	0.495	0.003	0.772	0.774	0.366	0.364	0.035	0.745	0.170	0.123	0.057		1.335	0.380		

OUTLINE VERSION	REFERENCE			EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA		
PKG-B2E					03/12/2013



Earless flanged ceramic package; 2 leads (1—DRAIN、2—GATE、3—SOURCE)



UNIT	A	b	c	D	D ₁	E	E ₁	F	H	L	Q	U ₁	U ₂	W ₂
mm	4.72	12.83	0.15	20.02	19.96	9.50	9.53	1.14	19.94	5.33	1.70	20.70	9.91	0.25
	3.43	12.57	0.08	19.61	19.66	9.30	9.25	0.89	18.92	4.32	1.45	20.45	9.65	
inches	0.186	0.505	0.006	0.788	0.786	0.374	0.375	0.045	0.785	0.210	0.067	0.815	0.390	0.010
	0.135	0.495	0.003	0.772	0.774	0.366	0.364	0.035	0.745	0.170	0.057	0.805	0.380	

OUTLINE VERSION	REFERENCE			EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA		
PKG-B2					03/12/2013



Revision history

Table 6. Document revision history

Date	Revision	Datasheet Status
2017/01/23	Rev 1.0	Preliminary Datasheet
2017/03/17	Rev 2.0	Preliminary Datasheet

Disclaimers

Specifications are subject to change without notice. Innogrations believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Innogrations for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Innogrations. Innogrations makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Innogrations in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Innogrations products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Innogrations product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility. For any concerns or questions related to terms or conditions, pls check with Innogrations and authorized distributors

Copyright © by Innogrations (Suzhou) Co.,Ltd.