


IWR 0520F; IWR0520FM; IWR0520U; IWR 0260U; IWR0520UM

HIGH VOLTAGE FAST RECTIFIER DIODES & DIODES ARRAYS



MAXIMUM RATINGS

Rating	Symbol	IWR 0520F IWR 0520FM	IWR 0520U	IWR 0260 U	IWR 0520UM	Unit.
Peak Repetitive Reverse Voltage	U_{RR}	200	200	600	200	V
Peak Rectified Forward Current $t_j=175^\circ\text{C}$	I_F	5	5	2	5	A
Nonrepetitive Peak Surge Current , $t \leq 8$ ms	I_{FS}	35	35	14	35	A
Operating Junction Temperature	T_J	+175				$^\circ\text{C}$
Storage Temperature	T_{STG}	-65 ... +175				$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS for $T_{AMB}=25^\circ\text{C}$

Rating (Mode of measure)	Symbol	IWR 0520F IWR 0520FM	IWR 0520U	IWR 0260 U	IWR 0520UM	Unit.
Maximum Instantaneous Forward Voltage * (I_{FMAX})	U_R	1,1	1,2	1,7	1,2	V
Maximum Instantaneous Reverse Current * (U_{RRMAX})	I_R	50				μA
Maximum Reverse Recovery Time ($I_F=1$ A, $di/dt=50$ A/ μs , $U_{RR}=30$ V, $I_{REC}=10\%$ I_R)	t_{REC}	250	25	60	25	Ns
Maximum Thermal Resistance, Junction to Case	$R_{\theta JC}$	4,5				$^\circ\text{C/W}$

* $t_p \leq 300$ μs , $Q \geq 50$

IWR 0520F; IWR0520U; IWR 0260U – diodes (pinning: pin 2 – cathode , pin 3 - anode)

IWR0520FM; IWR0520UM – diode array with common cathode (pinning: pin 1- anode 1, pin 2- common cathode, pin 3 - anode 2)



Korzhenevsky 12, Minsk, 220108, Republic of Belarus

Fax: +375 (17) 278 28 22,

Phone: +375 (17) 278 07 11, 212 24 70, 212 24 61,
212 69 16

E-mail: office@bms.by

URL: www.bms.by

BELMICROSYSTEMS