




**High Voltage, High Gain
BIMOSFET™**
**IXBH2N250
IXBT2N250**
**Monolithic Bipolar MOS
Transistor**


$$V_{CES} = 2500V$$

$$I_{C110} = 2A$$

$$V_{CE(sat)} \leq 3.80V$$

| Symbol | Test Conditions | Maximum Ratings | |
|----------------|--|--------------------|------------|
| V_{CES} | $T_C = 25^\circ C$ to $150^\circ C$ | 2500 | V |
| V_{CGR} | $T_J = 25^\circ C$ to $150^\circ C$, $R_{GE} = 1M\Omega$ | 2500 | V |
| V_{GES} | Continuous | ± 20 | V |
| V_{GEM} | Transient | ± 30 | V |
| I_{C25} | $T_C = 25^\circ C$ | 5 | A |
| I_{C110} | $T_C = 110^\circ C$ | 2 | A |
| I_{CM} | $T_C = 25^\circ C$, 1ms | 13 | A |
| SSOA | $V_{GE} = 15V$, $T_{VJ} = 125^\circ C$, $R_G = 47\Omega$ | $I_{CM} = 6$ | A |
| (RBSOA) | Clamped Inductive Load | $V_{CE} \leq 2000$ | V |
| P_C | $T_C = 25^\circ C$ | 32 | W |
| T_J | | -55 ... +150 | $^\circ C$ |
| T_{JM} | | 150 | $^\circ C$ |
| T_{stg} | | -55 ... +150 | $^\circ C$ |
| T_L | Maximum Lead Temperature for Soldering | 300 | $^\circ C$ |
| T_{SOLD} | 1.6 mm (0.062in.) from Case for 10s | 260 | $^\circ C$ |
| M_d | Mounting Torque (TO-247) | 1.13 / 10 | Nm/lb.in |
| Weight | TO-247 | 6 | g |
| | TO-268 | 4 | g |

TO-268 (IXBT)

TO-247 (IXBH)


G = Gate D = Drain
S = Source Tab = Drain

G = Gate C = Collector
E = Emitter Tab = Collector

Features

- High Blocking Voltage
- Integrated Anti-parallel Diode
- International Standard Packages
- Low Conduction Losses

Advantages

- Low Gate Drive Requirement
- High Power Density

Applications

- Switched-Mode and Resonant-Mode Power Supplies
- Uninterruptible Power Supplies (UPS)
- Laser Generator
- Capacitor Discharge Circuit
- AC Switches

| Symbol | Test Conditions ($T_J = 25^\circ C$, Unless Otherwise Specified) | Characteristic Values | | |
|---------------|---|-----------------------|------|---------------------------|
| | | Min. | Typ. | Max. |
| BV_{CES} | $I_C = 250\mu A$, $V_{CE} = V_{GE}$ | 2500 | | V |
| $V_{GE(th)}$ | $I_C = 250\mu A$, $V_{CE} = V_{GE}$ | 3.0 | | 5.5 V |
| I_{CES} | $V_{CE} = 0.8 \cdot V_{CES}$, $V_{GE} = 0V$ $T_J = 125^\circ C$ | | | 10 μA 100 μA |
| I_{GES} | $V_{CE} = 0V$, $V_{GE} = \pm 20V$ | | | ± 100 nA |
| $V_{CE(sat)}$ | $I_C = 2A$, $V_{GE} = 15V$, Note 1 $T_J = 125^\circ C$ | 3.15 | | V |
| | | 4.08 | | V |

| Symbol | Test Conditions ($T_J = 25^\circ\text{C}$, Unless Otherwise Specified) | Characteristic Values | | |
|--------------|---|-----------------------|------|--------------------|
| | | Min. | Typ. | Max. |
| g_{fs} | $I_C = 2\text{A}, V_{CE} = 10\text{V}$, Note 1 | 0.85 | 1.40 | S |
| C_{ies} | $V_{CE} = 25\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$ | | 145 | pF |
| C_{oes} | | | 8.7 | pF |
| C_{res} | | | 3.2 | pF |
| Q_g | $I_C = 2\text{A}, V_{GE} = 15\text{V}, V_{CE} = 1\text{kV}$ | | 10.6 | nC |
| Q_{ge} | | | 0.8 | nC |
| Q_{gc} | | | 6.2 | nC |
| $t_{d(on)}$ | Resistive Switching times, $T_J = 25^\circ\text{C}$ $I_C = 2\text{A}, V_{GE} = 15\text{V}$ $V_{CE} = 2\text{kV}, R_G = 47\Omega$ | | 30 | ns |
| t_r | | | 180 | ns |
| $t_{d(off)}$ | | | 70 | ns |
| t_f | | | 182 | ns |
| $t_{d(on)}$ | Resistive Switching times, $T_J = 125^\circ\text{C}$ $I_C = 2\text{A}, V_{GE} = 15\text{V}$ $V_{CE} = 2\text{kV}, R_G = 47\Omega$ | | 30 | ns |
| t_r | | | 280 | ns |
| $t_{d(off)}$ | | | 74 | ns |
| t_f | | | 178 | ns |
| R_{thJC} | | | 3.90 | $^\circ\text{C/W}$ |
| R_{thCS} | | 0.21 | | $^\circ\text{C/W}$ |

Reverse Diode

| Symbol | Test Conditions ($T_J = 25^\circ\text{C}$, Unless Otherwise Specified) | Characteristic Values | | |
|----------|--|-----------------------|------|---------------|
| | | Min. | Typ. | Max. |
| V_F | $I_F = 2\text{A}, V_{GE} = 0\text{V}$, Note 1 | | | 2.4 V |
| t_{rr} | $I_F = 2\text{A}, V_{GE} = 0\text{V}, -di_F/dt = 100\text{A}/\mu\text{s}$ $V_R = 100\text{V}, V_{GE} = 0\text{V}$ | | 0.92 | μs |
| I_{RM} | | | 9.80 | A |
| Q_{RM} | | | 4.50 | μC |

Note 1. Pulse test, $t \leq 300\mu\text{s}$, duty cycle, $d \leq 2\%$.


PRELIMINARY TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

IXYS Reserves the Right to Change Limits, Test Conditions and Dimensions.

IXYS MOSFETs and IGBTs are covered 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2
by one or more of the following U.S. patents: 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2
4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537


TO-268 Outline



Pins: 1 - Gate
2,4 - Collector
3 - Emitter

| SYMBOL | INCHES | | MILLIMETERS | |
|--------|--------|------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | .193 | .201 | 4.90 | 5.10 |
| A1 | .106 | .114 | 2.70 | 2.90 |
| A2 | .001 | .010 | 0.02 | 0.25 |
| b | .045 | .057 | 1.15 | 1.45 |
| b2 | .075 | .083 | 1.90 | 2.10 |
| C | .016 | .026 | 0.40 | 0.65 |
| C2 | .057 | .063 | 1.45 | 1.60 |
| D | .543 | .551 | 13.80 | 14.00 |
| D1 | .488 | .500 | 12.40 | 12.70 |
| D2 | .320 | .335 | 8.13 | 8.50 |
| E | .624 | .632 | 15.85 | 16.05 |
| E1 | .524 | .535 | 13.30 | 13.60 |
| E2 | .045 | .055 | 1.14 | 1.39 |
| e | .215 | BSC | 5.45 | BSC |
| H | .736 | .752 | 18.70 | 19.10 |
| L | .094 | .106 | 2.40 | 2.70 |
| L1 | .047 | .055 | 1.20 | 1.40 |
| L2 | .039 | .045 | 1.00 | 1.15 |
| L3 | .010 | BSC | 0.25 | BSC |
| L4 | .150 | .161 | 3.80 | 4.10 |

TO-247 Outline



Pins: 1 - Gate
2,4 - Collector
3 - Emitter

| SYM | INCHES | | MILLIMETERS | |
|-----|--------|------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | .190 | .205 | 4.83 | 5.21 |
| A1 | .087 | .100 | 2.21 | 2.54 |
| A2 | .075 | .085 | 1.91 | 2.16 |
| b | .045 | .055 | 1.14 | 1.40 |
| b2 | .075 | .085 | 1.91 | 2.16 |
| b4 | .115 | .126 | 2.92 | 3.20 |
| c | .023 | .033 | 0.58 | 0.84 |
| D | .820 | .840 | 20.83 | 21.34 |
| E | .620 | .635 | 15.75 | 16.13 |
| E2 | .175 | .195 | 4.44 | 4.95 |
| e | .215 | BSC | 5.45 | BSC |
| L | .780 | .810 | 19.81 | 20.57 |
| L1 | .160 | .177 | 4.06 | 4.50 |
| Q | .220 | .240 | 5.59 | 6.10 |
| R | .520 | .540 | 13.21 | 13.72 |
| S | .242 | BSC | 6.15 | BSC |
| T | .355 | .375 | 9.02 | 9.53 |
| U | .345 | .370 | 8.76 | 9.40 |
| ØP | .140 | .144 | 3.55 | 3.66 |
| W | .000 | .004 | 0.00 | 0.10 |

Fig. 1. Output Characteristics @ $T_J = 25^\circ\text{C}$




Fig. 2. Extended Output Characteristics @ $T_J = 25^\circ\text{C}$




Fig. 3. Output Characteristics @ $T_J = 125^\circ\text{C}$




Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature




Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage




Fig. 6. Input Admittance




Fig. 7. Transconductance




Fig. 8. Forward Voltage Drop of Intrinsic Diode




Fig. 9. Gate Charge




Fig. 10. Capacitance




Fig. 11. Reverse-Bias Safe Operating Area




Fig. 12. Maximum Transient Thermal Impedance




Fig. 13. Resistive Turn-on Rise Time vs. Junction Temperature




Fig. 14. Resistive Turn-on Rise Time vs. Collector Current




Fig. 15. Resistive Turn-on Switching Times vs. Gate Resistance




Fig. 16. Resistive Turn-off Switching Times vs. Junction Temperature




Fig. 17. Resistive Turn-off Switching Times vs. Collector Current





Fig. 18. Resistive Turn-off Switching Times vs. Gate Resistance





Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.