




HiPerFAST™ IGBT

IXGH20N30


V_{CES}	=	300 V
I_{C25}	=	40 A
$V_{CE(sat)typ}$	=	1.45 V
$t_{fi(typ)}$	=	180 ns



Preliminary data

Symbol	Test Conditions	Maximum Ratings		
V_{CES}	$T_J = 25^\circ\text{C}$ to 150°C	300	V	
V_{CGR}	$T_J = 25^\circ\text{C}$ to 150°C ; $R_{GE} = 1 \text{ M}\Omega$	300	V	
V_{GES}	Continuous	± 20	V	
V_{GEM}	Transient	± 30	V	
I_{C25}	$T_c = 25^\circ\text{C}$	40	A	
I_{C90}	$T_c = 90^\circ\text{C}$	20	A	
I_{CM}	$T_c = 25^\circ\text{C}$, 1 ms	80	A	
SSOA (RBSOA)	$V_{GE} = 15 \text{ V}$, $T_{VJ} = 125^\circ\text{C}$, $R_G = 10 \Omega$ Clamped inductive load, $L = 100 \mu\text{H}$	$I_{CM} = 40$ @ $0.8 V_{CES}$	A	
P_c	$T_c = 25^\circ\text{C}$	200	W	
T_J		-55 ... +150	°C	
T_{JM}		150	°C	
T_{stg}		-55 ... +150	°C	
Maximum Lead temperature for soldering 1.6 mm (0.062 in.) from case for 10 s		300	°C	
M_d	Mounting torque (M3)	1.13/10 Nm/lb.in.		
Weight		TO-247 AD	6	g

TO-247 AD



G = Gate, C = Collector,
E = Emitter, TAB = Collector

Features

- International standard package JEDEC TO-247 AD
- High current handling capability
- Newest generation HDMOS™ process
- MOS Gate turn-on
 - drive simplicity

Applications

- AC motor speed control
- DC servo and robot drives
- DC choppers
- Uninterruptible power supplies (UPS)
- Switched-mode and resonant-mode power supplies

Advantages

- High power density
- Suitable for surface mounting
- Switching speed for high frequency applications
- Easy to mount with 1 screw, (isolated mounting screw hole)

Symbol	Test Conditions	Characteristic Values		
		($T_J = 25^\circ\text{C}$, unless otherwise specified)	min.	typ.
BV_{CES}	$I_c = 250 \mu\text{A}$, $V_{GE} = 0 \text{ V}$	300		V
$V_{GE(th)}$	$I_c = 250 \mu\text{A}$, $V_{CE} = V_{GE}$	2.5	5	V
I_{CES}	$V_{CE} = 0.8 \cdot V_{CES}$ $V_{GE} = 0 \text{ V}$	$T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$	200	μA 1 mA
I_{GES}	$V_{CE} = 0 \text{ V}$, $V_{GE} = \pm 20 \text{ V}$		± 100	nA
$V_{CE(sat)}$	$I_c = I_{C90}$, $V_{GE} = 15 \text{ V}$	1.45	1.6	V

IXYS reserves the right to change limits, test conditions, and dimensions.

97527A (7/00)

© 2000 IXYS All rights reserved


1 - 2



IXGH20N30

Symbol	Test Conditions	Characteristic Values ($T_j = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
g_{fs}	$I_c = I_{C90}$; $V_{CE} = 10 \text{ V}$, Pulse test, $t \leq 300 \mu\text{s}$, duty cycle $\leq 2\%$	12	18	S
C_{ies}	$V_{CE} = 25 \text{ V}$, $V_{GE} = 0 \text{ V}$, $f = 1 \text{ MHz}$	1500	pF	
C_{oes}		130	pF	
C_{res}		40	pF	
Q_g	$I_c = I_{C90}$, $V_{GE} = 15 \text{ V}$, $V_{CE} = 0.5 V_{CES}$	90	nC	
Q_{ge}		15	nC	
Q_{gc}		35	nC	
$t_{d(on)}$	Inductive load, $T_j = 25^\circ\text{C}$ $I_c = I_{C90}$, $V_{GE} = 15 \text{ V}$, $L = 100 \mu\text{H}$, $V_{CE} = 0.8 V_{CES}$, $R_G = R_{off} = 4.7 \Omega$ Remarks: Switching times may increase for V_{CE} (Clamp) $> 0.8 \cdot V_{CES}$, higher T_j or increased R_G	15	ns	
t_{ri}		30	ns	
$t_{d(off)}$		100	ns	
t_{fi}		180	ns	
E_{off}		0.6	mJ	
$t_{d(on)}$	Inductive load, $T_j = 125^\circ\text{C}$ $I_c = I_{C90}$, $V_{GE} = 15 \text{ V}$, $L = 100 \mu\text{H}$, $V_{CE} = 0.8 V_{CES}$, $R_G = R_{off} = 4.7 \Omega$ Remarks: Switching times may increase for V_{CE} (Clamp) $> 0.8 \cdot V_{CES}$, higher T_j or increased R_G	15	ns	
t_{ri}		30	ns	
E_{on}		0.3	mJ	
$t_{d(off)}$		250	420	ns
t_{fi}		300	450	ns
E_{off}		1.0	1.6	mJ
R_{thJC}			0.83	K/W
R_{thCK}		0.25		K/W

TO-247 AD (IXGH) Outline



Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	19.81	20.32	0.780	0.800
B	20.80	21.46	0.819	0.845
C	15.75	16.26	0.610	0.640
D	3.55	3.65	0.140	0.144
E	4.32	5.49	0.170	0.216
F	5.4	6.2	0.212	0.244
G	1.65	2.13	0.065	0.084
H	-	4.5	-	0.177
J	1.0	1.4	0.040	0.055
K	10.8	11.0	0.426	0.433
L	4.7	5.3	0.185	0.209
M	0.4	0.8	0.016	0.031
N	1.5	2.49	0.087	0.102

DataSheet4U.com