

2SK1834

Silicon N-Channel Power F-MOS

■ Features

- Avalanche energy capability guaranteed : EAS > 15mJ
- $V_{GS}=\pm 30V$ guaranteed
- High-speed switching : $t_f = 25ns$
- No secondary breakdown

■ Applications

- Non-contact relay
- Solenoid drive
- Motor drive
- Control equipment
- Switching mode regulator


■ Absolute Maximum Ratings ($T_c = 25^\circ C$)

Parameter	Symbol	Rating	Unit	
Drain-Source breakdown voltage	V_{DSS}	800	V	
Gate-Source voltage	V_{GSS}	± 30	V	
Drain current	DC	I_D	± 2	A
	Pulse	I_{DP}	± 4	A
Avalanche energy capability	EAS *	15	mJ	
Allowable power dissipation	$T_c = 25^\circ C$	P_D	40	W
	$T_a = 25^\circ C$		2	
Channel temperature	T_{ch}	150	$^\circ C$	
Storage temperature	T_{stg}	-55 to +150	$^\circ C$	


* $L = 7.5mH$, $I_L = 2A$, $V_{DD} = 50V$, 1 pulse

■ Electrical Characteristics ($T_c = 25^\circ C$)


Parameter	Symbol	Condition	Min	Typ	Max	Unit	
Drain-Source cut-off current	I_{DSS}	$V_{DS} = 640V$, $V_{GS} = 0$			0.1	mA	
Gate-Source leakage current	I_{GSS}	$V_{GS} = \pm 30V$, $V_{DS} = 0$			± 1	μA	
Drain-Source breakdown voltage	V_{DSS}	$I_D = 1mA$, $V_{GS} = 0$	800			V	
Gate threshold voltage	V_{th}	$V_{DS} = 25V$, $I_D = 1mA$	2		5	V	
Drain-Source ON-resistance	$R_{DS(on)}$	$V_{GS} = 10V$, $I_D = 1A$		4.8	7	Ω	
Forward transadmittance	$ Y_{fs} $	$V_{DS} = 25V$, $I_D = 1A$	0.7	1.1		S	
Diode forward voltage	V_{DSF}	$I_{DR} = 2A$, $V_{GS} = 0$			-1.3	V	
Input capacitance	C_{iss}	$V_{DS} = 20V$, $V_{GS} = 0$, $f = 1MHz$		350		pF	
Output capacitance	C_{oss}				60		pF
Feedback capacitance	C_{rss}				25		pF
Turn-on time	t_{on}	$V_{GS} = 10V$, $I_D = 1A$ $V_{DD} = 200V$, $R_L = 200\Omega$		35		ns	
Fall time	t_f				25		ns
Turn-off time (delay time)	$t_{d(off)}$				60		ns
Channel-Case heat resistance	$R_{th(ch-c)}$				3.125	$^\circ C/W$	




$I_D - V_{DS}$




$|Y_{fs}| - I_D$




$R_{DS(on)} - I_D$




$I_D - V_{GS}$




$C_{iss}, C_{oss}, C_{rss} - V_{DS}$




$t_{on}, t_f, t_d(off) - I_D$




$P_D - T_a$




Area of safe operation (ASO)




$EAS - T_j$





Switching measurement circuit



Avalanche capability test circuit

