

Features

- Types up to 1000 V V_{RRM}
- Ideal for printed circuit board
- Surge overload rating to 65 Amps peak
- High temperature soldering guaranteed 250°C/ 10 seconds
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Reliable, low cost construction utilizing molded plastic technique

Mechanical Data

Leads: Tin plated copper
Weight: 0.047 oz, 1.33 g
Mounting position: Any
Terminals: Leads solderable per MIL-STD-202, Method 208
Polarity: Polarity marked on body

KBPM Package



Maximum ratings, at $T_j = 25 \text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	KBPM206G	KBPM208G	KBPM210G	Unit
Repetitive peak reverse voltage	V_{RRM}		600	800	1000	V
RMS reverse voltage	V_{RMS}		420	560	700	V
DC blocking voltage	V_{DC}		600	800	1000	V
Continuous forward current	I_F	$T_C \leq 65 \text{ }^\circ\text{C}$	2	2	2	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25 \text{ }^\circ\text{C}$, $t_p = 8.3 \text{ ms}$	65	65	65	A
Operating temperature	T_j		-55 to 150	-55 to 150	-55 to 150	$^\circ\text{C}$
Storage temperature	T_{stg}		-55 to 150	-55 to 150	-55 to 150	$^\circ\text{C}$

Electrical characteristics, at $T_j = 25 \text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	KBPM206G	KBPM208G	KBPM210G	Unit
Diode forward voltage	V_F	$I_F = 2 \text{ A}$, $T_j = 25 \text{ }^\circ\text{C}$	1.1	1.1	1.1	V
Reverse current	I_R	$V_R = 50 \text{ V}$, $T_j = 25 \text{ }^\circ\text{C}$ $V_R = 50 \text{ V}$, $T_j = 125 \text{ }^\circ\text{C}$	5 500	5 500	5 500	μA

Thermal characteristics

Thermal resistance, junction - case	R_{thJA}		14.0	14.0	14.0	$^\circ\text{C/W}$
-------------------------------------	------------	--	------	------	------	--------------------

