

Ph Free

RoHS Compliant

Features

- Ultra Miniture ceramic package
2.0 (L) ×1.6 (W) ×0.55 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage Vcc=1.8V/ 2.5V/ 3.3V
Compatible Low Power Supply Consumption
- Wide Operating Voltage Range 1.6 to 3.63V

Table 1

Freq. Tol. Code	× 10 ⁻⁶	Operating Temperature Range (°C)	Note
O	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC2016B 40.0000 C 1 0 E 00
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (2.0×1.6mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ Enable Function (45/ 55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

Specifications


Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	f _o		1.5	50	MHz	
Frequency Tolerance	f _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	ppm
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	T _{stg}		-55	+125	°C	
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.5	+6	V	
Supply Voltage	V _{cc}		1.6	3.63	V	
Current Consumption (Maximum Loaded)	I _{cc}	1.5≤f _o <30MHz	—	4	mA	
		30≤f _o <40MHz	—	5.5		
		40≤f _o <50MHz	—	6.5		
Stand-by Current	I _{std}		—	10	μA	
Symmetry	SYM	@ 50% V _{cc}	45	55	%	
Rise/ Fall Time (10% V _{cc} to 90% V _{cc} Maximum Loaded)	tr/ tf		—	5	nS	
Low Level Output Voltage	V _{OL}	I _{OL} =4mA	—	10% V _{cc}	V	
High Level Output Voltage	V _{OH}	I _{OH} =-4mA	90% V _{cc}	—	V	
CMOS Load	L _{CMOS}	CMOS Output	—	15	pF	
Input Voltage Range	V _{IN}		0	V _{cc}	V	
Low Level Input Voltage	V _{IL}		—	30% V _{cc}	V	
High Level Input Voltage	V _{IH}		70% V _{cc}	—	V	
Disable Time	t _{dis}		—	100	nS	
Enable Time	t _{ena}		—	5	mS	
Start-up Time	t _{str}	@ Minimum operating voltage to be 0 sec.	—	10	mS	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

