

KD16SF60

TRIACs

600V, 16A

Feature

- Full molded
- High voltage
- Tj=150°C
- Stable surge-on current capability
- Pb free terminal
- RoHS:Yes


OUTLINE

Package (House Name): FTO-220AG

Package (JEITA Code): SC-91



Equivalent circuit



Absolute Maximum Ratings (unless otherwise specified : Tc=25°C)

| Item | Symbol | Conditions | Ratings | Unit |
|---|---------------------|--|------------|------------------|
| Storage temperature | T _{stg} | | -55 to 150 | °C |
| Junction temperature | T _j | | -40 to 150 | °C |
| Repetitive peak off-state voltage | V _{DRM} | | 600 | V |
| Non-repetitive peak off-state voltage | V _{DSM} | * | 720 | V |
| R.M.S. on-state current | I _{T(RMS)} | T _c =107°C, commercial frequency, sine wave, $\theta=360^\circ\text{C}$ | 16 | A |
| Surge on-state current | I _{TSM} | T _j =25°C, 60Hz sine wave, Non-repetive 1 cycle peak | 120 | A |
| Current squared time | I ² t | T _j =25°C, t=8.33ms, Non-repetitive | 106.5 | A ² S |
| Critical rate of rise of on-state current | di/dt | | 50 | A/μs |
| Peak gate dissipation | P _{GM} | f=60Hz, Duty≤10% | 5 | W |
| Average gate dissipation | P _{G(AV)} | | 0.5 | W |
| Peak gate current | I _{GM} | f=60Hz, Duty≤10% | 2 | A |
| Peak gate voltage | V _{GM} | f=60Hz, Duty≤10% | 10 | V |
| Dielectric strength | V _{dis} | Terminals to case, AC 1 minute | 2 | kV |
| Mounting Torque | TOR | (Recommended torque:0.3N·m) | 0.5 | N·m |





* :See the original Specifications

Electrical Characteristics (unless otherwise specified : Tc=25°C)


| Item | Symbol | Conditions | Ratings | | | Unit |
|--|-------------|---------------------------------------|---------|-----|------|------------|
| | | | MIN | TYP | MAX | |
| Off-state current | I_{DRM} | VD=600V, Pulse measurement | | | 10 | μ A |
| On-state voltage | V_{TM} | ITM=25A, Pulse measurement | | | 1.5 | V |
| Gate trigger voltage | V_{GTI} | VD=6V, RL=10 Ω , T1-, T2+, G+ | | | 1.5 | V |
| Gate trigger voltage | V_{GTII} | VD=6V, RL=10 Ω , T1-, T2+, G- | | | 1.5 | V |
| Gate trigger voltage | V_{GTIII} | VD=6V, RL=10 Ω , T1+, T2-, G- | | | 1.5 | V |
| Gate trigger voltage | V_{GTIV} | VD=6V, RL=10 Ω , T1+, T2-, G+ | | | - * | V |
| Gate non-trigger voltage | V_{GD} | Tj=150°C, VD=1/2VDRM | 0.1 | | | V |
| Gate trigger current | I_{GTI} | VD=6V, RL=10 Ω , T1-, T2+, G+ | | | 30 | mA |
| Gate trigger current | I_{GTII} | VD=6V, RL=10 Ω , T1-, T2+, G- | | | 30 | mA |
| Gate trigger current | I_{GTIII} | VD=6V, RL=10 Ω , T1+, T2-, G- | | | 30 | mA |
| Gate trigger current | I_{GTIV} | VD=6V, RL=10 Ω , T1+, T2-, G+ | | | - * | mA |
| Latching current | I_{LI} | IG=0.1A, T1-, T2+, G+ | | | 100 | mA |
| Latching current | I_{LII} | IG=0.1A, T1-, T2+, G- | | | 100 | mA |
| Latching current | I_{LIII} | IG=0.1A, T1+, T2-, G- | | | 100 | mA |
| Latching current | I_{LIV} | IG=0.1A, T1+, T2-, G+ | | | - * | mA |
| Holding current | I_H | IT=1A | | | 100 | mA |
| Critical rate of rise of off-state voltage | dv/dt | Tj=150°C, VD=2/3VDRM | 100 | | | V/ μ s |
| Critical rate of rise of commutating voltage | (dv/dt)c | Tj=150°C, VD=2/3VDRM, (di/dt)c=-8A/ms | 1 | | | V/ μ s |
| Thermal resistance | Rth(j-c) | Junction to case with heatsink | | | 1.51 | °C/W |

* :See the original Specifications


CHARACTERISTIC DIAGRAMS




Gate characteristic




Gate trigger current - Pulse width




Gate trigger voltage - Pulse width




Gate trigger current - Junction temperature






Gate trigger voltage - Junction temperature



Holding current - Junction temperature




Latching current - Junction temperature



J8

| | |
|------------|-----------------|
| JEDEC Code | - |
| JEITA Code | SC-91 |
| House Name | FTO-220AG(3pin) |



Notes

1. If you wish to use any such product, please be sure to refer to the specifications issued by Shindengen.
2. All products described or contained herein are designed with a quality level intended for use in standard applications requiring an ordinary level of reliability. If these products are to be used in equipment or devices for special or specific applications requiring an extremely high grade of quality or reliability in which failures or malfunctions of products may directly affect human life or health, a local Shindengen office must be contacted in advance to confirm that the intended use of the product is appropriate. Shindengen products are grouped into the following three applications according to the quality grade.
【Standard applications】
Computers, office automation and other office equipment, communication terminals, test and measurement equipment, audio/visual equipment, amusement equipment, consumer electronics, machine tools, personal electronic equipment, industrial equipment, etc.
【Special applications】
Transportation equipment (vehicles, ships, etc.), trunk-line communication equipment, traffic signal control systems, anti-disaster/crime systems, safety equipment, medical equipment, etc.
【Specific applications】
Nuclear reactor control systems, aircraft, aerospace equipment, submarine repeaters, life support equipment and systems, etc.
3. Although Shindengen continuously endeavors to enhance the quality and reliability of its products, customers are advised to consider and take safety measures in their design, such as redundancy, fire containment and anti-failure, so that personal injury, fires, or societal damages can be prevented.
4. Please note that all information described or contained herein is subject to change without notice due to product upgrades and other reasons. When buying Shindengen products, please contact the Company's offices or distributors to obtain the latest information.
5. Shindengen shall not bear any responsibility with regards to damages or infringement of any third-party patent rights and other intellectual property rights incurred due to the use of information on this website.
6. The information and materials on this website neither warrant the use of Shindengen's or any third party's patent rights and other intellectual property rights, nor grant license to such rights.
7. In the event that any product described or contained herein falls under the category of strategic products controlled under the Foreign Exchange and Foreign Trade Control Law of Japan, exporting of such products shall require an export license from the Japanese government in accordance with the above law.
8. No reprinting or reproduction of the materials on this website, either in whole or in part, is permitted without proper authorization from Shindengen.