

SPECIFICATION FOR LCD MODULE

Customer : _____

Product Model: _____ KD50G10-40NC-A3

Sample code: _____

Designed by	Checked by	Approved by

Final Approval by Customer


☐ LCM Machinery OK Checked By _____ ☐ LCM Display OK Checked By _____	☐ LCM OK ☐ NG, Problem survey: Approved By _____
--	--

※The specification of "TBD" should refer to the measured value of sample . If there is difference between the design specification and measured value, we naturally shall negotiate and agree to solution with customer.

Contents

No.	Item	Page
1.	Numbering System	4/24
2	Scope	5/24
3	Normative Reference	5/24
4	Definitions	5/24
5	Technology Specifications	7/24
6	Circuit block diagram	11/24
7	Reliability Test Condition and Methods	15/21
8	Inspection standard	16/21
9	Handling Precautions	22/24
10	Precaution for use	23/24
11	Dimensional Outline	24/24

1 Numbering System



No	Definition	Specifications
(1)	TFT LCM Productor No.	KD ---- Kingdisplay technology Co.,Ltd
(2)	Display monitor opposite angle line size	Unit :mm or mmm (size <10 inch: takes two integers ; size >=10 inch: takes three integers)
(3)	Productor Types	D ---- Digital photo frame / DVD G ----GPS M ----MP P ----Mobil-Phone 。 。 。
(4)	Productor Development Series No.	By two figures characters expression from 01 to 99
(5)	Interface PIN Number	By two figures characters expression from 01 to 99
(6)	With Touch Panel Or Not	T----With T/P ; N----Without T/P
(7)	LCD Type	A----AUO ; M----CMO ; C----CPT; P----PVI; L----LG; W----Wintek; H----HSD; T----Topply; Y----Hydis; I----Hitach; S----Sharp。。。
(8)	Productor Development edition No.	By The English litters : A 1~ Z9

2 Scope

This specification applies to the TFT LCD module which is designed and manufactured by LCM Factory of Shenzhen K&D Technology Co.,Ltd.

3 Normative Reference

GB/T4619-1996 《Liquid Crystal Display Test Method》

GB/T2424 《Basic environmental Testing Procedures for Electric and Electronic Products.》


GB/T2423 《Basic Testing Procedures for Electric and Electronic Products》

IEC61747-1 《SIXTH PARTGB2828`2829-87 《National Standard of PRC》


4 Definitions

4.1 Definitions of Vop

The definitions of threshold voltage Vth1, Vth2 the following typical waveforms are applied on liquid crystal by the method of equalized voltage for each duty and bias.



【 selected waveform 】



【 non-selected waveform 】

① Vth1: The voltage which the brightness of segment indicates 50% of saturated value on the conditions of selected waveform

($f_i=80\text{Hz}$, $\Phi=10^\circ$ $\theta=270^\circ$ at 25°C)

② Vth2: The voltage which the brightness of segment indicates 50% of saturated value on the conditions of non-selected waveform

($f_i=80\text{Hz}$, $\Phi=10^\circ$ $\theta=270^\circ$ at 25°C)

③ Vop: $(V_{th1}(50\%)+V_{th2}(50\%))/2$ ($f_i=80\text{Hz}$, $\Phi=10^\circ$ $\theta=270^\circ$ at 25°C)

4.2 Definition of Response Time Tr, Td

① Tr: The time required which the brightness of segment becomes 10% from 100% when waveform is switched to selected one from non-selected one. ($f_i=80\text{Hz}$, $\Phi=10^\circ$ $\theta=270^\circ$ at 25°C)

② Td: The time required which the brightness of segment becomes 90% from 10% when waveform is switched to


selected one from selected one. ($f_i=80\text{Hz}$, $\Phi=10^\circ$, $\theta=270^\circ$ at 25°C)

4.3 Definition of Contrast Ratio Cr


$$\text{Cr} = A/B$$

- ① A: Segments brightness in case of non-selected waveform
- ② B: Segments brightness in case of selected waveform

4.4 Definition of Angle and Viewing Range



Angular Graph: Contrast Ratio



Such as:

Viewing Angle Range:

80($\text{Cr} > 2$) Horizontal

70($\text{Cr} > 2$) Vertical

5 Technology Specifications

5.1 Feature

This single-display module is suitable for use in Multimedia Player products. The LCD adopts one backlight with High brightness 12-lamps white LED.

- 1) Construction: 5" a-Si color TFT-LCD ,White LED backlight and FPC.
- 2) LCD:
 - 2.1 Amorphous-TFT 5-inch display, transmissive, normally white type.
 - 2.2 480(RGB)×272 dots Matrix.
 - 2.3 Narrow-contact ledge technique.
 - 2.4 LCD Driver IC: NT39024CH-D/3EA \ ILI6480G
- 3) RGB interface.
- 4) Video signal interface: Parallel RGB.

5.2 Mechanical Specifications

Item	Specifications	Unit
Dimensional outline	120.70(W) ×75.80(H)×3.1 Max(T)	mm
Active area	110.88(W) ×62.83 (H)	mm
Pixel size	231(W) ×231(H)	um
Resolution	480(RGB) ×272	pixel

5.3 Absolute Max. Rating

Item	Symbol	Value			Unit	Remark
		Min	typ	Max		
Logic power supply	DVDD	3.0	3.3	3.6	V	
Input high voltage	V _{IH}	0.7DVDD	-	DVDD	V	
Input low voltage	V _{IL}	0	-	0.3DVDD	V	
Operating temperature	T _{OPR}	-20		+70	°C	
Storage temperature	T _{STG}	-30		+80	°C	
Clock frequency	F _{CLK}	-	9	15	MHz	Note1

Note: For parallel RGB interface, maximum clock frequency is 15MHz,

5.4 Electrical Characteristics (VSS=0V, Ta=-20 to 70°C)

(Ta=25°C, DVDD=2.25V to 3.6V, AVDD=4.8V to 5.2V, DVSS=AVSS=0V)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Input low leakage current	I _{IL}	No pull-up or pull-down	-1	-	1	μA
Input high leakage current	I _{IH}	No pull-up or pull-down	-1	-	1	μA
Output low voltage	V _{OL} ^{*1}	I _{OL} =1mA	DVSS	-	DVSS+0.4	V
Output high voltage	V _{OH} ^{*1}	I _{OH} =-1mA	DVDD-0.4	-	DVDD	V
Gamma resistor	R _{GMA}	AVDD=5V, T _A =25°C, V _O to V _n =4V	-	17.1	-	kΩ
Driver output current	I _{VOL}	AVDD=5V, V _O =0.2V, V _{IN} =0.7V	-	-	(80)	μA
	I _{VOH}	AVDD=5V, V _O =4.8V, V _{IN} =4.3V	(80)	-	-	μA
Average output deviation (chip to chip)	ΔV _d	Center gary level	-	-	10	mV
Output deviation	ΔV _{O1}	V _O =1.5V to AVDD-1.5V	-	(±10)	(±15)	mV
Output deviation	ΔV _{O2}	V _O <1.5V or >AVDD-1.5V	-	(±20)	(±40)	mV
Logic dynamic current	I _{DD1}	DVDD	-	(1.0) ^{*2}	(2.0) ^{*3}	mA
Driver dynamic current	I _{DD2}	AVDD	-	8.75 ^{*4}	10 ^{*5}	mA
Input pull up/down resistance	R _I	V _{IL} =0V or V _{IH} =DVDD	150	-	-	kΩ

Note:

1. CKV, STV, OEV pins
2. Parallel interface, f_{CLK}=9MHz, f_{STB}=17.14KHz, dot inversion pattern, DVDD=2.5V, TA=25°C
3. Parallel interface, f_{CLK}=9MHz, f_{STB}=17.14KHz, dot inversion pattern, DVDD=2.75V, TA=-30 to 85°C
4. Parallel interface, f_{CLK}=9MHz, f_{STB}=17.14KHz, all white (NBW="H") pattern, AVDD=5V, V_O=4.5V, V_n=0.2V, TA=25°C
5. Parallel interface, f_{CLK}=9MHz, f_{STB}=17.14KHz, all white (NBW="H") pattern, AVDD=5.2V, V_O=4.5V, V_n=0.2V, TA=-30 to 85°C

5.5 Optical specifications

Item		Symbol	Conditions	Specifications			Unit	Note
				Min.	Typ.	Max.		
Transmittance		T%	Viewing normal angle $\theta_x = \theta_y = 0^\circ$		7.5		%	All left side data are based on CMO's following condition -T6 NTSC: 50% LC:5091 Light : C light (Machine:BM5A) Normal Polarizer Without DBEF Simulation Data Reference Only
Contrast Ratio		CR		150	250		--	
Response Time		T _R			15	20	ms	
		T _F			35	50	ms	
Chromaticity	Red	X _R		0.585	0.615	0.645		
		Y _R		0.314	0.344	0.374		
	Green	X _G		0.277	0.307	0.337		
		Y _G		0.532	0.562	0.592		
	Blue	X _B		0.103	0.133	0.163		
		Y _B		0.120	0.150	0.180		
	White	X _W		0.279	0.309	0.339		
		Y _W		0.320	0.350	0.380		
Viewing Angle	Hor.	θ_{x+}	Center CR≥10		45		deg.	
		θ_{x-}			45			
	Ver.	θ_{y+}			15			
		θ_{y-}			35			

*Note (1) Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.

$$\text{Contrast Ratio (CR)} = L_{63} / L_0$$


L63: Luminance of gray level 63

L0: Luminance of gray level 0

$$CR = CR(10)$$

CR (X) is corresponding to the Contrast Ratio of the point X at Figure in Note (5).


*Note (2) Definition of Response Time (T_R , T_F):



5.6 LED back light specification (12 White Chips)

Item	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	V _f	I _f =40mA	18	19.2	20.4	V
Uniformity (with L/G)	Δ B _p	I _f =40mA	80	-	-	%
Luminance for LCD	L _v	I _f =40mA	4800	-	-	cd/m ²

LED CIRCUIT




5.7 Interface Pin Connections

PIN NO.	Symbol	Description
1	LED-K	LED backlight(Cathode)
2	LED-A	LED backlight(anode)
3	GND	Ground
4	VDD	Power supply (Digital +3.0V)
5-12	R0-R7	Red Data
13-20	G0-G7	Green Data
21-28	B0-B7	Blue Data
29	GND	Ground
30	CLK	Clodk
31	DISP	Display on/off
32	HSYNC	Horizontal sync input in RGB mode (short to GND if not used)
33	VSYNC	Vertical sync input in RGB mode (short to GND if not used)
34	DEN	Data Enable
35	NC	NC
36	GND	Ground
37	NC	NC
38	NC	NC
39	NC	NC
40	NC	NC


6 Signal timing diagram and Circuit block diagram

6.1 Circuit block diagram




6.2 Signal Timing Diagram

6.2.1 Power ON/OFF Sequence



6.2.2 Reset timing

The reset input must be held for at least 1ms after power is stable.




6.2.3 Timing Diagram of interface Signal

(480RGBx272, $T_A=25^\circ\text{C}$, DVDD=2.25V to 3.6V, DVSS= 0V)


PARAMETER	Symbol	Min.	Typ.	Max.	Unit
Clock cycle	$1/t_c^{*1}$	-	9	15	MHz
Hsync cycle	$1/f_H$	-	17.14	-	KHz
Vsync cycle	$1/f_V$	-	59.94	-	Hz
Horizontal Signal					
Horizontal cycle	th^{*2}	-	525	-	CLK
Horizontal display period	thd	-	480	-	CLK
Horizontal front porch	thf	2	-	-	CLK
Horizontal pulse width	thp	2	41	-	CLK
Horizontal back porch	thb	2	2	-	CLK
Vertical Signal					
Vertical cycle	tv	-	286	-	H
Vertical display period	tvd	-	272	-	H
Vertical front porch	tvf	1	2	-	H
Vertical pulse width	tvp	1	10	-	H
Vertical back porch	tvb	1	2	-	H

Note:

- Parallel interface. Clock frequency and horizontal signal parameters are tripled in serial interface.
The Maximum clock frequency of serial interface is 33MHz
- $thd=480\text{CLK}$, $thf=2\text{CLK}$, $thp=41\text{CLK}$, $thb=2\text{CLK}$, $thf + fhp + ftb > 44$



6.2.4 Vertical Timing Diagram







Timing	480RGBx272	480RGBx240	240RGBx320	240RGBx240
A	8	8	4	4
B	4	4	2	2
C	0	0	0	0
D	10	10	5	5
E	34	34	17	17
F	6	6	3	3
G	2	2	1	1

7 Reliability Test Conditions And Methods




NO	Item	Condition	Method
1	High / Low Temperature Storage	80℃/-30℃ 120hrs	Check and record every 48Hrs
2	High / Low Temperature Life	70℃/-20℃ 120hrs (operating mode)	Check and record every 48Hrs
3	High Temperature、High Humidity Operating	60℃,90% RH, 96Hrs	Check and record every 48hrs
4	Thermal Shock	-30℃(30Min) → 25℃(5Min) → 80℃(30Min) (conversion time, : 5 sec) 20 cycles	Each 10 cycles end , check
5	Vibration	10Hz~55Hz~10Hz Amplitude: 1.5mm 2hrs for each direction(X,Y,Z)	Each direction end, Check the Appearance and Electrical Characteristics
6	Static Electricity	Gap mood: ±1KV~±8KV (10 times air discharge with positive/negative voltage voltage gap : 1kv) Touch mood: ±1KV~±4KV	Each discharge end, Check the Electrical Characteristics
7	Curve	60 Thousand times, 40 times/min 150° (according to die if exist)	Check and record every 2~4 thousand times
8	Slump	Free faller movement for each side、cording、angle (75cm High、6 sides、2 angle、2 cording)	End


8 Inspection standard

No	Item	Criterion											
01	Outline Dimension	In accord with drawing											
02	Position-finding Dimension Assemble Dimension	In accord with drawing											
03	LCD black spots, white spots (Round type)	Round type: non display 3.1 Small area LCD  <table><thead><tr><th>Dimension</th><th>Qualified Quantity</th></tr></thead><tbody><tr><td>$D \leq 0.1$</td><td>Ignore</td></tr><tr><td>$0.1 < D \leq 0.15$</td><td>2</td></tr><tr><td>$D > 0.15$</td><td>0</td></tr></tbody></table>	Dimension	Qualified Quantity	$D \leq 0.1$	Ignore	$0.1 < D \leq 0.15$	2	$D > 0.15$	0			
		Dimension	Qualified Quantity										
$D \leq 0.1$	Ignore												
$0.1 < D \leq 0.15$	2												
$D > 0.15$	0												
		Unit : mm 3.2 Large area LCD  <table><thead><tr><th>Dimension</th><th>Qualified Quantity</th></tr></thead><tbody><tr><td>$D \leq 0.1$</td><td>Ignore</td></tr><tr><td>$0.1 < D \leq 0.15$</td><td>2</td></tr><tr><td>$0.15 < D \leq 0.20$</td><td>1</td></tr><tr><td>$D > 0.20$</td><td>0</td></tr></tbody></table> C-STN : if $D > 0.1$, unqualified	Dimension	Qualified Quantity	$D \leq 0.1$	Ignore	$0.1 < D \leq 0.15$	2	$0.15 < D \leq 0.20$	1	$D > 0.20$	0	
Dimension	Qualified Quantity												
$D \leq 0.1$	Ignore												
$0.1 < D \leq 0.15$	2												
$0.15 < D \leq 0.20$	1												
$D > 0.20$	0												

04	LCD black spots, white spots (Line Style)	4.1 Small area LCD																		
		Unit : mm																		
			<table><tr><th>Length</th><th>Width</th><th>Qualified Quantity</th></tr><tr><td>-</td><td>≤0.015</td><td>Ignore</td></tr><tr><td>≤1.0</td><td rowspan="2">0.015<W≤0.025</td><td>2</td></tr><tr><td>≤2.0</td><td>1</td></tr><tr><td>≤1.0</td><td>0.025<W≤0.05</td><td>1</td></tr><tr><td>-</td><td>D>0.05</td><td>According to circle</td></tr></table>	Length	Width	Qualified Quantity	-	≤0.015	Ignore	≤1.0	0.015<W≤0.025	2	≤2.0	1	≤1.0	0.025<W≤0.05	1	-	D>0.05	According to circle
Length	Width	Qualified Quantity																		
-	≤0.015	Ignore																		
≤1.0	0.015<W≤0.025	2																		
≤2.0		1																		
≤1.0	0.025<W≤0.05	1																		
-	D>0.05	According to circle																		
		4.2Large area LCD																		
			<table><tr><th>Length</th><th>Width</th><th>Qualified Quantity</th></tr><tr><td>-</td><td>≤0.015</td><td>Ignore</td></tr><tr><td>≤2.0</td><td>0.015<W≤0.025</td><td>2</td></tr><tr><td>≤1.0</td><td>0.025<W≤0.05</td><td>1</td></tr><tr><td>-</td><td>D>0.05</td><td>According to circle</td></tr></table>	Length	Width	Qualified Quantity	-	≤0.015	Ignore	≤2.0	0.015<W≤0.025	2	≤1.0	0.025<W≤0.05	1	-	D>0.05	According to circle		
Length	Width	Qualified Quantity																		
-	≤0.015	Ignore																		
≤2.0	0.015<W≤0.025	2																		
≤1.0	0.025<W≤0.05	1																		
-	D>0.05	According to circle																		
		CSTN : If W ≥ 0.015 , unqualified Ignore beyond viewing area																		
05	LCD Scratch 、 Threadlike Fiber	Same to NO.3 circle sightline and surface of LCD is vertical (2)Same to NO.3 line style																		
06	POL	It is not admissible that POL is beyond the edge of glass, else, unqualified. It is essential that POL is over the 50 percent of width of frame , else ,unqualified. According to the drawing in case of special definition.																		
07	IC/FPC Bonding	Scratch	Reject																	

		Intensity Of Adhesion	If lower than specification, reject	
		Gold Fold Twist	Reject	
07	IC/FPC Bonding	Silicon	According to outline, no gold outside, seal can not be higher than LCD	
		FPC Gold Sever	Reject	
08	SMT	Lack of Component、Polarity Inverse	If exist, reject	
		Leak Solder、Virtual Solder	If exist, reject	
		Short Circuit In Solder Point	If exist, reject	
		Tin Ball	If exist, reject	
		Tin Acumination	If visual, reject	
		Height Solder Point	If higher 0.5mm than component. reject	
		Height of component	Either side higher 0.5mm than component, reject	

		Component Shift	 $X < 3/4Z$ $y > 1/3D$ reject reject	
08	SMT	Few Tin	 If $\theta \leq 20^\circ$ reject	
		Component Deflection	 If $Y > 1/3D$ reject	
		Component Carcass Sideways	Reject	

		Component Carcass Sideways	If exist with visual inspection , reject	
		Lot Tin	A: Tin accrete the solder side completely , hollowly ,Ok B: Tin accrete the solder side completely , full circle arc , ok C: Jointing include whole solder side, height of tin>50 percent of height of component, reject	
		Few Tin	A: Tin accrete the solder side completely , hollowly ,Ok B: height of tin > 1/3 of solder side of component , ok C: height of tin $\leq$ 1/3 of solder side of component, reject	
08	SMT	Normal  Jointing side		
09	Light	Short circuit 、 Open circuit	Forbid	
		Quality of CSTN Display	1、 Rolling strake with visual inspection, forbid 2、 Differentness of color in viewing area with visual inspection (full white、 red、 green、 blue), forbid 3 、 Display change with visual inspection , forbid	

10	Color Of CIE Coordinate				Drive LCD under normal condition, 25℃ Φ=0 θ=0 Test white、red、green blue with DMS Record	
			x	y		
		white	±0.05	±0.05		
		Red	±0.05	±0.05		
		Green	±0.05	±0.05		
		Blue	±0.05	±0.05		
		According to the specification or sample customer have approved				
11	Brightness	In accord with product specification	Drive condition is according to specification Measure location is in Follow Picture 3、Adjust brightness instrument to zero , burrow against the surface of LCD , press “measure” , record when the display is steady. (YOKOGAWA-3298)			
			Measure location			
12	CR (Max)	According to specification	According to product specification Measure instrument (DMS-501)			
13	Response time	According to specification	According to product specification Measure instrument (DMS-501)			
14	Viewing angle	According to specification	According to product specification Measure instrument (DMS-501)			
15	Vibration、Ring	Compare with the sample customer supply	Compare with the sample customer supply when assemble			
16	Frequency Of FPC Bend	According to the use of product (main FPC of foldaway cell phone ≥6 thousand)	Measure instrument Bend angle : 150° Fix FPC in the casement when customer supply			

9 Handling Precautions

9.1 Mounting method

The LCD panel of Daxian LCD module consists of two thin glass plates with polarizers which easily be damaged. And since the module is so constructed as to be fixed by utilizing fitting holes in the printed circuit board.

Extreme care should be needed when handling the LCD modules.

9.2 Caution of LCD handling and cleaning

When cleaning the display surface, Use soft cloth with solvent [recommended below] and wipe lightly

- Isopropyl alcohol
- Ethyl alcohol

Do not wipe the display surface with dry or hard materials that will damage the polarizer surface.

Do not use the following solvent:

- Water
- Aromatics

Do not wipe ITO pad area with the dry or hard materials that will damage the ITO patterns

Do not use the following solvent on the pad or prevent it from being contaminated:

- Soldering flux
- Chlorine (Cl), Sulfur (S)

If goods were sent without being silicene coated on the pad, ITO patterns could be damaged due to the corrosion as time goes on.

If ITO corrosion happens by miss-handling or using some materials such as Chlorine (Cl), Sulfur (S) from customer, Responsibility is on customer.

9.3 Caution against static charge

The LCD module uses C-MOS LSI drivers, so we recommend that you:

Connect any unused input terminal to Vdd or Vss, do not input any signals before power is turned on, and ground your body, work/assembly areas, assembly equipment to protect against static electricity.

9.4 packing

- Module employs LCD elements and must be treated as such.
- Avoid intense shock and falls from a height.
- To prevent modules from degradation, do not operate or store them exposed direct to sunshine or high temperature/humidity

9.5 Caution for operation

- It is an indispensable condition to drive LCD's within the specified voltage limit since the higher voltage than the limit causes the shorter LCD life.
- An electrochemical reaction due to direct current causes LCD's undesirable deterioration, so that the use of direct current drive should be avoided.
- Response time will be extremely delayed at lower temperature than the operating temperature range and on the other hand at higher temperature LCD's show dark color in them. However those phenomena do not mean malfunction or out of order with LCD's, which will come back in the specified

operation temperature.

- If the display area is pushed hard during operation, some font will be abnormally displayed but it resumes normal condition after turning off once.
- A slight dew depositing on terminals is a cause for electro-chemical reaction resulting in terminal open circuit.

Usage under the maximum operating temperature, 50%Rh or less is required.

9.6 storage

In the case of storing for a long period of time for instance, for years for the purpose or replacement use, the following ways are recommended.

- Storage in a polyethylene bag with the opening sealed so as not to enter fresh air outside in it . And with no desiccant.
- Placing in a dark place where neither exposure to direct sunlight nor light's keeping the storage temperature range.
- Storing with no touch on polarizer surface by the anything else.

[It is recommended to store them as they have been contained in the inner container at the time of delivery from us

9.7 Safety

- It is recommendable to crash damaged or unnecessary LCD's into pieces and wash off liquid crystal by either of solvents such as acetone and ethanol, which should be burned up later.
- When any liquid leaked out of a damaged glass cell comes in contact with your hands, please wash it off well with soap and water

10 Precaution for use

10.1

A limit sample should be provided by the both parties on an occasion when the both parties agreed its necessity. Judgment by a limit sample shall take effect after the limit sample has been established and confirmed by the both parties.

10.2

On the following occasions, the handing of problem should be decided through discussion and agreement between responsible of the both parties.

- When a question is arisen in this specification
- When a new problem is arisen which is not specified in this specifications
- When an inspection specifications change or operating condition change in customer is reported to Daxian , and some problem is arisen in this specification due to the change
- When a new problem is arisen at the customer's operating set for sample evaluation in the customer site.

11 Dimensional Outline

