371-9923

Traditional Series

Motor
Patented Brushless DC motor design.
Frame
Injection molded non-flammable black thermoplastic UL 94V-0 rating and aluminum
Bering System :
Precision, life-lubricated ball bearing system
Precision, oil-impregnated sintered sleeve bearing system
Insulation
lass E integral ground system rated @100 Deg C
Insulation Resistance
More than 500M ohm between internal stator and lead wire(+) measured by DC 500V
Dielectric Strength
600VAC for one minute
Safety Protection :Electronic locked rotor protected
Operating Temperature
-10 to +70 Deg.C
Storage Temperature
-40 to +70 Deg.C
Operating Voltage
Rated voltage ¡Ó15%
Professional Design
We Can design to fit any special application requirement¡@

DC Brushless Fan 40x40x20mm

¡@

¡@

Model	P/N	Voltage VDC	Bearing Style	Current AMP	Input Watts	Speed RPM	AirFlow CFM	Pressure Inch-H_2O	Noise dBA	Weight (g)
KD0504PKS2		5	S	0.19	1.0	6000	6.5	0.12	25.5	28
KD0504PKS3	¡@	5	S	0.14	0.7	4500	5.2	0.08	22.8	28
KD0504PKB2	¡@	5	B	0.19	1.0	6500	7.0	0.16	29	28
KD0504PKB3		5	B	0.14	0.7	5300	6.2	0.12	24	28
KD1204PKS1	H	12	S	0.09	1.2	7200	8.9	0.21	25.5	28
KD1204PKS2	H	12	S	0.07	0.8	6200	7.7	0.16	21	28
KD1204PKS3	H	12	S	0.06	0.7	5200	6.3	0.11	18	28
KD1204PKB1	H	12	B	0.09	1.2	7400	9.1	0.22	27	28
3719923 KD1204PKB2	H	12	B	0.07	0.8	6500	8.0	0.17	22.5	28
KD1204PKB3	H	12	B	0.05	0.6	5400	6.5	0.12	19	35
KD2404PKS2		24	S	0.05	1.2	6000	6.5	0.12	25.5	35
KD2404PKS3		24	S	0.03	0.8	4500	5.2	0.08	22.8	35
KD2404PKB2		24	B	0.04	1.0	6500	7.0	0.16	29	35
KD2404PKB3	¡@	24	B	0.03	0.7	5000	6.0	0.11	24	35

B : Ball S : Sleeve Frame: PBT plastic

¡@Products index / DC Fan (MS Series) / DC Fan (Traditional series)

SUNON

E-mail : sunon@www.sunon.com.tw

¡@

www.DataSheet4U.com