


371-9947

Traditional Series

<p>Motor Patented Brushless DC motor design. Frame Injection molded non-flammable black thermoplastic UL 94V-0 rating and aluminum Bearing System : Precision, life-lubricated ball bearing system Precision, oil-impregnated sintered sleeve bearing system Insulation Class E integral ground system rated @100 Deg C Insulation Resistance More than 500M ohm between internal stator and lead wire(+) measured by DC 500V Dielectric Strength 600VAC for one minute Safety Protection :Electronic locked rotor protected Operating Temperature -10 to +70 Deg.C Storage Temperature -40 to +70 Deg.C Operating Voltage Rated voltage $\pm 15\%$ Professional Design We Can design to fit any special application requirement;@</p>	<p>DC Brushless Fan 60x60x25mm</p>  <p>i@i@ i@</p>
---	--

Model	P/N	Voltage VDC	Bearing Style	Current AMP	Input Watts	Speed RPM	AirFlow CFM	Pressure Inch-H ₂ O	Noise dBA	Weight (g)
KD1206PTS1	H	12	S	0.16	1.9	4300	22.5	0.20	33.5	59
KD1206PTS2	H	12	S	0.11	1.3	3700	18.5	0.15	29	59
KD1206PTS3	H	12	S	0.07	0.8	3100	16.0	0.10	25	59
KD1206PTB1	H	12	B	0.17	2.0	4300	22.5	0.20	34	59
3719947-KD1206PTB2	H	12	B	0.11	1.3	3700	18.0	0.15	30	59
KD1206PTB3	H	12	B	0.07	0.8	3100	16.0	0.10	26	59
B : Ball S : Sleeve			Frame: PBT plastic							

i@Products index / DC Fan (MS Series) / DC Fan (Traditional series)



E-mail : sunon@www.sunon.com.tw