371-9984

Traditional Series

Motor
Patented Brushless DC motor design.
Frame
Injection molded non-flammable black thermoplastic UL 94V-0 rating and aluminum
Bering System :
Precision, life-lubricated ball bearing system
Precision, oil-impregnated sintered sleeve bearing system
Insulation
lass E integral ground system rated @100 Deg C
Insulation Resistance
More than 500M ohm between internal stator and lead wire(+) measured by DC 500V
Dielectric Strength
600VAC for one minute
Safety Protection :Electronic locked rotor protected
Operating Temperature
-10 to +70 Deg.C
Storage Temperature
-40 to +70 Deg.C
Operating Voltage
Rated voltage ¡Ó15%
Professional Design
We Can design to fit any special application requirement¡@

DC Brushless Fan 92x92x25mm

¡@

¡@

Model	P/N	Voltage VDC	Bearing Style	Current AMP	Input Watts	Speed RPM	AirFlow CFM	Pressure Inch-H_2O	Noise dBA	Weight (g)
KD1209PTS1	H	12	S	0.22	2.6	2500	45.5	0.14	33	108
KD1209PTS2	H	12	S	0.21	2.5	2400	44.0	0.14	32	108
KD1209PTS3	H	12	S	0.14	1.7	2100	39.0	0.11	28	108
KD1209PTB1	H	12	B	0.21	2.5	2700	49.5	0.17	34.5	108
371 9984- KD1209PTB2	H	12	B	0.20	2.4	2600	48.5	0.16	33	108
KD1209PTB3	H	12	B	0.13	1.6	2300	41.0	0.12	30	108
KD2409PTS1-6A		24	S	0.14	3.4	2800	50.0	0.17	35	121
KD2409PTS2-6A		24	S	0.09	2.2	2500	44.0	0.15	33	121
KD2409PTS3-6A		24	S	0.07	1.7	2100	39.0	0.11	27	121
KD2409PTB1-6A		24	B	0.14	3.4	3000	51.0	0.20	37	121
KD2409PTB2-6A		24	B	0.09	2.2	2600	45.0	0.18	34	121
KD2409PTS3-6A		24	B	0.07	1.7	2300	40.0	0.13	28	121

B : Ball **S : Sleeve** Frame: PBT plastic

Products index / DC Fan (MS Series) / DC Fan (Traditional series)

SUNON

E-mail : sunon@www.sunon.com.tw

¡@

www.DataSheet4U.com