


ULTRA HIGH SPEED SWITCHING APPLICATION.

FEATURES


- Small Package : SOT-23.
- Low Forward Voltag : $V_F=0.9V(\text{Typ.})$.
- Fast Reverse Recovery Time : $t_{rr}=1.6\text{ns}(\text{Typ.})$.
- Small Total Capacitance : $C_T=0.9\text{pF}(\text{Typ.})$.

MAXIMUM RATING (Ta=25)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum (Peak) Reverse Voltage	V_{RM}	85	V
Reverse Voltage	V_R	80	V
Maximum (Peak) Forward Current	I_{FM}	300	mA
Average Forward Current	I_O	100	mA
Surge Current (10ms)	I_{FSM}	2	A
Power Dissipation	P_D	150	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	



Marking



ELECTRICAL CHARACTERISTICS (Ta=25)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	$V_{F(1)}$	$I_F=1\text{mA}$	-	0.60	-	V
	$V_{F(2)}$	$I_F=10\text{mA}$	-	0.72	-	
	$V_{F(3)}$	$I_F=100\text{mA}$	-	0.90	1.20	
Reverse Current	I_R	$V_R=80\text{V}$	-	-	0.5	μA
Total Capacitance	C_T	$V_R=0, f=1\text{MHz}$	-	0.9	3.0	pF
Reverse Recovery Time	t_{rr}	$I_F=10\text{mA}$	-	1.6	4.0	ns







Fig. 1. REVERSE RECOVERY TIME(t_{rr}) TEST CIRCUIT

