


## D-TYPE FLIP FLOP WITH PRESET AND CLEAR

The KIC7W74FK is a high speed C<sup>2</sup>MOS D FLIP FLOP fabricated with silicon gate C<sup>2</sup>MOS technology. It achieves the high speed operation similar to equivalent LSTTL while maintaining the C<sup>2</sup>MOS low power dissipation. The signal level applied to the D INPUT is transferred to Q OUTPUT during the positive going transition of the CLOCK pulse CLEAR and PRESET are independent of the CLOCK and are accomplished by setting the appropriate input to an "L" level input is equipped with protection circuits against static discharge or transient excess voltage.

### FEATURES


- High Speed :  $f_{max}=77\text{MHz(Typ.)}$  at  $V_{CC}=5\text{V}$ .
- Low Power Dissipation :  $I_{CC}=2\mu\text{A(Max.)}$  at  $T_a=25^\circ\text{C}$ .
- High Noise Immunity :  $V_{NIH}=V_{NIL}=28\% V_{CC(\text{Min.})}$ .
- Output Drive Capability : 10 LSTTL Loads
- Symmetrical Output Impedance :  $|I_{OH}|=I_{OL}=4\text{mA(Min.)}$
- Balanced Propagation Delays :  $t_{pLH}\approx t_{pHL}$
- Wide Operating Voltage Range :  $V_{CC(\text{opr})}=2\sim 6\text{V}$ .




### MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage Range	$V_{CC}$	-0.5~7	V
DC Input Voltage	$V_{IN}$	-0.5~ $V_{CC}+0.5$	V
DC Output Voltage	$V_{OUT}$	-0.5~ $V_{CC}+0.5$	V
Input Diode Current	$I_{IK}$	±20	mA
Output Diode Current	$I_{OK}$	±20	mA
DC Output Current	$I_{OUT}$	±25	mA
DC $V_{CC}$ /Ground Current	$I_{CC}$	±25	mA
Power Dissipation	$P_D$	200	mW
Storage Temperature	$T_{stg}$	-65~150	°C
Lead Temperature (10s)	$T_L$	260	°C

### MARKING




### PIN CONNECTION(TOP VIEW)



# KIC7W74FK

## LOGIC DIAGRAM



## TRUTH TABLE

INPUTS				OUTPUTS		FUNCTION
CLR	PR	D	CK	Q	$\bar{Q}$	
L	H	×	×	L	H	CLEAR
H	L	×	×	H	L	PRESET
L	L	×	×	H	H	-
H	H	L	↑	L	H	-
H	H	H	↑	H	L	-
H	H	×	↓	Q <sub>n</sub>	$\bar{Q}_n$	NO CHANGE

× : Don't care

## RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	$V_{CC}$	2~6	V
Input Voltage	$V_{IN}$	0~ $V_{CC}$	V
Output Voltage	$V_{OUT}$	0~ $V_{CC}$	V
Operating Temperature	$T_{opr}$	-40~85	°C
Input Rise and Fall Time	$t_r, t_f$	0~1000 ( $V_{CC}=2.0V$ ) 0~ 500 ( $V_{CC}=4.5V$ ) 0~ 400 ( $V_{CC}=6.0V$ )	ns

# KIC7W74FK

## DC ELECTRICAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	TEST CONDITION		Ta=25°C			Ta=-40~85°C		UNIT	
				V <sub>CC</sub>	MIN.	TYP.	MAX.	MIN.		MAX.
High-Level Input Voltage	V <sub>IH</sub>	-		2.0	1.5	-	-	1.5	-	V
				4.5	3.15	-	-	3.15	-	
				6.0	4.2	-	-	4.2	-	
Low-Level Input Voltage	V <sub>IL</sub>	-		2.0	-	-	0.5	-	0.5	V
				4.5	-	-	1.35	-	1.35	
				6.0	-	-	1.8	-	1.8	
High-Level Output Voltage	V <sub>OH</sub>	V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub>	I <sub>OH</sub> =-20μA	2.0	1.9	2.0	-	1.9	-	V
				4.5	4.4	4.5	-	4.4	-	
				6.0	5.9	6.0	-	5.9	-	
				4.5	4.18	4.31	-	4.13	-	
Low-Level Output Voltage	V <sub>OL</sub>	V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub>	I <sub>OL</sub> =20μA	2.0	-	0.0	0.1	-	0.1	V
				4.5	-	0.0	0.1	-	0.1	
				6.0	-	0.0	0.1	-	0.1	
				4.5	-	0.17	0.26	-	0.33	
Input Leakage Current	I <sub>IN</sub>	V <sub>IN</sub> =V <sub>CC</sub> or GND		6.0	-	-	±0.1	-	±1.0	μA
				6.0	-	-	2.0	-	20.0	
Quiescent Supply Current	I <sub>CC</sub>	V <sub>IN</sub> =V <sub>CC</sub> or GND		6.0	-	-	2.0	-	20.0	μA

## TIMING REQUIREMENTS (Input t<sub>r</sub>=t<sub>f</sub>=6ns)

CHARACTERISTIC	SYMBOL	TEST CONDITION		Ta=25°C			Ta=-40~85°C	UNIT
				V <sub>CC</sub>	Typ.	LIMIT	LIMIT	
Minimum Pulse Width (CLOCK)	t <sub>w(L)</sub> t <sub>w(H)</sub>	-		2.0	-	75	95	ns
				4.5	-	15	19	
				6.0	-	13	16	
Minimum Pulse Width ( $\overline{\text{CLR}}$ , $\overline{\text{PR}}$ )	t <sub>w(L)</sub>	-		2.0	-	75	95	
				4.5	-	15	19	
				6.0	-	13	16	
Minimum Set-up Time	t <sub>s</sub>	-		2.0	-	75	95	
				4.5	-	15	19	
				6.0	-	13	16	
Minimum Hold Time	t <sub>h</sub>	-		2.0	-	0	0	
				4.5	-	0	0	
				6.0	-	0	0	
Minimum Removal Time ( $\overline{\text{CLR}}$ , $\overline{\text{PR}}$ )	t <sub>rem</sub>	-		2.0	-	25	30	
				4.5	-	5	6	
				6.0	-	4	5	
Clock Frequency	f	-		2.0	-	6	5	MHz
				4.5	-	31	25	
				6.0	-	36	29	

# KIC7W74FK

## AC ELECTRICAL CHARACTERISTICS (C<sub>L</sub>=15pF, V<sub>CC</sub>=5V, Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Transition Time	t <sub>TLH</sub> t <sub>THL</sub>	-	-	6	12	ns
Propagation Delay Time (CLOCK-Q, $\bar{Q}$ )	t <sub>pLH</sub> t <sub>pHL</sub>	-	-	13	26	
Propagation Delay Time ( $\bar{CLR}$ , $\bar{PR}-Q, \bar{Q}$ )	t <sub>pLH</sub> t <sub>pHL</sub>	-	-	14	26	
Maximum Clock Frequency	f <sub>MAX</sub>	-	36	77	-	MHz

## AC ELECTRICAL CHARACTERISTICS (C<sub>L</sub>=50pF, Input t<sub>r</sub>=t<sub>f</sub>=6ns)

CHARACTERISTIC	SYMBOL	TEST CONDITION	V <sub>CC</sub>	Ta=25°C			Ta=-40~85°C		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	
Output Transition Time	t <sub>TLH</sub> t <sub>THL</sub>	-	2.0	-	30	75	-	95	ns
			4.5	-	8	15	-	19	
			6.0	-	7	13	-	16	
Propagation Delay Time (CLOCK-Q, $\bar{Q}$ )	t <sub>pLH</sub> t <sub>pHL</sub>	-	2.0	-	48	150	-	190	
			4.5	-	16	30	-	38	
			6.0	-	13	26	-	32	
Propagation Delay Time ( $\bar{CLR}$ , $\bar{PR}-Q, \bar{Q}$ )	t <sub>pLH</sub> t <sub>pHL</sub>	-	2.0	-	51	150	-	190	
			4.5	-	17	30	-	38	
			6.0	-	15	26	-	32	
Maximum Clock Frequency	f <sub>MAX</sub>	-	2.0	6	21	-	5	-	MHz
			4.5	31	63	-	25	-	
			6.0	36	67	-	29	-	
Input Capacitance	C <sub>IN</sub>	-	-	5	10	-	10	pF	
Power Dissipation Capacitance	C <sub>PD</sub>	(Note 1)	-	34	-	-	-		

Note 1 : C<sub>PD</sub> is defined as the value of internal equivalent capacitance which is calculated from the operating current consumption without load.

Average operating current can be obtained by the equation.

$$I_{CC(opp)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}$$