



## N-Channel MOSFET

### AO3434A-HF (KO3434A-HF)

#### ■ Features

- $V_{DS} (V) = 30V$
- $I_D = 4 A (V_{GS} = 10V)$
- $R_{DS(ON)} < 52m\ \Omega (V_{GS} = 10V)$
- $R_{DS(ON)} < 60m\ \Omega (V_{GS} = 4.5V)$
- $R_{DS(ON)} < 78m\ \Omega (V_{GS} = 2.5V)$
- Pb-Free Package May be Available. The G-Suffix Denotes a Pb-Free Lead Finish



#### ■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	
Continuous Drain Current	$I_D$	4	A
		3	
Pulsed Drain Current	$I_{DM}$	20	
Power Dissipation	$P_D$	1.4	W
		0.9	
Thermal Resistance.Junction- to-Ambient	$R_{thJA}$	90	$^\circ C/W$
		125	
Thermal Resistance.Junction- to-Case	$R_{thJC}$	80	
Junction Temperature	$T_J$	150	$^\circ C$
Storage Temperature Range	$T_{stg}$	-55 to 150	

## N-Channel MOSFET

### AO3434A-HF (KO3434A-HF)

#### ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Drain-Source Breakdown Voltage	V <sub>DSS</sub>	I <sub>D</sub> =250 μA, V <sub>GS</sub> =0V	30			V	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =30V, V <sub>GS</sub> =0V			1	μA	
		V <sub>DS</sub> =30V, V <sub>GS</sub> =0V, T <sub>J</sub> =55°C			5		
Gate-Body Leakage Current	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±10V			±10	μA	
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250 μA	0.7		1.5	V	
Static Drain-Source On-Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =4A			52	mΩ	
		V <sub>GS</sub> =10V, I <sub>D</sub> =4A, T <sub>J</sub> =125°C			82		
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =3A			60		
		V <sub>GS</sub> =2.5V, I <sub>D</sub> =2A			78		
On state drain current	I <sub>D(ON)</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =5V	20			A	
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =5V, I <sub>D</sub> =4A		15		S	
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =15V, f=1MHz		245		pF	
Output Capacitance	C <sub>oss</sub>			35			
Reverse Transfer Capacitance	C <sub>rss</sub>			20			
Gate Resistance	R <sub>g</sub>		V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz		5		
Total Gate Charge (10V)	Q <sub>g</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, I <sub>D</sub> =4A		5.7	10	nC	
Total Gate Charge (4.5V)				2.6	5		
Gate Source Charge			Q <sub>gs</sub>		0.5		
Gate Drain Charge			Q <sub>gd</sub>		1		
Turn-On DelayTime			t <sub>d(on)</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, R <sub>L</sub> =3.75 Ω, R <sub>G</sub> =3 Ω			2
Turn-On Rise Time	t <sub>r</sub>		3.5				
Turn-Off DelayTime	t <sub>d(off)</sub>		22				
Turn-Off Fall Time	t <sub>f</sub>		3.5				
Body Diode Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 4A, di/dt= 500A/us		6.5		nC	
Body Diode Reverse Recovery Charge	Q <sub>rr</sub>			7.5			
Maximum Body-Diode Continuous Current	I <sub>S</sub>				1.5	A	
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =1A, V <sub>GS</sub> =0V			1	V	

\* The static characteristics in Figures 1 to 6 are obtained using <300us pulses, duty cycle 0.5% max.

#### ■ Marking

Marking	Y4** F
---------	--------

## N-Channel MOSFET AO3434A-HF (KO3434A-HF)

■ Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

## N-Channel MOSFET AO3434A-HF (KO3434A-HF)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)