

1-CHANNEL TRANSISTOR OUTPUT TYPE PHOTO COUPLER

The KPC817 Series contains a light emitting diode optically coupled to a phototransistor. Input-output isolation voltage is 5000Vrms. Response time(tr) is typically 4us and minimum CTR is 50% at input current of 5mA.


FEATURES

- Collector-Emitter Voltage : Min.80V
- Current Transfer Ratio
(CTR : MIN. 50% at $I_F=5mA$, $V_{CE}=5V$).
- High isolation voltage between input and output.
($V_{ISO}=5,000Vrms$)
- Safety approval.
-UL and cUL : No.E177885
-VDE : No.40043394
-CQC : No.15001137903

APPLICATIONS

- Feedback circuit in power supply.
- Switching Mode Power Supply.
- System appliances, Measuring instruments.
- Registers, Copiers, Automatic vending machines.
- Electric home appliances such as fan heaters, etc.




BLOCK DIAGRAM AND PIN CONFIGURATIONS (TOP VIEW)



1. ANODE
2. CATHODE
3. EMITTER
4. COLLECTOR

RANK TABLE OF CURRENT TRANSFER RATIO(CTR)

RANK MARK	CTR (%)	TEST CONDITION
(None)	50~600	$I_F=5mA$, $V_{CE}=5V$, $T_a=25$
A	80~160	
B	130~260	
C	200~400	
D	300~600	
L	50~100	



KPC817 Series

MAXIMUM RATING (Ta=25)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Input	Forward Current	I _F	50	mA
	Reverse Voltage	V _R	6	V
	Power Dissipation	P _D	70	mW
Output	Collector Power Dissipation	P _C	150	mW
	Collector Current	I _C	50	mA
	Collector-Emitter Voltage	V _{CEO}	80	V
	Emitter-Collector Voltage	V _{ECO}	6	V
Total Power Dissipation		P _{tot}	200	mW
Isolation Voltage		V _{ISO}	5000	V _{rms}
Operating Temperature		T _{opr}	-50 110	
Storage Temperature		T _{stg}	-55~125	
Soldering Temperature		T _{sol}	260	


ELECTRO-OPTICAL CHARACTERISTICS (Ta=25 unless otherwise noted)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input	Forward	V _F	I _F =20mA	-	1.2	1.4	V
	Reverse Current	I _R	V _R =4V	-	-	10	uA
	Terminal Capacitance	C _t	V=0, f=1kHz	-	30	250	pF
Output	Collector Dark Current	I _{CEO}	V _{CE} =20V, I _F =0	-	-	100	nA
	Collector-Emitter Breakdown Voltage	BV _{CEO}	I _C =0.1mA, I _F =0	80	-	-	V
	Emitter-Collector Breakdown Voltage	BV _{ECO}	10uA, I _F =0	6	-	-	V
Transfer Characteristics	*Current Transfer Ratio	CTR	I _F =5mA, V _{CE} =5V	50	-	600	%
	Collector-Emitter Saturation Voltage	V _{CE(sat)}	I _F =20mA, I _C =1mA	-	0.1	0.2	V
	Isolation Resistance	R _{ISO}	DC500V, 40~60% R.H.	5 × 10 ¹⁰	1 × 10 ¹¹	-	
	Floating Capacitance	C _f	V=0, f=1MHz	-	0.6	1.0	pF
	Cut-off Frequency	F _C	V _{CE} =5V, I _C =2mA, R _L =100 , -3dB	-	80	-	kHz
	Rise Time	T _r	V _{CE} =2V, I _C =2mA, R _L =100	-	4	18	us
	Fall Time	T _f	V _{CE} =2V, I _C =2mA, R _L =100	-	3	18	us


$$* CTR = \frac{I_C}{I_F} \times 100\%$$

KPC817 Series


Forward Current vs. Ambient Temperature




Collector Power Dissipation vs. Ambient Temperature




Current Transfer Ratio vs. Forward Current




Forward Current vs. Forward Voltage



Collector Current vs. Collector-Emitter Voltage




Relative Current Transfer Ratio vs. Ambient Temperature




KPC817 Series


Collector-Emitter Saturation Voltage vs. Ambient Temperature




Collector Dark Current vs. Ambient Temperature




Response Time vs. Load Resistance



Frequency Response



Collector-Emitter Saturation Voltage vs. Forward Current



TEST Circuit for Response Time

