




# KSA614

KSA614

## Low Frequency Power Amplifier Power Regulator

- Collector-Base Voltage :  $V_{CBO} = -80V$
- Collector Dissipation :  $P_C = 25W$  ( $T_C = 25^\circ C$ )



1.Base 2.Collector 3.Emitter

## PNP Epitaxial Silicon Transistor

### Absolute Maximum Ratings $T_C = 25^\circ C$ unless otherwise noted

| Symbol    | Parameter                                    | Ratings    | Units      |
|-----------|--|------------|------------|
| $V_{CBO}$ | Collector- Base Voltage                      | - 80       | V          |
| $V_{CEO}$ | Collector- Emitter Voltage                   | - 55       | V          |
| $V_{EBO}$ | Emitter- Base Voltage                        | - 5        | V          |
| $I_C$     | Collector Current                            | - 3        | A          |
| $P_C$     | Collector Dissipation ( $T_C = 25^\circ C$ ) | 25         | W          |
| $T_J$     | Junction Temperature                         | 150        | $^\circ C$ |
| $T_{STG}$ | Storage Temperature                          | - 55 ~ 150 | $^\circ C$ |

### Electrical Characteristics $T_C = 25^\circ C$ unless otherwise noted

| Symbol        | Parameter                            | Test Condition                | Min. | Typ.   | Max.  | Units   |
|---------------|--------------------------------------|-------------------------------|------|--------|-------|---------|
| $BV_{CBO}$    | Collector-Base Breakdown Voltage     | $I_C = - 500\mu A, I_E = 0$   | - 80 |        |       | V       |
| $BV_{CEO}$    | Collector-Emitter Breakdown Voltage  | $I_C = - 10mA, I_B = 0$       | - 55 |        |       | V       |
| $BV_{EBO}$    | Emitter-Base Breakdown Voltage       | $I_E = - 500\mu A, I_C = 0$   | - 5  |        |       | V       |
| $I_{CBO}$     | Collector Cut-off Current            | $V_{CB} = - 50V, I_E = 0$     |      |        | - 50  | $\mu A$ |
| $h_{FE}$      | DC Current Gain                      | $V_{CE} = - 5V, I_C = - 0.5A$ | 40   |        | 240   |         |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage | $I_C = - 1A, I_B = - 0.1A$    |      | - 0.15 | - 0.5 | V       |

### $h_{FE}$ Classification

| Classification | R       | O        | Y         |
|----------------|---------|----------|-----------|
| $h_{FE}$       | 40 ~ 80 | 70 ~ 140 | 120 ~ 240 |

# Typical Characteristics




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. Base-Emitter Saturation Voltage  
Collector-Emitter Saturation Voltage




Figure 4. Collector Output Capacitance




Figure 5. Safe Operating Area





Figure 6. Power Derating



- NOTES:**
- A) REFERENCE JEDEC, TO-220, VARIATION AB
  - B) ALL DIMENSIONS ARE IN MILLIMETERS.
  - C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ].
  - D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
  - E) DOES NOT COMPLY JEDEC STANDARD VALUE.
  - F) "A1" DIMENSIONS AS BELOW:  
 SINGLE GAUGE = 0.51 - 0.61  
 DUAL GAUGE = 1.10 - 1.45
  - G) DRAWING FILE NAME: TO220B03REV9
  - H) PRESENCE IS SUPPLIER DEPENDENT
  - I) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local  
Sales Representative