



PRODUCT SPECIFICATION

cosmo ELECTRONICS CORPORATION	SOLID STATE RELAY :	NO. 58021103	REV.
	KSD203DC2	SHEET 1 OF 3	5

1. OUTSIDE DIMENSION : UNIT (mm)



2. SCHEMATIC : TOP VIEW



PRODUCT SPECIFICATION

cosmo ELECTRONICS CORPORATION	SOLID STATE RELAY :	NO. 58021103	REV. 5
	KSD203DC2	SHEET 2 OF 3	

3. Absolute Maximum Ratings

Parameter		Symbol	Rating	Unit
Input	Input signal voltage	V_{IN}	4~24	VDC
	Drop-out voltage	V_{do}	1	VDC
Output	Output power dissipation	P_c	30	W
	Collector voltage	V_{CEO}	100	V
	Output current	I_o	3	A
Peak surge current 50us		I_{surge}	9	A
Isolation voltage		V_{iso}	4000	Vrms
Operating temperature		T_{opr}	-30~100	°C
Storage temperature		T_{stg}	-30~125	°C
Soldering temperature 10 sec		T_{sol}	260	°C

4. Electrical Characteristics

Parameter		Symbol	Conditions	MIN	TYP	MAX	Unit
Input	Pick-up voltage	V_{pu}	$I_t=1A_{rms}$			4	VDC
	Input current	I_{in}	$V_{in}=4\sim 24V$			25	mA
	Terminal capacitance	C_T	$V=0, f=1KHz$		30		pF
Output	Collector-emitter breakdown voltage	BV_{CEO}	$I_F=0$	100			
	Output leak current	I_{leak}	$V=30V, I_F=0$			15	uA
Collector current		I_c	$I_F=1mA, V_{CE}=2V$	0.05		3	A
Collector-emitter saturation voltage		$V_{CE(sat)}$	$I_F=5mA, I_c=100mA$			2.0	V
Isolation resistance		R_{iso}	DC500V	10			GΩ
Floating capacitance		C_r	$V=0, f=1MHz$			3	pF
Cut-off frequency		F_c	$V_{CE}=2V, I_c=200mA$ $R_L=100\Omega$	2			KHz
Response time(Rise)		T_r	$V_{CE}=2V, I_c=20mA$			500	uS
Response time(Fall)		T_f	$R_L=100\Omega$			200	uS

PRODUCT SPECIFICATION

cosmo ELECTRONICS CORPORATION	SOLID STATE RELAY :	NO. 58021103	REV.
	KSD203DC2	SHEET 3 OF 3	5

- **Application Notice**

The statements regarding the suitability of products for certain types of applications are based on cosmo's knowledge of general applications of cosmo products. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to verify the specifications are suitable for use in a particular application. Customers are solely responsible for all aspects of their own product design or applications. The parameters provided in the datasheet may vary in different applications and performance may vary over time. All operating parameters (including typical parameters) must be validated by customer's technical experts for different applications. cosmo assumes no liability for customer' product design or applications. Product specifications do not expand or otherwise change cosmo's terms and conditions of purchase, including but not limited to the warranty expressed therein.

When using cosmo products, please comply with safety standards and instructions. cosmo has no liability and responsibility to the damage caused by improper use of the instructions specified in the specifications.

cosmo products are designed for use in general electronic equipment such as telecommunications, office automation equipments, personal computers, test and measurement equipments, consumer electronics, industrial control, instrumentation, audio, video.

cosmo devices shall not be used in equipment that requires higher level of reliability and safety, such as nuclear power control equipment, telecommunication equipment(trunk lines), space application, medical and other life supporting equipments, and equipment for aircraft, military, automotive or any other application that can cause human injury or death.

cosmo reserves the right to change the specifications, data, characteristics, structure, materials and other contents at any time without notice. Please contact cosmo to obtain the latest specification.

cosmo disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.