

isc Silicon NPN Power Transistor

KSH44H11

DESCRIPTION


- Lead formed for surface mount applications(NO suffix)
- Straight lead(IPAK, “—I” suffix)
- Electrically similar to popular KSE44H
- Fast switching speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Switching regulators
- Power amplifier
- Converters

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CEO}	Collector-Emitter Voltage	80	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	8	A
I_{CP}	Collector Current-Pulse	16	A
P_C	Total Power Dissipation @ $T_a=25^{\circ}\text{C}$	1.75	W
P_C	Total Power Dissipation @ $T_C=25^{\circ}\text{C}$	20	W
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\text{C}$



isc Silicon NPN Power Transistor**KSH44H11****ELECTRICAL CHARACTERISTICS****T_C=25°C unless otherwise specified**



SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
V _{(BR)CEO} *	Collector-Emitter Breakdown Voltage	I _C = 30mA; I _B = 0	80			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =8A; I _B = 400mA			1.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C =8A; I _B = 800mA			1.5	V
I _{CEO}	Collector Cutoff Current	V _{CE} = 80V; I _E = 0			10	uA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0			50	uA
h _{FE1}	DC Current Gain	I _C = 2A; V _{CE} = 1V	60			
h _{FE2}	DC Current Gain	I _C = 4A; V _{CE} = 1V	40			
f _T	Current-Gain—Bandwidth Product	I _C = 0.5A; V _{CE} = 10V		50		MHz

*:Pulse test PW≤300us,duty cycles≤2%

isc Silicon NPN Power Transistor

KSH44H11

Outline Drawing



isc Silicon NPN Power Transistor**KSH44H11****NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.