

Frequency Synthesizer

KSN-800A-119+

50Ω 684 to 800 MHz

The Big Deal

- Low phase noise and spurious
- Robust design and construction
- Small size 0.80" x 0.58" x 0.15"



CASE STYLE: DK1042

Product Overview

The KSN-800A-119+ is a Frequency Synthesizer, designed to operate from 684 to 800 MHz for W-CDMA application. The KSN-800A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.15") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Low phase noise and spurious: <ul style="list-style-type: none">• Phase Noise: -104 dBc/Hz typ. @ 10 kHz offset• Comparison Spurious: -96 dBc typ.• Reference Spurious: -116 dBc typ.	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Robust design and construction	To enhance the robustness of KSN-800A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.
Small size, 0.80" x 0.58" x 0.15"	The small size enables the KSN-800A-119+ to be used in compact designs.

www.DataSheet4U.com



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

www.DataSheet4U.com

Frequency Synthesizer

KSN-800A-119+

50Ω 684 to 800 MHz

Features

- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC VCO=+5V, VCC PLL=+3.3V)
- Small size 0.80" x 0.58" x 0.15"

Applications

- W-CDMA

General Description

The KSN-800A-119+ is a Frequency Synthesizer, designed to operate from 684 to 800 MHz for W-CDMA application. The KSN-800A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.15") to shield against unwanted signals and noise. To enhance the robustness of KSN-800A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.




CASE STYLE: DK1042
PRICE: \$29.95 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Simplified Schematic



www.DataSheet4U.com



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see www.minicircuits.com



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. OR
M126669
EDR-8530/2F1
KSN-800A-119+
www.DataSheet4U.com
100321
Page 2 of 11

Electrical Specifications (over operating temperature -40°C to +85°C)

Parameters	Test Conditions	Min.	Typ.	Max.	Units
Frequency Range	-	684	-	800	MHz
Step Size	-	-	200	-	kHz
Settling Time	Within ± 500 Hz	-	15	-	mSec
Output Power	-	0	+3	+6	dBm
SSB Phase Noise	@ 100 Hz offset	-	-80	-	dBc/Hz
	@ 1 kHz offset	-	-76	-70	
	@ 10 kHz offset	-	-104	-98	
	@ 100 kHz offset	-	-128	-121	
	@ 1 MHz offset	-	-148	-141	
Reference Spurious Suppression	Ref. Freq. 10 MHz	-	-116	-86	dBc
Comparison Spurious Suppression	Step Size 200 kHz	-	-96	-76	
Non - Harmonic Spurious Suppression	-	-	-90	-	
Harmonic Suppression	-	-	-30	-25	
VCO Supply Voltage	5.00	+4.75	5.00	+5.25	
PLL Supply Voltage	3.30	3.15	3.30	3.45	mA
VCO Supply Current	-	-	36	43	
PLL Supply Current	-	-	6	13	
Reference Input (External)	Frequency	10 (sine wave)	-	10	MHz
	Amplitude	1	-	1	V _{P-P}
	Input impedance	-	-	100	KΩ
	Phase Noise @ 1 kHz offset	-	-	-145	dBc/Hz
RF Output port Impedance	-	-	50	-	Ω
Input Logic Level	Input high voltage	-	2.80	-	V
	Input low voltage	-	-	0.60	V
Digital Lock Detect	Locked	-	2.75	-	V
	Unlocked	-	-	0.40	V
Frequency Synthesizer PLL	-	ADF4118			
PLL Programming	-	3-wire serial 3.3V CMOS			
Register Map @ 800 MHz	F_Register	-	(MSB) X0XXX00000X0010010010 (LSB)		
	N_Register	-	(MSB) 100000011111010000001 (LSB)		
	R_Register	-	(MSB) 1XXXX0000000011001000 (LSB)		

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	6.3V
PLL Supply Voltage	6.3V
VCO Supply Voltage to PLL Supply Voltage	-0.3V to +5.5V
Reference Frequency Voltage	-0.3Vmin, VCC PLL +0.3Vmax
Data, Clock, LE Levels	-0.3Vmin, VCC PLL +0.3Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see [minicircuits.com](http://www.minicircuits.com)

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp. www.DataSheet4U.com

Typical Performance Data

FREQUENCY (MHz)	POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURENT (mA)		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
684	4.94	4.58	4.15	34.18	36.36	37.47	5.24	6.22	7.15
685	4.93	4.57	4.14	34.18	36.37	37.48	5.20	6.19	7.13
700	4.76	4.43	3.97	34.18	36.37	37.49	5.21	6.22	7.15
715	4.46	4.26	3.77	34.21	36.38	37.50	5.22	6.24	7.17
730	4.16	4.05	3.55	34.25	36.41	37.52	5.19	6.22	7.15
745	4.01	3.81	3.31	34.31	36.44	37.54	5.21	6.24	7.18
760	3.91	3.52	3.03	34.31	36.45	37.54	5.22	6.26	7.19
775	3.64	3.22	2.73	34.28	36.43	37.54	5.20	6.24	7.17
790	3.20	2.91	2.41	34.24	36.41	37.54	5.21	6.26	7.19
800	2.90	2.71	2.20	34.21	36.41	37.54	5.20	6.25	7.18

FREQUENCY (MHz)	HARMONICS (dBc)					
	F2			F3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
684	-29.68	-32.70	-35.76	-52.50	-51.42	-57.83
685	-29.82	-32.70	-35.82	-52.86	-51.30	-57.92
700	-34.31	-36.25	-38.40	-55.24	-55.19	-63.99
715	-38.02	-38.40	-38.62	-58.97	-60.78	-78.94
730	-34.42	-36.56	-36.84	-54.99	-58.14	-62.40
745	-33.75	-36.41	-37.64	-55.34	-58.67	-63.17
760	-34.91	-37.81	-39.66	-58.43	-59.26	-62.54
775	-38.88	-39.79	-42.65	-63.99	-60.88	-62.52
790	-40.99	-43.74	-42.58	-60.77	-59.63	-61.77
800	-39.99	-43.40	-41.63	-57.43	-59.57	-58.73

www.DataSheet4U.com



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+25°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
684	-83.72	-75.87	-105.32	-129.64	-149.75
685	-82.65	-77.02	-106.58	-129.66	-149.71
700	-83.80	-76.59	-106.22	-129.50	-149.63
715	-84.52	-77.07	-105.40	-129.16	-149.39
730	-83.48	-77.68	-104.93	-129.19	-149.32
745	-83.30	-77.95	-104.39	-128.89	-149.01
760	-86.68	-77.97	-104.09	-127.57	-147.82
775	-85.07	-75.38	-102.92	-126.73	-146.83
790	-82.84	-75.34	-103.08	-125.89	-146.04
800	-81.00	-75.60	-101.97	-125.42	-145.70

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	-45°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
684	-82.15	-77.63	-106.15	-130.60	-150.79
685	-84.92	-79.28	-106.01	-130.46	-151.00
700	-79.64	-78.02	-105.98	-130.21	-150.62
715	-83.32	-77.26	-105.23	-130.08	-150.36
730	-81.79	-79.22	-105.50	-130.36	-150.56
745	-83.75	-77.86	-105.25	-130.34	-150.94
760	-85.18	-79.17	-104.60	-129.57	-149.90
775	-84.55	-78.69	-102.69	-127.64	-147.88
790	-82.63	-77.72	-102.55	-126.32	-146.64
800	-82.44	-77.27	-101.80	-125.77	-145.96

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+85°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
684	-83.68	-77.13	-105.27	-128.26	-148.36
685	-84.25	-76.14	-105.06	-128.19	-148.40
700	-83.04	-76.38	-104.94	-128.22	-148.34
715	-82.46	-76.69	-104.34	-128.03	-148.27
730	-83.01	-77.37	-104.38	-127.84	-148.02
745	-82.50	-77.73	-103.05	-127.36	-147.54
760	-83.42	-76.23	-102.69	-126.50	-146.82
775	-82.79	-74.51	-102.31	-125.73	-145.96
790	-80.15	-75.36	-101.87	-125.17	-145.32
800	-79.95	-74.73	-101.36	-124.69	-144.87



COMPARISON SPURIOUS ORDER	COMPARISON SPURIOUS @ Fcarrier 684MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @ Fcarrier 742MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @ Fcarrier 800MHz+(n*Fcomparison) (dBc) note 1		
	n			n			n		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-116.76	-115.98	-117.51	-115.80	-117.11	-117.67	-112.12	-116.15	-115.96
-4	-115.45	-114.30	-114.79	-117.41	-117.72	-112.22	-115.11	-116.47	-114.27
-3	-115.31	-102.15	-102.90	-112.77	-102.14	-103.13	-109.50	-101.43	-101.78
-2	-110.45	-108.20	-107.42	-105.14	-108.88	-105.36	-103.22	-108.17	-107.68
-1	-93.25	-97.76	-96.89	-96.63	-98.09	-96.50	-97.62	-93.92	-98.26
0 note 2	-	-	-	-	-	-	-	-	-
+1	-93.38	-94.57	-95.52	-95.06	-96.66	-95.10	-96.91	-98.99	-94.47
+2	-104.48	-106.33	-107.70	-105.13	-107.90	-104.59	-109.23	-105.67	-105.89
+3	-115.27	-105.99	-101.17	-110.78	-100.49	-103.78	-110.57	-101.62	-101.85
+4	-114.56	-117.23	-116.41	-114.51	-117.65	-118.40	-112.31	-112.53	-116.32
+5	-115.45	-115.69	-116.18	-116.13	-118.26	-117.39	-113.80	-116.58	-115.04

Note 1: Comparison frequency 200 kHz
 Note 2: All spurs are referenced to carrier signal (n=0).

REFERENCE SPURIOUS ORDER	REFERENCE SPURIOUS @ Fcarrier 684MHz+(n*Freference) (dBc) note 3			REFERENCE SPURIOUS @ Fcarrier 742MHz+(n*Freference) (dBc) note 3			REFERENCE SPURIOUS @ Fcarrier 800MHz+(n*Freference) (dBc) note 3		
	n			n			n		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-122.11	-112.98	-112.04	-122.17	-114.45	-111.43	-123.59	-112.42	-112.99
-4	-122.53	-123.88	-126.61	-124.90	-124.77	-123.39	-107.01	-124.21	-111.58
-3	-121.66	-120.74	-121.14	-119.18	-121.82	-121.28	-117.61	-115.79	-113.03
-2	-125.88	-129.55	-126.23	-129.85	-125.86	-125.13	-103.21	-122.99	-106.63
-1	-116.36	-118.10	-118.44	-115.58	-119.37	-114.23	-110.15	-108.22	-110.47
0 note 4	-	-	-	-	-	-	-	-	-
+1	-119.80	-121.59	-123.12	-116.73	-115.93	-114.90	-108.77	-109.33	-111.57
+2	-128.73	-126.16	-124.59	-124.96	-127.50	-124.01	-106.67	-126.34	-110.07
+3	-119.49	-121.03	-123.46	-115.02	-118.67	-118.57	-115.49	-115.58	-121.02
+4	-127.34	-125.02	-124.69	-124.89	-126.07	-124.95	-111.02	-122.88	-114.70
+5	-119.94	-115.81	-112.72	-117.31	-115.99	-110.95	-112.51	-111.76	-111.63

Note 3: Reference frequency 10 MHz
 Note 4: All spurs are referenced to carrier signal (n=0).



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Typical Performance Curves


OUTPUT POWER Vs FREQUENCY



2nd HARMONIC Vs FREQUENCY



3rd HARMONIC Vs FREQUENCY



www.DataSheet4U.com



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


PHASE NOISE @100Hz offset




PHASE NOISE @1kHz offset




PHASE NOISE @10kHz offset



PHASE NOISE @100kHz offset



PHASE NOISE @1MHz offset



www.DataSheet4U.com









IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp.

Pin Configuration




Pin Connection

Pin Number	Function
1	VCC PLL
2	GND
3	REF IN
4	GND
5	VCC VCO
6	GND
7	RF OUT
8	GND
9	LOCK DET
10	CLOCK
11	DATA
12	LE
13	GND
14	GND

Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.



www.DataSheet4U.com



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Device Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: DK1042

Tape & Reel: TR-F28

Suggested Layout for PCB Design: PL-249

Evaluation Board: TB-567-1+

Environment Ratings: ENV03T2