

30A Avg.

30 Volts


SBD

KSQ30A03LB

■最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	V_{RRM}	30	V
平均整流電流 Average Rectified Forward Current	I_O	50Hz、正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	30
実効順電流 R.M.S. Forward Current	$I_F(RMS)$	47.1	A
サージ順電流 Surge Forward Current	I_{FSM}	400 50Hz正弦半波、1サイクル、非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	T_{jw}	-40~+150	°C
保存温度範囲 Storage Temperature Range	T_{stg}	-40~+150	°C
締付トルク Mounting torque	F_{tor}	推奨値 Recommended Value	0.5 N·m

■OUTLINE DRAWING(mm)



■APPROX. NET WEIGHT:5.55g

■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	I_{RM}	$T_j=25^{\circ}C$, $V_{RM}=V_{RRM}$, 一素子あたり Per Diode	—	—	25	mA
ピーク順電圧 Peak Forward Voltage	V_{FM}	$T_j=25^{\circ}C$, $I_{FM}=30A$, 一素子あたり Per Diode	—	—	0.50	V
熱抵抗 Thermal Resistance	$R_{th(j-c)}$	接合部・ケース間 Junction to Case	—	—	1.3	°C/W

■定格・特性曲線

