

### ● Description

The KT1410 series consist of a photodarlington optically coupled to a gallium arsenide infrared-emitting diode in a 4 pin LSOP wide body package. Collector-emitter voltage is 300V. It features a high current transfer ratio, low coupling capacitance and high isolation voltage.


### ● Features

1. Halogen free
2. Pb free and RoHS compliant
3. Temperature range -55°C to 115°C
4. Opaque type, SMD low profile 4 lead package
5. High collector-emitter voltage ( $V_{CE0} : 300V$ )
6. High current transfer ratio  
(CTR : Min.1000% at  $I_F = 1mA, V_{CE} = 2V$ )
7. High isolation voltage 5000Vrms
8. 8mm outer creepage distance
9. MSL class 1
10. Agency Approvals:
  - UL Approved (No. E169586): UL1577
  - c-UL Approved (No. E169586)
  - VDE Approved (No. 40031267): DIN EN60747-5-5
  - FIMKO Approved: EN60065, EN60950, EN60335, EN60601
  - CQC Approved: GB8898-2011, GB4943.1-2011

### ● Applications

- Telephone sets
- Copiers, facsimiles
- Interfaces with various power supply circuits power distribution boards.
- Hybrid substrates which require high density mounting


### ● Schematic



1. Anode
2. Cathode
3. Emitter
4. Collector


### ● Outside Dimension

Unit : mm



TOLERANCE : ±0.2mm

### ● Device Marking



#### Notes:

**cosmo**

141□

YWW

□: CTR rank

Y: Year code / WW: Week code

### ● Absolute Maximum Ratings

(Ta=25°C)

| Parameter                        |                             | Symbol           | Rating      | Unit             |
|----------------------------------|-----------------------------|------------------|-------------|------------------|
| Input                            | Forward current             | I <sub>F</sub>   | 50          | mA               |
|                                  | Peak forward current        | I <sub>FP</sub>  | 1           | A                |
|                                  | Reverse voltage             | V <sub>R</sub>   | 6           | V                |
|                                  | Power dissipation           | P <sub>D</sub>   | 70          | mW               |
| Output                           | Collector-Emitter voltage   | V <sub>CEO</sub> | 300         | V                |
|                                  | Emitter-Collector voltage   | V <sub>ECO</sub> | 0.1         | V                |
|                                  | Collector current           | I <sub>C</sub>   | 150         | mA               |
|                                  | Collector power dissipation | P <sub>C</sub>   | 150         | mW               |
| Total power dissipation          |                             | P <sub>tot</sub> | 170         | mW               |
| Isolation voltage 1 minute       |                             | V <sub>iso</sub> | 5000        | V <sub>rms</sub> |
| Operating temperature            |                             | T <sub>opr</sub> | -55 to +115 | °C               |
| Storage temperature              |                             | T <sub>stg</sub> | -55 to +125 | °C               |
| Soldering temperature 10 seconds |                             | T <sub>sol</sub> | 260         | °C               |

### ● Electro-optical Characteristics


(Ta=25°C)

| Parameter                |                                      | Symbol               | Conditions                                                      | Min.               | Typ.             | Max. | Unit |
|--------------------------|--------------------------------------|----------------------|-----------------------------------------------------------------|--------------------|------------------|------|------|
| Input                    | Forward voltage                      | V <sub>F</sub>       | I <sub>F</sub> =20mA                                            | -                  | 1.2              | 1.4  | V    |
|                          | Reverse current                      | I <sub>R</sub>       | V <sub>R</sub> =4V                                              | -                  | -                | 10   | uA   |
|                          | Terminal capacitance                 | C <sub>t</sub>       | V=0, f=1KHz                                                     | -                  | 30               | -    | pF   |
| Output                   | Collector dark current               | I <sub>CEO</sub>     | V <sub>CE</sub> =200V, I <sub>F</sub> =0                        | -                  | -                | 1    | uA   |
|                          | Collector-Emitter breakdown voltage  | BV <sub>CEO</sub>    | I <sub>C</sub> =0.1mA, I <sub>F</sub> =0                        | 300                | -                | -    | V    |
| Transfer characteristics | Current transfer ratio               | CTR                  | I <sub>F</sub> =1mA, V <sub>CE</sub> =2V                        | 1000               | -                | -    | %    |
|                          | Collector-Emitter saturation voltage | V <sub>CE(sat)</sub> | I <sub>F</sub> =1mA, I <sub>C</sub> =2mA                        | -                  | -                | 1.5  | V    |
|                          | Isolation resistance                 | R <sub>iso</sub>     | DC500V, 40 to 60%RH                                             | 5x10 <sup>10</sup> | 10 <sup>11</sup> | -    | Ω    |
|                          | Floating capacitance                 | C <sub>f</sub>       | V=0, f=1MHz                                                     | -                  | 0.6              | 1.0  | pF   |
|                          | Response time (Rise)                 | t <sub>r</sub>       | V <sub>CC</sub> =2V, I <sub>C</sub> =20mA, R <sub>L</sub> =100Ω | -                  | 100              | 300  | us   |
|                          | Response time (Fall)                 | t <sub>f</sub>       |                                                                 | -                  | 20               | 100  | us   |


Classification table of current transfer ratio is shown below.

| CTR Rank | CTR ( % ) |
|----------|-----------|
| KT1410   | Min.1000  |


**Fig.1 Current Transfer Ratio  
vs. Forward Current**




**Fig.2 Collector Power Dissipation  
vs. Ambient Temperature**




**Fig.3 Collector Dark Current  
vs. Ambient Temperature**




**Fig.4 Forward Current  
vs. Ambient Temperature**




**Fig.5 Forward Current  
vs. Forward Voltage**




**Fig.6 Collector Current vs. Collector-Emitter Voltage**




**Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature**





**Fig.8 Collector-Emitter Saturation Voltage vs. Forward Current**



**Fig.9 Response Time vs. Load Resistance**



## ● Test Circuit for Response Time




### ● Recommended Soldering Conditions

#### (a) Infrared reflow soldering :

- Peak reflow soldering : 260°C or below (package surface temperature)
- Time of peak reflow temperature : 10 sec
- Time of temperature higher than 230°C : 30-60 sec
- Time to preheat temperature from 180~190°C : 60-120 sec
- Time(s) of reflow : Two
- Flux : Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

#### Recommended Temperature Profile of Infrared Reflow



#### (b) Wave soldering :

- Temperature : 260°C or below (molten solder temperature)
- Time : 10 seconds or less
- Preheating conditions : 120°C or below (package surface temperature)
- Time(s) of reflow : One
- Flux : Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

#### (c) Cautions :

- Fluxes : Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent.
- Avoid shorting between portion of frame and leads.

- **Numbering System**

## KT1410 (Z)


### Notes:

KT1410 = Part No.

Z = Tape and reel option (TLD 、TRU)


| Option | Description            | Packing quantity    |
|--------|------------------------|---------------------|
| TLD    | TLD tape & reel option | 3000 units per reel |
| TRU    | TRU tape & reel option | 3000 units per reel |

- **Recommended Pad Layout for Surface Mount Lead Form**



Unit : mm

### ● 4-pin LSOP Carrier Tape & Reel



### ● Application Notice

The content of datasheet is the guidance for product use only. cosmo takes no responsibility to the accuracy of the information provided here. For continuously improving all of products, including quality, reliability, function...etc., cosmo reserves the right to change the specification, characteristics, data, materials, and structure of products without notice. Please contact with cosmo to obtain the latest specification.

It would be required to comply with the absolute maximum ratings listed in the specification. cosmo has no liability and responsibility to the damage caused by improper use of the products.

cosmo products are intended to be designed for use in general electronics application list below:

- a. Personal computer
- b. OA machine
- c. Audio / Video
- d. Instrumentation
- e. Electrical application
- f. Measurement equipment
- g. Consumer electronics
- h. Telecommunication

cosmo devices shall not be used or related with equipment requiring higher level of quality / reliability, or malfunction, or failure which may cause loss of human life, bodily injury, includes, without limitation:

- a. Medical and other life supporting equipments
- b. Space application
- c. Telecommunication equipment (trunk lines)
- d. Nuclear power control
- e. Equipment used for automotive vehicles, trains, ships...etc.

This publication is the property of cosmo. No part of this publication may be reproduced or copied in any form or any means electronically or mechanically for any purpose, in whole or in part without any written permission expressed from cosmo.