

HIGH FREQUENCY APPLICATION.  
VHF BAND AMPLIFIER APPLICATION.

### FEATURES

- High Gain :  $G_{pe}=33\text{dB(Typ.)}$  ( $f=45\text{MHz}$ ).
- Good Linearity of  $h_{FE}$ .

### MAXIMUM RATING ( $T_a=25^\circ\text{C}$ )


CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	$V_{CBO}$	30	V
Collector-Emitter Voltage	$V_{CEO}$	25	V
Emitter-Base Voltage	$V_{EBO}$	4	V
Collector Current	$I_C$	50	mA
Emitter Current	$I_E$	-50	mA
Collector Power Dissipation	$P_C$	625	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	-55 ~ 150	$^\circ\text{C}$




### ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$ )

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		$I_{CBO}$	$V_{CB}=30\text{V}, I_E=0$	-	-	0.1	$\mu\text{A}$
Emitter Cut-off Current		$I_{EBO}$	$V_{EB}=3\text{V}, I_C=0$	-	-	0.1	
Collector-Emitter Breakdown Voltage		$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	25	-	-	V
DC Current Gain		$h_{FE}$	$V_{CE}=12.5\text{V}, I_C=12.5\text{mA}$	20	-	200	
Saturation Voltage	Collector-Emitter	$V_{CE(sat)}$	$I_C=15\text{mA}, I_B=1.5\text{mA}$	-	-	0.2	V
	Base-Emitter	$V_{BE(sat)}$		-	-	1.5	
Collector Output Capacitance		$C_{ob}$	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$	0.8	-	2.0	pF
Collector-Base Time Constant		$C_c \cdot r_{bb}$	$V_{CB}=10\text{V}, I_E=-1\text{mA}, f=30\text{MHz}$	-	-	25	pS
Transition Frequency		$f_T$	$V_{CE}=12.5\text{V}, I_C=12.5\text{mA}$	300	-	-	MHz
Power Gain (Fig.1)		$G_{pe}$	$V_{CC}=12.5\text{V}, I_E=-12.5\text{mA}, f=45\text{MHz}$	28	-	36	dB


Fig. 1 45MHz  $G_{pe}$  TEST CIRCUIT




### STATIC CHARACTERISTICS




### $I_C - V_{CE}$




### $G_{pe} - I_E$ (See Fig 1)




### $h_{FE} - I_C$




$f_T - I_C$




$C_{ob} - V_{CB}$




$g_{oe}, C_{oe} - I_C$



$g_{oe}, C_{oe} - I_C$



$g_{ie}, C_{ie} - I_C$



$g_{ie}, C_{ie} - I_C$

