

KTC4374 TRANSISTOR (NPN)**FEATURES**

Power dissipation

 P_{CM} : 500 mW ($T_{amb}=25^{\circ}C$)

Collector current

 I_{CM} : 400 mA

Collector-base voltage

 $V_{(BR)CBO}$: 80 V


Operating and storage junction temperature range

 T_J, T_{stg} : $-55^{\circ}C$ to $+150^{\circ}C$ **SOT-89**

1. BASE

2. COLLECTOR

3. EMITTER

**ELECTRICAL CHARACTERISTICS** ($T_{amb}=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=1mA, I_E=0$	80			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	80			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=1mA, I_C=0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB}=80V, I_E=0$			0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=5V, I_C=0$			0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=2V, I_C=50mA$	70		240	
	$h_{FE(2)}$	$V_{CE}=2V, I_C=200mA$	50			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=200mA, I_B=20mA$			0.4	V
Base-emitter voltage	V_{BE}	$V_{CE}=2V, I_C=5mA$			0.8	V
Transition frequency	f_T	$V_{CE}=10V, I_C=10mA$		100		MHz
Collector output capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$		10		pF

CLASSIFICATION OF $h_{FE(1)}$

Rank	O	Y
Range	70-140	120-240
Marking	EO	EY