



FOR LOW-FREQUENCY AMPLIFICATION.

FEATURES

- High forward current transfer ratio h_{FE} .
- Low collector to emitter saturation voltage $V_{CE(sat)}$.
- High emitter to base voltage V_{EBO} .
- Low noise voltage NV.
- ESM type package, allowing downsizing of the equipment and automatic insertion through the tape packing and the magazine packing.

MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CBO}	50	V
Collector-Emitter Voltage		V_{CEO}	40	V
Emitter-Base Voltage		V_{EBO}	15	V
Collector Current	DC	I_C	50	mA
	Pulse	I_{CP}	100	
Collector Power Dissipation		P_C	100	mW
Junction Temperature		T_j	150	°C
Storage Temperature Range		T_{stg}	-55 ~ 150	°C




ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=20V, I_E=0$	-	-	100	nA
	I_{CEO}	$V_{CE}=20V, I_B=0$	-	-	1	μA
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=10\mu A, I_E=0$	50			V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=1mA, I_B=0$	40			V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	15			V
DC Current Gain	h_{FE} (Note)	$V_{CE}=10V, I_C=2mA$	400	1000	2000	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=10mA, I_B=1mA$	-	0.05	0.2	V
Transition Frequency	f_T	$V_{CB}=10V, I_E=-2mA, f=200MHz$	-	120	-	MHz


Note : h_{FE} Classification A:400~800, B:600~1200, C:1000~2000

KTD1824E


$I_C - V_{CE}$




$h_{FE} - I_C$




$V_{CE(sat)} - I_C$




$I_C - V_{BE}$



$f_T - I_E$



$C_{ob} - V_{CB}$



KTD1824E

