

# SPECIFICATION FOR APPROVAL

## 承 認 書

Description : **Magnetic Buzzer**

Kingstate Part No. : **KXG0906**

Customer's Model No. :

Specification No. : **TKR-5254**

Number Of The Edition : **1.1**

CUSTOMER'S APPROVED SIGNATURE		



志豐電子股份有限公司 KINGSTATE ELECTRONICS CORP.

Address: 10F, No. 69-11, Sec. 2, Chung Cheng E. Rd., Tamshui County, Taipei Hsien, Taiwan, R.O.C.

International sales dept.: TEL : 886-2-2809-5651 FAX:886-2-2809-7151

Domestic sales dept.: TEL : 886-2-2809-0668 FAX:886-2-28096748

[http : //www.kingstate.com.tw](http://www.kingstate.com.tw)


Approved by	Checked by	Issued by
		Merry 06/18/15`

## A. SCOPE 範疇


This specification applies magnetic buzzer, **KXG0906**

此規格書適用於電磁式蜂鳴器, **KXG0906**


## B. SPECIFICATION 規格

No.	Item	Unit	Specification	Condition
1	Rated Voltage 額定電壓	Vo-p	6.0	
2	Operating Volt. 操作電壓	Vo-p	5.0~7.0	
3	Mean Current 平均耗電流	mA	Max. 120	Applying rated voltage, 3500Hz square wave, 1/2duty 施以額定電壓, 3500Hz, 方波, 50%負載
4	Coil Resistance 直流阻抗	$\Omega$	25 $\pm$ 5	
5	Sound Output 輸出音壓	dB	Min. 80	Distance at 10cm(A-weight free air). Applying rated voltage 2700Hz, square wave, 1/2duty 在自由音場 10 公分處, 施以額定電壓, 2700Hz, 方波, 50%負載
			Min. 100	Distance at 10cm(A-weight free air). Applying rated voltage 3500Hz, square wave, 1/2duty 在自由音場 10 公分處, 施以額定電壓, 3500Hz, 方波, 50%負載
6	Rated Frequency 額定頻率	Hz	3500	
7	Operating Temp. 操作溫度	$^{\circ}\text{C}$	-30 ~ +70	
8	Storage Temp. 儲存溫度	$^{\circ}\text{C}$	-40 ~ +85	
9	Dimension 尺寸	mm	$\phi 9.0 \times H5.5$	See attached drawing. 請參照外觀尺寸圖
10	Weight 重量	gram	0.6	
11	Material 材質		PBT	
12	Terminal 端子		Pin type (鍍全錫/Plating Sn)	See attached drawing. 請參照外觀尺寸圖
13	Environmental Protection Regulation 環保法規		HSF	
14	Storage life 保存期限	month	6	6 months preservation at room temp. (25 $\pm$ 3 $^{\circ}\text{C}$ ), Humidity 40% 在室溫下 25 $\pm$ 3 $^{\circ}\text{C}$ , 濕度 40% 以下可保存 6 個月.

**C. TYPICAL FREQUENCY RESPONSE CURVE** 頻率響應曲線




**D. APPEARANCE DRAWING** 外觀尺寸圖



**Tol: ± 0.5**  
**Unit: mm**



## E. MEASUREMENT METHOD 測量方式



## F. MECHANICAL CHARACTERISTICS 機械特性

No.	Item	Test condition	Evaluation standard
1	Solderability 焊錫附著性	Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of +270±5°C for 3±1 seconds. 端子部份浸入松香溶液5秒後,再浸入+270±5°C 熔融焊錫槽中 3±1 秒.	90% min. lead terminals shall be wet with solder. (Except the edge of terminal) 浸入端子部份附著焊錫 90%以上.(末端斷面不算)
2	Soldering Heat Resistance 焊錫耐熱性	Lead terminal are immersed up to 1.5mm from sounder's body in solder bath of +260±5°C for 3±1 seconds. 距離端子根部 1.5mm 的位置,浸入+260±5°C 的焊錫槽 3±1 秒.	No interference in operation 操作無任何不良
3	Terminal Mechanical Strength 端子強度	The force 10 seconds of 9.8N (1.0kg) is applied to each terminal in axial direction. 各端子的軸方向施以 9.8N(1.0kg)的力量 10 秒.	No damage and cutting off 端子不鬆動, 不脫落
4	Vibration 振動測試	Buzzer shall be measured after being applied vibration of amplitude of 1.5mm with 10 to 55hz band of vibration frequency to each of 3 per-pendicular directions for 2 hours. 振動週波數 10~55HZ、全振幅 1.5mm 於 X.Y.Z 3 個方向,各 2 小時.	After the test the part shall meet specifications with-out any damage in appearance and the SPL should be in ±10dB compared with initial one.
5	Drop test 落下測試	The part only shall be dropped from a height of 75cm onto a 40mm thick wooden board 3 times in 3 axes (X.Y.Z). (a total of 9 times). 單體從 75 公分高處, X.Y.Z.3 個方向,各 3 回,落於 40mm 厚木板上.	經測試後,單體除音壓外,外觀及電氣特性須符合規格. 輸出音壓變化量須在 ±10dBA 內.

## G. ENVIRONMENT TEST 環境測試

No.	Item	Test condition	Evaluation standard
1	High temp. test 高溫測試	After being placed in a chamber at +85°C for 96 hours. 置於+85°C環境中 96 小時	After the test the part shall meet specifications with-out any degradation in appearance and performance except SPL after 4 hours at +25°C. the SPL should be in ±10dBA compared with initial one. 經測試後，靜置於+25°C（室溫）環境中 4 小時後，單體除音壓外，外觀及電氣特性須符合規格。輸出音壓變化量須在±10dBA 內。
2	Low temp. test 低溫測試	After being placed in a chamber at -40°C for 96 hours. 置於-40°C環境中 96 小時	
3	Thermal Shock 熱衝擊試驗	The part shall be subjected to 10 cycles. One cycle shall consist of; 對單體施以熱衝擊試驗 10 次循環,其循環內容如圖示 	
4	Temp./ Humidity Cycle 溫度/溼度循環測試	The part shall be subjected to 10 cycles. One cycle shall be 24 hours and consist of; 單體承受溫度/溼度循環測試 10 次. 其循環內容如圖示 	



## H. RELIABILITY TEST 信賴性測試

No.	Item	Test condition	Evaluation standard
1	Operating life test 壽命測試	<p>1. Continuous life test 高溫壽命測試(連續) The part shall be subjected to 72 hours at +55°C with 6V, 3500Hz applied. 在+55°C環境下,輸入 6V,3500Hz 連續操作 72 小時。</p> <p>2. Intermittent life test 室溫壽命測試(間歇) A duty cycle of 1 minute on, 1 minutes off, a minimum of 10000 times at room temp.( +25±10°C) with 6V,3500Hz applied. 在室溫下(+25±10°C), 輸入 6V,3500Hz 通電 1 分鐘/斷電 1 分鐘,測試 10000 次循環。</p>	After the test the part shall meet specifications with-out any degradation in appearance and performance except SPL after 4 hours at +25°C. the SPL should be in ±10dBA compared with initial one. 經測試後，靜置於+25°C（室溫）環境中 4 小時後，單體除音壓外，外觀及電氣特性須符合規格。輸出音壓變化量須在±10dBA 內。


### TEST CONDITION.

Standard Test Condition : a) Temperature : +5 ~ +35°C    b) Humidity : 45-85%    c) Pressure : 860-1060mbar  
 一般測試條件 : a) 溫度 : +5 ~ +35°C    b) 濕度 : 45-85%    c) 氣壓 : 860-1060mbar  
 Judgement Test Condition : a) Temperature : +25 ± 2°C    b) Humidity : 60-70%    c) Pressure : 860-1060mbar  
 爭議時測試條件 : a) 溫度 : +25 ± 2°C    b) 濕度 : 60-70%    c) 氣壓 : 860-1060mbar

# I. PACKING STANDARD 包裝規格

Lot No.	XXXXXXXXXX
Part No.	XXXXXXXXXX
Quantity	XXXX PCS
Date:	DD MM YY
	
	

\* The label sticked on inner boxes and the outer of carton.



包裝箱	長×寬×高(mm)	包裝數量(只)
泡沫盒	240×160×28	1x100PCS=100PCS
塑料袋	240×160×280	10LAYERx100PCS=1000PCS
紙箱	510×420×280	1000PCSx5=5000PCS