




L16B40

Preliminary

CMOS IC

16-BIT CONSTANT CURRENT LED DRIVER WITH BUILT-IN TO ELIMINATE THE GHOSTING



DESCRIPTION

UTC **L16B40** is a new 16-bit constant current LED driver IC with 20V output rating. Output currents with high accuracy and consistency can be preset through an external resistor. The output current ranges from 2mA to 40mA.

Moreover, the fast current response time and built-in to eliminate the ghosting make UTC **L16B40** performing better in output current and display image.

FEATURES


- * Built-in to eliminate the ghosting
- * Supply voltage range: 3.3V ~ 5.5V
- * Constant output current range: 2 ~ 40mA
- * Output voltage: 20V (Max.)
- * Operating temperature range: -40°C ~ 85°C
- * Output current accuracy:
ICs: ±3.0% (Typ.)

ORDERING INFORMATION


Ordering Number	Package	Packing
L16B40G-R24-R	SSOP-24	Tape Reel

<p>L16B40G-R24-R</p> <ul style="list-style-type: none"> (1) Packing Type (2) Package Type (3) Green Package 	<ul style="list-style-type: none"> (1) R: Tape Reel (2) R24: SSOP-24 (3) G: Halogen Free and Lead Free
--	---

MARKING




PIN CONFIGURATION



■ PIN DESCRIPTION


PIN NO.	PIN NAME	DESCRIPTION
1	GND	Ground
2	DAI	Serial-data input
3	DCK	Clock input
4	LAT	Data strobe signal input
5~20	OUT0 ~15	Constant current outputs
21	ENB	Enable signal input
22	DAO	Serial-data output
23	REXT	Input terminal used to connect an external resistor for setting up output current
24	V _{DD}	Supply voltage

■ BLOCK DIAGRAM




■ EQUIVALENT CIRCUITS OF INPUTS AND OUTPUTS


DAI/DCK




LAT



DAO



ENB



■ ABSOLUTE MAXIMUM RATING ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage Range	V_{DD}	0 ~ 7.0	V
Input Voltage Range	V_{IN}	-0.4 ~ $V_{DD}+0.4$	V
Output Current (OUT15 ~ 0)	I_{OUT}	40	mA
Output Voltage (OUT15 ~ 0)	V_{OUT}	-0.3 ~ 20	V
Clock Frequency	F_{DCK}	30	MHz
GND Pin Current	F_{GND}	1000	mA
Power Dissipation (on PCB)	P_D	0.9	W
Thermal Resistance (on PCB)	$R_{TH(i-a)}$	75	$^\circ\text{C}/\text{W}$
Operating Temperature	T_{OPR}	-40 ~ +85	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{DD}		3.3	5.0	5.5	V
Output Voltage (OUT15 ~ 0)	V_{OUT}	I_{OUT} off			20	V
		I_{OUT} on	0.7		$0.5 \times V_{DD}$	V
Output Current	I_{OUT}	OUT15 ~ 0	2		40	mA
	I_{OH}	$V_{OH}=V_{DD}-0.2\text{V}$		-0.66		
	I_{OL}	$V_{OL}=0.2\text{V}$		2.0		
Input Voltage (DAI/ENB/LAT/DCK)	V_{IH}	$V_{DD}=3.3\text{V}\sim 5.5\text{V}$	$0.7 \times V_{DD}$		V_{DD}	V
	V_{IL}		0		$0.3V_{DD}$	

■ ELECTRICAL CHARACTERISTICS ($V_{DD}=5.0\text{V}$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{DD}		4.5	5.0	5.5	V
Sustaining Voltage At OUT Ports	V_{OUT}	OUT15 ~ 0			20	V
Output Leakage Current	I_{LEAK}	$V_{OUT}=20\text{V}$			1	μA
Input Voltage	"H" level	Logic Level	$0.7 \times V_{DD}$		V_{DD}	V
	"L" level		0		$0.3 \times V_{DD}$	
DAO Voltage	V_{OH}	$I_{OH}=-0.66\text{mA}$	$V_{DD}-0.2$			V
	V_{OL}	$I_{OL}=1.0\text{mA}$			0.2	
Output Current Accuracy	I_{CS}	I_{OSC}	$V_{OUT}=1.0\text{V}$, $R_{EXT}=2045\Omega$	± 3.0		%
Output Current Vs.	Output Voltage Regulation	$\%/\Delta V_{OUT}$	$R_{EXT}=2045\Omega$, $V_{OUT}=1\text{V}\sim 2\text{V}$		± 0.1	%V
	Supply Voltage Regulation	$\%/\Delta V_{DD}$	$R_{EXT}=2045\Omega$, $V_{DD}=4.5\text{V}\sim 5.5\text{V}$		± 1	
Supply Current	$I_{DD\ OFF1}$	R_{EXT} open, OUT15 ~ 0 off		2.1	3.1	mA
	$I_{DD\ OFF2}$	$R_{EXT}=2045\Omega$, OUT15 ~ 0 off		6.2		
	$I_{DD\ ON}$	$R_{EXT}=2045\Omega$, OUT15 ~ 0 on		7.1		

■ ELECTRICAL CHARACTERISTICS ($V_{DD}=3.3V$)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage		V_{DD}		3.0	3.3	3.6	V
Sustaining Voltage At OUT Ports		V_{OUT}	OUT15 ~ 0			20	V
Output Leakage Current		I_{LEAK}	$V_{OUT}=20V$			1	μA
Input Voltage	"H" level	V_{IH}	Logic Level	$0.7 \times V_{DD}$		V_{DD}	V
	"L" level	V_{IL}		0		$0.3 \times V_{DD}$	
DAO Voltage		V_{OH}	$I_{OH}=-0.66mA$	$V_{DD}-0.2$			V
		V_{OL}	$I_{OL}=1.0mA$			0.2	
Output Current Accuracy	ICs	I_{OSC}	$V_{OUT}=1.0V, R_{EXT}=2045\Omega$		± 3.0		%
Output Current Vs.	Output Voltage Regulation	$\%/\Delta V_{OUT}$	$R_{EXT}=2045\Omega, V_{OUT}=1V\sim 2V$			± 0.1	%V
	Supply Voltage Regulation	$\%/\Delta V_{DD}$	$R_{EXT}=2045\Omega, V_{DD}=3.0V\sim 3.6V$			± 1	
Supply Current		I_{DD_OFF1}	R_{EXT} open, OUT15 ~ 0 off		2.1	3.1	mA
		I_{DD_OFF2}	$R_{EXT}=2045\Omega, OUT15 \sim 0$ off		6.2		
		I_{DD_ON}	$R_{EXT}=2045\Omega, OUT15 \sim 0$ on		7.1		


■ SWITCHING CHARACTERISTICS ($V_{DD}=5.0V$)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Delay Response Time (Low to High)	DCK to DAO	t_{pLH}	$R_{EXT}=872\Omega, V_{IH}=V_{DD}, V_{IL}=0, V_{LED}=5.0V, R_L=47\Omega, C_L=12pF$		33		ns
	LAT to OUT15~0	t_{pLH1}			53		
	ENB to OUT15~0	t_{pLH2}			52		
Delay Response Time (High to Low)	DCK to DAO	t_{pHL}			23		
	LAT to OUT15~0	t_{pHL1}			54		
	ENB to OUT15~0	t_{pHL2}			53		
Output Rise Time Of OUT Ports		t_{or}			45		
Output Fall Time Of OUT Ports		t_{of}			44		

■ SWITCHING CHARACTERISTICS ($V_{DD}=3.3V$)


PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Delay Response Time (Low to High)	DCK to DAO	t_{pLH}	$R_{EXT}=872\Omega, V_{IH}=V_{DD}, V_{IL}=0, V_{LED}=5.0V, R_L=47\Omega, C_L=12pF$		34		ns
	LAT to OUT15~0	t_{pLH1}			55		
	ENB to OUT15~0	t_{pLH2}			54		
Delay Response Time (High to Low)	DCK to DAO	t_{pHL}			26		
	LAT to OUT15~0	t_{pHL1}			56		
	ENB to OUT15~0	t_{pHL2}			55		
Output Rise Time Of OUT Ports		t_{or}			47		
Output Fall Time Of OUT Ports		t_{of}			46		

■ TEST CRICUIT FOR SWITCHING CHARACTERISTICS




■ TIMING WAVEFORM


1. DCK, DAI, DAO, LAT, ENB, OUT15:0




2. ENB, OUT15:0



■ SEQUENCE DIAGRAM



■ TYPICAL APPLICATION CIRCUIT



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.