



Connectors

Interface	Description	Type Number	Inner Contact Attachment	Outer Contact Attachment	Plating Code	Max. Length in (mm)	Max. Dia. in (mm)
N Male	Hex Head	L2PNM-H	Solder	Self-Flare	SG	2.1 (53)	0.94 (23.9)
N Male	Hex Head	L2PNM-HC	Captivated	Self-Flare	SG	2.1 (53)	0.94 (23.9)
N Female	-	L2PNF	Solder	Self-Flare	SG	2.4 (61)	0.63 (16.0)
N Female	Bulk Head	L2PNF-BH	Solder	Self-Flare	SG	2.4 (61)	0.88 (22.4)
4, 1/9.5 DIN	-	L2PKM-C	Captivated	Self-Flare	SS	1.9 (48)	0.95 (24.1)
4, 1/9.5 DIN	-	L2PKM	Solder	Self-Flare	SS	1.9 (48)	0.95 (24.1)
4, 1/9.5 DIN	Right Angle	L2PKR-C	Captivated	Self-Flare	SS	2.0/1.5 (50/38)	0.95 (24.1)
7-16 DIN Male	-	L2PDM-C	Captivated	Self-Flare	SS	1.9 (48)	1.1 (27.9)
7-16 DIN Female	-	L2PDF-C	Captivated	Self-Flare	SS	1.9 (48)	1.4 (35.6)
7-16 DIN Female	Panel Mount	L2PDF-PMC	Captivated	Self-Flare	SS	1.9 (48)	1.25 (31.8)
UHF Male	-	L42P	Solder	Self-Flare	BB	2.3 (58)	0.68 (17.3)
UHF Female	-	L42U	Solder	Self-Flare	BB	2.3 (58)	0.91 (23.1)
SMA Male	-	L42WS	Solder	Self-Flare	BG	2.2 (56)	0.68 (17.3)
TNC Male	-	L42EWT	Solder	Self-Flare	NG	2.1 (53)	0.68 (17.3)
TNC Female	-	L42ENT	Solder	Self-Flare	NG	1.9 (48)	0.68 (17.3)

Plating Codes: BB - Brass Body and Pin, BS - Brass Body and Silver Plated Pin, NG - Nickel Plated Body and Gold Plated Pin, SG - Silver Plated Body and Gold Plated Pin, SS - Silver Plated Body and Pin