

LC-X1265P



Labels will vary, see page 73 for example of labels.

Specifications

Nominal voltage		12V
Rated capacity (20 hour rate)		65Ah
Dimensions	Length	350 mm
	Width	166 mm
	Height	175 mm
	Total Height	175 mm
Approx. mass		20 kg


Characteristics

Capacity (note) (25°C)	20 hour rate (3.25A)	65Ah	
	10 hour rate (5.9A)	59Ah	
	5 hour rate (10.6A)	53Ah	
	1 hour rate (40A)	40Ah	
	1.5 hour rate discharge Cut-off voltage 10.5 V	26A	
Internal resistance	Fully charged battery (25°C)	Approx. 7mΩ	
Temperature dependency of capacity (20 hour rate)	40°C	102%	
	25°C	100%	
	0°C	85%	
	-15°C	65%	
Self discharge (25°C)	Residual capacity after standing 3 months	91%	
	Residual capacity after standing 6 months	82%	
	Residual capacity after standing 12 months	64%	
Charge Method (Constant Voltage)	Trickle use	Initial current	9.75 A or smaller
		Control voltage	13.6V to 13.8V (per 12V cell 25°C)


(Note) The above characteristics data are average values obtained within three charge/discharge cycles, not the minimum values.

For standby power supplies. Expected trickle life: Approx. 6 years at 25°C, Approx. 10 years at 20°C.

Dimensions (mm)



Discharge characteristics (25°C) (Note)



Duration of discharge vs. Discharge current (Note)

