





12 x 2 Character LCD



FEATURES

• Type: Character







• Duty cycle: 1/16

• 5 x 8 dots includes cursor

• + 5 V power supply

• LED can be driven by pin 1, pin 2, or A and K

 Material categorization: For definitions of compliance please see www.vishay.com/doc?99912

MECHANICAL DATA							
ITEM	STANDARD VALUE	UNIT					
Module Dimension	55.7 x 32.0						
Viewing Area	46.0 x 14.5						
Dot Size	0.45 x 0.60	mm					
Dot Pitch	0.55 x 0.70] """					
Mounting Hole	31.2 x 30.0						
Character Size	2.65 x 5.50						

ABSOLUTE MAXIMUM RATINGS									
ITEM	CVMPOL	STAN	LINIT						
ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT				
Power Supply	V _{DD} to V _{SS}	- 0.3	-	7.0	V				
Input Voltage	VI	- 0.3	-	V_{DD}	V				

Note

• $V_{SS} = 0 \text{ V}, V_{DD} = 5.0 \text{ V}$

ELECTRICAL CHARACTERISTICS								
ITEM	SYMBOL	CONDITION	ST	STANDARD VALUE				
	STWIBOL	CONDITION	MIN. TYP.		MAX.	UNIT		
Input Voltage	V_{DD}	$V_{DD} = + 5 V$	4.7	5.0	5.3	V		
Supply Current	I _{DD}	$V_{DD} = + 5 V$	-	1.3	1.5	mA		
Recommended LC Driving Voltage for Normal Temperature Version Module		- 20 °C	4.9	5.2	5.5			
		0 °C	4.5	4.8	5.1			
	V_{DD} to V_{0}	25 °C	4.1	4.4	4.7	V		
		50 °C	3.8	4.2	4.4			
		70 °C	3.5	4.0	4.1			
LED Forward Voltage	V _F	25 °C	-	4.2	4.6	V		
LED Forward Current	I _F	25 °C	-	40	80	mA		

OPTIONS	OPTIONS									
		PROCES	S COLOR		BACKLIGHT					
TN	STN Gray	STN Yellow	STN Blue	FSTN B&W	STN Color	None	LED	EL	CCFL	
Х	Х	х	Х	Х		х	Х	х		


For detailed information, please see the "Product Numbering System" document.



www.vishay.com

DISPLAY CHAR	DISPLAY CHARACTER ADDRESS CODE											
Display Position												
	1	2	3	4	5	6	7	8	9	10	11	12
DD RAM Address	00	01	02	03	04	05	06	07	08	0A	0B	0C
DD RAM Address	40	41	42	43	44	45	46	47	48	4A	4B	4C

INTERFACE PIN FUNCTION							
PIN NO.	SYMBOL	FUNCTION					
1	V _{SS}	Ground					
2	V _{DD}	+ 5 V					
3	V ₀	Contrast adjustment					
4	RS	H/L register select signal					
5	R/W	H/L read/write signal					
6	Е	$H \rightarrow L$ enable signal					
7	DB0	H/L data bus line					
8	DB1	H/L data bus line					
9	DB2	H/L data bus line					
10	DB3	H/L data bus line					
11	DB4	H/L data bus line					
12	DB5	H/L data bus line					
13	DB6	H/L data bus line					
14	DB7	H/L data bus line					
15	A/V _{EE}	4.2 V for LED ($R_A = 0 \Omega$)/negative voltage output					





Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.