

2.2 Common Anode 0.56 Inch (14.20mm)

PRODUCT DESCRIPTION	
(1) Double Digit 0.56 Inch (14.20mm) Height	(5) Gray or black color background
(2) Low current operation	(6) Common Anode
(3) Excellent color and font characteristics	(7) RoHs Compliant Part
(4) Colors: White, blue, red, yellow and green	

Absolute Maximum Rating (Ta = 25°C)

PARAMETER	RED	AMBER	GREEN	BLUE	WHITE	UNITS
DC Forward Current Per Segment	30	30	25	30	20	mA
Peak Current Per Segment ⁽¹⁾	70	50	50	25	25	mA
Avg. Forward Current (Pulse Operation) Per Segment	30	30	25	25	25	mA
Derating Linear From 25°C Per Segment	0.3					mA/°C
Reverse Voltage ⁽²⁾	3					V
Operating Temperature	-25 to +85					°C
Storage Temperature	-30 to +85					°C

(1) Pulse conditions of 1/10 duty and 0.1msec width, for long operating life, max. of 20mA recommended

(2) Reverse biasing of the dot matrix is not recommend, will cause damage to the leds

Electro-optical Characteristics (Ta = 25°C)

PART NUMBER	DICE MATERIAL (COLOR)	PEAK WAVELENGTH (nm)	MAX. REVERSE CURRENT / SEGMENT (A)	VF (V) TYP	VF (V) MAX.	LUMINOUS INTENSITY / SEGMENT AVERAGE (IF = 10mA)
LEDD5622AUR11	AlGaAs Red	660	10	1.8	2.3	20,000 ucd
LEDD5622TB11	InGaN Blue	468	10	3.3	4.0	30,000 ucd
LEDD5622YG11	GaP Green	568	10	1.9	2.3	20,000 ucd
LEDD5622UY11	AllnGaP Amber	590	10	1.8	2.3	22,000 ucd
LEDD5622TW11	InGaN White	5,500K	10	3.3	4.0	30,000 ucd

DEVICE DIAGRAM

PIN		PIN		PIN		PIN	
1	Cathode E1	6	Cathode D2	11	Cathode A2	16	Cathode A1
2	Cathode D1	7	Cathode G2	12	Cathode F2	17	Cathode G1
3	Cathode C1	8	Cathode C2	13	Common Anode 2	18	Cathode F1
4	Cathode DP1	9	Cathode DP1	14	Common Anode 1		
5	Cathode E2	10	Cathode B2	15	Cathode B1		

